



Make any size gasket with **LOCTITE® 518 Flange Sealant**

Prevent rust and seizure of power end bolts with **LOCTITE® LB 8009 Heavy Duty Anti-Seize**

Prevent fretting corrosion while securing bearings with **LOCTITE® 638 Retaining Compound**

Rebuild and protect worn volutes with **LOCTITE® PC 7226 Pneu Wear** and/or **LOCTITE® PC 7227 Brushable Ceramic**

Prevent key wallow with **LOCTITE® 243 Medium Strength Threadlocker**

Repair key wallow with **LOCTITE® 660 Retaining Compound**

Prevent corrosion in pump housing and on impeller vanes; restore surface after wear and cavitation with **LOCTITE® PC 7227 Brushable Ceramic**

Prevent set screws from working loose with **LOCTITE® 222 Threadlocker** or **LOCTITE® 243 Threadlocker** (depending on fastener size)

Prevent corrosion and seizure of gland assembly nuts, and seizure of the impeller to the shaft with **LOCTITE® LB 8009 Heavy Duty Anti-Seize**

Rebuild worn shafts with **LOCTITE® EA 3478 Superior Metal**

Secure and prevent leakage between oil seals and housing with **LOCTITE® 243 Medium Strength Threadlocker** or **LOCTITE® 248 Medium Strength Threadlocker Stick**

Seal and protect flushing connectors with **LOCTITE® 567, 577 Thread Sealant**

Lubricate and prevent damage to O-rings with **LOCTITE® 8801 Silicone Lubricant**

Seal threaded fittings with **LOCTITE® 567 or 577 Thread Sealants**

Prevent corrosion and secure casing bolts and adapter bolts with **LOCTITE® 243 Medium Strength Threadlocker**

Keep mounting bolts tight with **LOCTITE® 290 Wicking Grade Threadlocker** or **LOCTITE® 263 High Strength Threadlocker**