



# FLOOR MARKING SIGNS

## INSTALLATION/REMOVAL INSTRUCTIONS

- ▶ **Made of a durable vinyl, adhering to clean, dry surfaces**
- ▶ **300mm in diameter**
- ▶ **Tough 0.6mm clear anti-slip over laminate**
- ▶ **Suitable for indoor use and heavy traffic area**

Safety Floor Markers are designed to provide warnings or instructions on floors. Brady's Floor Markers also come with a 0.6mm tough clear textured anti-slip over laminate to prevent accidents in a heavy foot traffic area such as warehouse and manufacturing facility.

Markers are made of a durable vinyl, with a heavy-duty pressure-sensitive adhesive that can adhere to many different clean and dry surfaces. They measure 300mm in diameter, providing plenty of warning within your facility.

### FLOOR MARKER INSTALLATION INSTRUCTIONS:

1. Ensure area is clean and free from dust and debris
2. Use a mop and some detergent to clean surface thoroughly
3. Allow time for surface to completely dry before continuing
4. Peel the protective backing off of the floor marker and lay it down at the installation point
5. Apply pressure evenly over the entire floor marker surface

### FLOOR MARKER REMOVAL INSTRUCTIONS:

1. Using a scraper if necessary, begin lifting the marker slowly from a chosen point
2. Pull the label back towards you at a 90° angle or less
3. Slowly continue this process until the removal is complete, cutting off portions where needed
4. If the sign is not lifting with ease, it is recommended that the decal is heated
5. Once the decal has been removed, wash the area with warm water, wipe down with a cloth and allow to dry

If any residue remains, you can use the following methods to help soften the adhesive: • Vinegar and warm water • Hand sanitiser/alcohol • Olive Oil

