

Diesel Nozzle Auto - Slim Profile

L-SFNAD60



The Lubemate Slim Profile Automatic Diesel Nozzle is built for reliable, high-performance fuel dispensing. Designed for durability and ease of use, it features a lightweight yet robust construction for effortless handling. Its auto shut-off function ensures spill-free refueling, preventing overfills for added safety. Perfect for demanding diesel applications, this slim profile diesel nozzle delivers efficiency and dependability.

Aluminium Body

Lightweight yet durable and strong

Equipped with a Swivel

Eases installation and prevents hose twisting



Automatic Shut-off

Prevent overspills & wastage

Trigger Lock

Allows flow control in 2 positions

TECHNICAL SPECIFICATIONS

-  Flow Rate: up to 60 LPM
-  Inlet: 3/4" BSPT (F)
-  Outlet Spout Diameter: 15/16"
-  Suitable Fluids: Diesel & Kerosene
-  Maximum Working Pressure: 50 PSI

RANGE OF 3/4" FUEL NOZZLES

L-FNAD	Automatic Diesel Nozzle 60 LPM (BSPT)
L-FNAD-P	Automatic Diesel Nozzle 60 LPM (BSPP)
L-FNADP	Auto Diesel Nozzle Premium 60 LPM (BSPT)
L-FNADP-P	Auto Diesel Nozzle Premium 60 LPM (BSPP)

APPLICATIONS:

- Automotive Workshops
- Trucks & Buses
- Mining
- Agriculture
- Construction Machinery
- Earthmoving Equipments
- Marine
- Industrial

*This nozzle is not intended for use at service stations (servo) / fuel stations or gas stations



Lubemate® is a practical, cost-effective range of equipment brought to you by the trusted team at Macnaught®. All Lubemate products are specially selected by our experienced technical team at Macnaught, ensuring they meet our strict quality standards. AU: Macnaught Pty Ltd 41-49 Henderson St, Turrella NSW 2205. Ph: 1800 185 102 Fax: +61 2 9597 7773 Email: info@macnaught.com.au Website: macnaught.com. NZ: Macnaught NZ 2/1 Hautu Drive, Wiri Auckland Macnaught Pty Ltd Ph: 0800 023 510 Email: nzorders@macnaught.com.au