

Safety Data Sheet

LOCTITE 510 GASKET ELIMINATOR known as Loctite 510 50ML AU

Page 1 of 9

SDS No.: 153499 V001.3

Date of issue: 16.10.2020

Section 1. Identification of the substance/preparation and of the company/undertaking

Product name: LOCTITE 510 GASKET ELIMINATOR known as Loctite 510 50ML AU

Intended use: Anaerobic Sealant

Supplier:

Henkel Australia Pty Ltd 135-141 Canterbury Road Kilsyth, Victoria, 3137 Australia

Phone: +61 (3) 9724 6444

24 HOUR EMERGENCY CONTACT NUMBER: 1800 032 379 **Emergency information:**

Section 2. Hazards identification

Classification of the substance or mixture

Hazardous according to the criteria of Safe Work Australia.

GHS Classification:

Hazard Class Hazard Category Target organ

Serious eye irritation Category 2A Skin sensitizer Category 1 Target Organ Systemic Toxicant -Category 3

Single exposure

Acute hazards to the aquatic

environment

respiratory tract irritation

Hazard pictogram:

Category 3

Signal word: Warning SDS No.: 153499

V001.3

LOCTITE 510 GASKET ELIMINATOR known as

Loctite 510 50ML AU

Hazard statement(s): H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation. H335 May cause respiratory irritation.

H402 Harmful to aquatic life.

Precautionary Statement(s):

Prevention: P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling. P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves, eye protection, and face protection.

Response: P302+P352 IF ON SKIN: Wash with plenty of water.

P304+P340+P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

Storage: P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal: P501 Dispose of contents/container to an appropriate treatment and disposal facility in

accordance with applicable laws and regulations.

Dangerous Goods information:

Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

Section 3. Composition / information on ingredients

General chemical description: Mixture

Type of preparation: Anaerobic Sealant

Identity of ingredients:

Chemical ingredients	CAS-No.	Proportion
Polyethylene glycol 200 dimethacrylate	25852-47-5	10- < 50 %
1,1'-(methylenedi-p-phenylene)bismaleimide	13676-54-5	1- < 10 %
α, α-dimethylbenzyl hydroperoxide	80-15-9	1- < 3 %
Propane-1,2-diol	57-55-6	< 10 %
non hazardous ingredients~		40-<100 %

Section 4. First aid measures

Ingestion: Do not induce vomiting.

Rinse out mouth. Do not drink.

Seek medical advice.

Skin: Rinse with running water and soap.

Seek medical advice.

Page 3 of 9

SDS No.: 153499 V001.3

LOCTITE 510 GASKET ELIMINATOR known as

Loctite 510 50ML AU

Eyes: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Seek medical advice.

Inhalation: Move to fresh air.

Seek medical advice.

First Aid facilities: Eye wash and safety shower

Normal washroom facilities

Medical attention and special

treatment:

Treat symptomatically and supportively.

Section 5. Fire fighting measures

Suitable extinguishing media: Carbon dioxide, foam, powder

Decomposition products in case of

fire:

Thermal decomposition can lead to release of irritating gases and vapors.

Oxides of carbon, oxides of nitrogen, irritating organic vapors.

Particular danger in case of fire: Do not expose to direct heat.

Special protective equipment for

fire-fighters:

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional fire fighting advice: In case of fire, keep containers cool with water spray.

Collect contaminated fire fighting water separately. It must not enter drains.

Section 6. Accidental release measures

Personal precautions: Avoid skin and eye contact.

Wear protective equipment. Ensure adequate ventilation. See advice in section 8

Environmental precautions: Do not let product enter drains.

Clean-up methods: For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for

disposal.

Section 7. Handling and storage

Precautions for safe handling: Use only in well-ventilated areas.

Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation.

Avoid skin and eye contact.

Conditions for safe storage: Store in original containers at 8-21°C (46.4-69.8°F) and do not return residual materials to

containers as contamination may reduce the shelf life of the bulk product.

Section 8. Exposure controls / personal protection

LOCTITE 510 GASKET ELIMINATOR known as

Loctite 510 50ML AU

National exposure standards:

Ingredient [Regulated substance]	form of exposure	TWA (ppm)	TWA (mg/m3)	Peak Limit. (ppm)	Peak Limit. (mg/m3)	STEL (ppm)	STEL (mg/m3)
SILICA, AMORPHOUS: FUMED SILICA (RESPIRABLE DUST) 112945-52-5	Respirable dust.		2				
FUMED SILICA (RESPIRABLE DUST) 112945-52-5	Respirable dust.		2				
PROPANE-1,2-DIOL TOTAL: (VAPOUR & PARTICULATES) 57-55-6	Total vapour and particulates.	150	474				
PROPANE-1,2-DIOL: PARTICULATES ONLY 57-55-6	Particulate.		10				

Provide adequate local exhaust ventilation to maintain worker exposure below exposure **Engineering controls:**

limits.

Eye protection: Wear protective glasses.

Skin protection: Wear suitable protective clothing.

Suitable protective gloves. Butyl rubber gloves.

Please note that in practice the working life of chemical resistant gloves may be considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed

then the gloves should be replaced.

Use only in well-ventilated areas. Respiratory protection:

If inhalation risk exists, wear a respirator or air supplied mask complying with the

requirements of AS/NZS 1715 and AS/NZS 1716.

Section 9. Physical and chemical properties

Appearance: Pink Gel

Odor: Mild Specific gravity: 1.1784

> 150 °C (> 302 °F) **Boiling point:** Flash point: > 93.3 °C (> 199.94 °F)

Vapor pressure: (; 27 °C (80.6 °F)) < 5 mm hg

Density: 1.178 g/cm3 Solubility in water: Slightly soluble

200,000 - 700,000 mPa.s Viscosity (dynamic):

(BROOKFIELD WITH HELIPATH; Instrument: HBT; speed of rotation: 2.5 min-1; Spindle No: TC; Method: ;; LCT STM 10; Viscosity Brookfield)

VOC content: < 3 %

(2010/75/EC)

Section 10. Stability and reactivity

Stability: Stable under recommended storage conditions.

Page 5 of 9

SDS No.: 153499 V001.3

LOCTITE 510 GASKET ELIMINATOR known as Loctite 510 50ML AU

Conditions to avoid: Avoid contact with incompatible substances, excessive heat, flames or other ignition

sources.

Incompatible materials: Reaction with strong acids.

Reacts with strong oxidants.

Hazardous decomposition

products:

Thermal decomposition can lead to release of irritating gases and vapors.

Irritating organic vapours.

carbon oxides. Sulphur oxides nitrogen oxides

Section 11. Toxicological information

Health Effects:

Ingestion: May cause gastrointestinal irritation with nausea, vomiting and diarrhea.

Skin: May cause mild skin irritation.

Contact with skin can cause irritation and allergic reaction (sensitization) in some individuals.

Eyes: Causes serious eye irritation.

Symptoms may include severe irritation, pain, tearing, blurred vision.

Inhalation: Irritates the nose, throat and respiratory system.

Can cause nausea and respiratory irritation, dizziness, weakness, fatigue, headache, narcosis, loss

of appetite and possible unconsciousness.

Acute toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time		
Polyethylene glycol 200 dimethacrylate 25852-47-5	LD50	> 5,000 mg/kg	oral		rat	not specified
1,1'-(methylenedi-p-	LD50	> 2,000 mg/kg	oral		rat	OECD Guideline 423 (Acute
phenylene)bismaleimide	LC50	0.515 - 1 mg/l	inhalation	4 h	rat	Oral toxicity)
13676-54-5	LD50	> 5,400 mg/kg	dermal		rat	OECD Guideline 436 (Acute
						Inhalation Toxicity: Acute
						Toxic Class (ATC) Method)
						not specified
α, α-dimethylbenzyl	LD50	382 mg/kg	oral		rat	other guideline:
hydroperoxide	LD50	530 - 1,060			rat	other guideline:
80-15-9	Acute	mg/kg	dermal			Expert judgement
	toxicity	1,100 mg/kg	dermal			
	estimate					
	(ATE)					
Propane-1,2-diol	LD50	22,000 mg/kg	oral		rat	not specified
57-55-6	LC50	> 317.042 mg/l	inhalation	2 h	rabbit	not specified
	LD50	> 2,000 mg/kg	dermal		rabbit	not specified

Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
α, α-dimethylbenzyl hydroperoxide 80-15-9	corrosive		rabbit	Draize Test
Propane-1,2-diol 57-55-6	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

LOCTITE 510 GASKET ELIMINATOR known as Loctite 510 50ML AU

Serious eye damage/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
1,1'-(methylenedi-p- phenylene)bismaleimide 13676-54-5	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Propane-1,2-diol 57-55-6	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
1,1'-(methylenedi-p- phenylene)bismaleimide 13676-54-5	sensitising	Guinea pig maximisat ion test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Propane-1,2-diol 57-55-6	not sensitising	Guinea pig maximisat ion test	guinea pig	equivalent or similar to OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
1,1'-(methylenedi-p- phenylene)bismaleimide 13676-54-5	negative	in vitro mammalian cell micronucleus test	with and without		OECD Guideline 487 (In vitro Mammalian Cell Micronucleus Test)
α, α-dimethylbenzyl hydroperoxide 80-15-9	positive	bacterial reverse mutation assay (e.g Ames test)	without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
α, α-dimethylbenzyl hydroperoxide 80-15-9	negative	dermal		mouse	not specified
Propane-1,2-diol 57-55-6	negative negative	bacterial reverse mutation assay (e.g Ames test) in vitro mammalian chromosome aberration test	without with and without		Ames Test OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Propane-1,2-diol 57-55-6	negative negative negative	oral: gavage intraperitoneal oral: gavage		rat mouse rat	not specified not specified not specified

Repeated dose toxicity:

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
α, α-dimethylbenzyl hydroperoxide 80-15-9		inhalation: aerosol	6 h/d5 d/w	rat	not specified
Propane-1,2-diol 57-55-6	NOAEL=1,700 mg/kg	oral: feed	2 yearsdaily	rat	not specified
Propane-1,2-diol 57-55-6	NOAEL=1000 mg/m3	inhalation	90 d6 h/d, 5 d/w	rat	not specified

Section 12. Ecological information

LOCTITE 510 GASKET ELIMINATOR known as Loctite 510 50ML AU

General ecological information:

Cured Loctite products are typical polymers and do not pose any immediate environmental hazards., Precautions required with respect to Environmental Hazards of articles in which this product is used should be considered., Do not empty into drains / surface water / ground water.

Ecotoxicity:

Harmful to aquatic life.

Toxicity:

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
Polyethylene glycol 200	LC50	> 10 - 100 mg/l	Fish	96 h	not specified	OECD Guideline
dimethacrylate 25852-47-5 Polyethylene glycol 200 dimethacrylate 25852-47-5	EC0	> 10 - 100 mg/l	Bacteria	3 h	not specified	203 (Fish, Acute Toxicity Test) OECD Guideline 209 (Activated Sludge, Respiration
1,1'-(methylenedi-p- phenylene)bismaleimide 13676-54-5	LC50	Toxicity > Water solubility	Fish	96 h	Carassius sp.	Inhibition Test) OECD Guideline 203 (Fish, Acute Toxicity Test)
1,1'-(methylenedi-p- phenylene)bismaleimide 13676-54-5	EC50	Toxicity > Water solubility	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
1,1'-(methylenedi-p- phenylene)bismaleimide 13676-54-5	NOEC	Toxicity > Water solubility	Algae	72 h	Pseudokirchneriella subcapitata	/
1,1'-(methylenedi-p- phenylene)bismaleimide 13676-54-5	EC50	Toxicity > Water solubility	Algae	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
1,1'-(methylenedi-p- phenylene)bismaleimide 13676-54-5	EC50	Toxicity > Water solubility	Bacteria	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline
α, α-dimethylbenzyl hydroperoxide 80-15-9	LC50	3.9 mg/l	Fish	96 h	Oncorhynchus mykiss	Inhibition Test) OECD Guideline 203 (Fish, Acute Toxicity Test)
α, α-dimethylbenzyl hydroperoxide 80-15-9	EC50	18 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation
α, α-dimethylbenzyl hydroperoxide 80-15-9	ErC50	3.1 mg/l	Algae	72 h	Pseudokirchneriella subcapitata	Test) OECD Guideline 201 (Alga, Growth Inhibition Test)
α, α-dimethylbenzyl hydroperoxide 80-15-9	EC10	70 mg/l	Bacteria	30 min		not specified
Propane-1,2-diol 57-55-6	LC50	> 10,000 mg/l	Fish	48 h	Leuciscus idus	DIN 38412-15
Propane-1,2-diol 57-55-6	EC50	18,340 mg/l	Daphnia	48 h	Ceriodaphnia dubia	other guideline:
Propane-1,2-diol 57-55-6	EC50	24,200 mg/l	Algae	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth
Propane-1,2-diol 57-55-6	NOEC	15,000 mg/l	Algae	14 d	Pseudokirchneriella subcapitata	Inhibition Test) OECD Guideline 201 (Alga, Growth
Propane-1,2-diol 57-55-6	EC50	> 1,000 mg/l	Bacteria	3 h	activated sludge	Inhibition Test) OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

Persistence and degradability:

Hazardous components	Result	Route of	Degradability	Method
CAS-No.		application		

LOCTITE 510 GASKET ELIMINATOR known as Loctite 510 50ML AU

Polyethylene glycol 200 dimethacrylate 25852-47-5	readily biodegradable	aerobic	> 60 %	OECD 301 A - F
1,1'-(methylenedi-p- phenylene)bismaleimide 13676-54-5	not readily biodegradable.	aerobic	0 %	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
α, α-dimethylbenzyl hydroperoxide 80-15-9		no data	0 %	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Propane-1,2-diol 57-55-6	not inherently biodegradable	aerobic	60 %	OECD Guideline 302 B (Inherent biodegradability: Zahn- Wellens/EMPA Test)
Propane-1,2-diol 57-55-6	readily biodegradable	aerobic	> 81.7 - 100 %	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)

Bioaccumulative potential / Mobility in soil:

Hazardous components	LogPow	Bioconcentration	Exposure	Species	Temperature	Method
CAS-No.		factor (BCF)	time			
1,1'-(methylenedi-p-	1.5				25 °C	OECD Guideline 117
phenylene)bismaleimide						(Partition Coefficient (n-
13676-54-5						octanol / water), HPLC
						Method)
α, α-dimethylbenzyl		9.1		calculation		OECD Guideline 305
hydroperoxide						(Bioconcentration: Flow-
80-15-9						through Fish Test)
α, α-dimethylbenzyl	2.16					not specified
hydroperoxide						
80-15-9						
Propane-1,2-diol	-1.07				20.5 °C	EU Method A.8 (Partition
57-55-6						Coefficient)

Section 13. Disposal considerations

Waste disposal of product: Dispose of in accordance with local and national regulations.

Contribution of this product to waste is very insignificant in comparison to article in

which it is used

Disposal for uncleaned package: After use, tubes, cartons and bottles containing residual product should be disposed of as

chemically contaminated waste in an authorised legal land fill site or incinerated.

Section 14. Transport information

Road and Rail Transport:

Dangerous Goods information: Not classified as Dangerous Goods according to the criteria of the

Australian Code for the Transport of Dangerous Goods by Road and

Rail (ADG Code).

Marine transport IMDG:

Not dangerous goods

Air transport IATA:

Not dangerous goods

Section 15. Regulatory information

SUSMP Poisons Schedule

None

Page 9 of 9

SDS No.: 153499 V001.3

LOCTITE 510 GASKET ELIMINATOR known as Loctite 510 50ML AU

AICS: All components are listed or are exempt from listing on the Australian Inventory of

Chemical Substances (AICS).

Section 16. Other information

Abbreviations/acronyms: ADGC - Australian Dangerous Goods Code

GHS: Globally Harmonized System CAS: Chemical Abstracts Service

OECD: Organization for Economic Cooperation and Development

NOAEL: No Observed Adverse Effect Level

LD 50: Lethal Dose 50%

LC 50: Lethal Concentration 50%

IMDG: International Maritime Dangerous Goods code

STEL - Short term exposure limit TWA - Time weighted average

IATA-DGR: International Air Transport Association - Dangerous Goods Regulations

Reason for issue: Reviewed SDS. Reissued with new date. involved chapters: 2,3,5,8,9,12,16

Date of previous issue: 19.11.2015

Disclaimer:

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel Australia Pty. Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel Australia Pty. Limited concerning the properties of the material.

The information contained in the Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel Australia Pty. Limited assumes no legal responsibility for reliance upon same. Henkel Australia Pty. Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Safety Data Sheet.

This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by either Commonwealth or State statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.

No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.