

Safety Data Sheet

LOCTITE 660 RETAINING COMPOUND

SDS No.: 164196

Page 1 of 10

V001.6

Date of issue: 19.10.2021

respiratory tract irritation

Section 1. Identification of the substance/preparation and of the company/undertaking

Product name: LOCTITE 660 RETAINING COMPOUND

Intended use: Anaerobic Adhesive

Supplier:

Henkel Australia Pty Ltd 135-141 Canterbury Road Kilsyth, Victoria, 3137 Australia

Phone: +61 (3) 9724 6444

Emergency information: 24 HOUR EMERGENCY CONTACT NUMBER: 1800 032 379

Section 2. Hazards identification

Classification of the substance or mixture

Hazardous according to the criteria of Safe Work Australia.

GHS Classification:

<u>Hazard Class</u> <u>Hazard Category</u> <u>Target organ</u>

Serious eye irritation Category 2A
Serious eye damage Category 1
Skin sensitizer Category 1
Target Organ Systemic Toxicant - Category 3

Single exposure

Respiratory sensitizer Category 1 Chronic hazards to the aquatic Category 4 environment

Hazard pictogram:



Signal word: Warning

SDS No.: 164196 V001.6

LOCTITE 660 RETAINING COMPOUND

Hazard statement(s): H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation. H335 May cause respiratory irritation.

H413 May cause long lasting harmful effects to aquatic life.

Precautionary Statement(s):

Prevention: P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling. P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves, eye protection, and face protection.

Response: P302+P352 IF ON SKIN: Wash with plenty of water.

P304+P340+P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

Storage: P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal: P501 Dispose of contents/container to an appropriate treatment and disposal facility in

accordance with applicable laws and regulations.

Dangerous Goods information:

Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

Section 3. Composition / information on ingredients

General chemical description: Mixture

Type of preparation: Anaerobic Sealant

Identity of ingredients:

Chemical ingredients	CAS-No.	Proportion
Methacrylic acid, monoester with propane-1,2-diol	27813-02-1	30- < 60 %
Silica, amorphous, fumed, crystfree	112945-52-5	< 10 %
α, α-dimethylbenzyl hydroperoxide	80-15-9	1- < 3 %
maleic acid	110-16-7	0.1-< 1 %
Acetic acid, 2-phenylhydrazide	114-83-0	< 1 %

Section 4. First aid measures

Ingestion: Rinse mouth, do not induce vomiting, consult a doctor.

Seek medical advice.

Skin: Rinse with running water and soap.

Seek medical advice.

SDS No.: 164196 V001.6

LOCTITE 660 RETAINING COMPOUND

Eyes: Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if

necessary.

Inhalation: Move to fresh air. If symptoms persist, seek medical advice.

Section 5. Fire fighting measures

Suitable extinguishing media: Foam, dry chemical or carbon dioxide.

 $\label{lem:case of optimization} \textbf{Decomposition products in case of} \quad \text{Oxides of carbon}.$

fire:

Oxides of sulfur. Oxides of nitrogen. Irritating organic vapours.

Particular danger in case of fire: None

 $S\,pecial\,protective\,equipment\,for$

fire-fighters:

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Section 6. Accidental release measures

Personal precautions: Avoid skin and eye contact.

See advice in section 8

Environmental precautions: Do not let product enter drains.

Clean-up methods: For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for

disposal.

Section 7. Handling and storage

Precautions for safe handling: Use only in well-ventilated areas.

Avoid skin and eye contact.

Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation.

Conditions for safe storage: Store in original containers at 8-21°C (46.4-69.8°F) and do not return residual materials to

containers as contamination may reduce the shelf life of the bulk product.

Section 8. Exposure controls / personal protection

National exposure standards:

In gredient [Regulated substance]	form of exposure	TWA (ppm)	TWA (mg/m3)		Peak Limit. (mg/m3)	STEL (ppm)	STEL (mg/m3)
SILICA, AMORPHOUS: FUMED SILICA (RESPIRABLE DUST) 112945-52-5	Respirable dust.		2	(ppm)	(mg/me)		(mg/mc)
FUMED SILICA (RESPIRABLE DUST) 112945-52-5	Respirable dust.		2				
Nuisance dusts, inhalable dust 112945-52-5	Inhalable dust.		10				

SDS No.: 164196 LOCTITE 660 RETAINING COMPOUND

V001.6

Engineering controls: Local exhaust ventilation is recommended when general ventilation is not sufficient to

control airborne contamination below occupational exposure limits.

Eye protection: Wear protective glasses.

Skin protection: Wear suitable protective clothing.

Avoid skin-contact.

Nitrile rubber gloves should be worn.

Please note that in practice the working life of chemical resistant gloves may be considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed

then the gloves should be replaced.

Respiratory protection: Use only in well-ventilated areas.

If inhalation risk exists, wear a respirator or air supplied mask complying with the

requirements of AS/NZS 1715 and AS/NZS 1716.

Section 9. Physical and chemical properties

Appearance: grey paste Odor: characteristic

Specific gravity:

> 149 °C (> 300.2 °F) **Boiling point:** > 93 °C (> 199.4 °F) Flash point:

(Tagliabue closed cup)

Density: 1.098 g/cm3 Solubility in water: Negligible

Section 10. Stability and reactivity

Stability: Stable under recommended storage conditions.

Incompatible materials: Reacts with strong oxidants.

Hazardous decomposition

products:

May produce fumes when heated to decomposition. Fumes may contain carbon monoxide

and other toxic fumes.

Section 11. Toxicological information

Page 5 of 10

SDS No.: 164196 V001.6

LOCTITE 660 RETAINING COMPOUND

Health Effects:

Ingestion:May be harmful if swallowed.Skin:May cause allergic skin reaction.Eyes:Causes serious eye damage.Inhalation:May cause respiratory tract irritation.

Acute toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time		
Methacrylic acid,	LD50	$> 2,000 \mathrm{mg/kg}$	oral		rat	OECD Guideline 401 (Acute
monoester with propane-	LD50	$> 5,000 \mathrm{mg/kg}$			rabbit	Oral Toxicity)
1,2-diol			dermal			not specified
27813-02-1						
Silica, amorphous, fumed,	LD50	> 5,000 mg/kg	oral		rat	OECD Guideline 401 (Acute
crystfree	LC0	0.139 mg/l	inhalation	4 h	rat	Oral Toxicity)
112945-52-5	LD50	$> 2,000 \mathrm{mg/kg}$	dermal		rabbit	not specified
						OECD Guideline 402 (Acute
						Dermal Toxicity)
α, α-dimethylbenzyl	LD50	382 mg/kg	oral		rat	other guideline:
hydroperoxide	LC50	1.370 mg/l	inhalation	4 h	rat	not specified
80-15-9	LD50	530 - 1,060	dermal		rat	other guideline:
	Acute	mg/kg	dermal			Expert judgement
	toxicity	1,100 mg/kg				
	estimate					
	(ATE)					
maleic acid	LD50	708 mg/kg	oral		rat	not specified
110-16-7	LD50	1,560 mg/kg			rabbit	not specified
			dermal			_
Acetic acid, 2-	LD50	270 mg/kg	oral		rat	not specified
phenylhydrazide						_
114-83-0						

Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1	not irritating	24 h	rabbit	Draize Test
Silica, amorphous, fumed, crystfree 112945-52-5	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
α, α-dimet hylbenzyl hydroperoxide 80-15-9	corrosive		rabbit	Draize Test
maleic acid 110-16-7	irritating	24 h	human	Patch Test

Serious eye damage/irritation:

Hazardous components	Result	Exposure	Species	Method
CAS-No.		time		
Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1	irritating		rabbit	Draize Test
Silica, amorphous, fumed, crystfree 112945-52-5	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
maleic acid 110-16-7	highly irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Page 6 of 10

LOCTITE 660 RETAINING COMPOUND

Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1	sensitising	Guinea pig maximisat ion test	guinea pig	not specified
maleic acid 110-16-7	sensitising	Mouse local lymphnod e assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
maleic acid 110-16-7	sensitising	Mouse local lymphnod e assay (LLNA)	guinea pig	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study/ Route of administration	Metabolic activation / Exposure time	Species	Method
Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1	negative negative	bacterial reverse mutation assay (e.g Ames test) mammalian cell gene mutation assay	with and without with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay) OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1	negative	oral: gavage		rat	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Silica, amorphous, fumed, crystfree 112945-52-5	negative negative negative	bacterial reverse mutation assay (e.g Ames test) in vitro mammalian chromosome aberration test DNA damage and repair assay, unscheduled DNA synthesis in mammalian cells in vitro			not specified not specified not specified
α, α-dimet hylbenzyl hydroperoxide 80-15-9	positive	bacterial reverse mutation assay (e.g Ames test)	without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
α, α-dimethylbenzyl hydroperoxide 80-15-9	negative	dermal		mouse	not specified
maleic acid 110-16-7	negative negative	bacterial reverse mutation assay (e.g Ames test) mammalian cell gene mutation assay	no data with and without		Ames Test OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)

Page 7 of 10

SDS No.: 164196

V001.6

LOCTITE 660 RETAINING COMPOUND

Repeated dose toxicity:

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1	NOAEL=300 mg/kg	oral: gavage		rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
α, α-dimethylbenzyl hydroperoxide 80-15-9		inhalation: aerosol	6 h/d5 d/w	rat	not specified
maleic acid 110-16-7	NOAEL=>= 40 mg/kg	oral: feed	90 ddaily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

Section 12. Ecological information

LOCTITE 660 RETAINING COMPOUND

General ecological information:

Do not empty into drains $\mbox{/}$ surface water $\mbox{/}$ ground water., May cause long-term adverse effects in the aquatic environment.

Toxicity:

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	LC50	493 mg/l	Fish	48 h	Leuciscus idus melanotus	DIN 38412-15
Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	EC50	> 143 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	EC50	> 97.2 mg/l	Algae	72 h	Pseudokirchneriella subcapitata	/
Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	NOEC	> 97.2 mg/l	Algae	72 h	Pseudokirchneriella subcapitata	
Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	EC10	1,140 mg/l	Bacteria	16 h		not specified
Silica, amorphous, fumed, crystfree 112945-52-5	LC50	> 10,000 mg/l	Fish	96 h	Brachydanio rerio (new name: Danio rerio)	OECD Guideline 203 (Fish, Acute Toxicity Test)
α, α-dimethylbenzyl hydroperoxide 80-15-9	LC50	3.9 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
α, α-dimet hylbenzyl hydroperoxide 80-15-9	EC50	18.84 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
α, α-dimethylbenzyl hydroperoxide 80-15-9	EC50	3.1 mg/l	Algae	72 h	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
α, α-dimethylbenzyl hydroperoxide 80-15-9	NOEC	1 mg/l	Algae	72 h	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
α, α-dimethylbenzyl hydroperoxide 80-15-9	EC10	70 mg/l	Bacteria	30 min	<i>sucspicatus</i>)	not specified
maleic acid 110-16-7	LC50	> 245 mg/l	Fish	48 h	Leuciscus idus	DIN 38412-15
maleic acid 110-16-7	EC50	42.81 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
maleic acid 110-16-7	EC50	74.35 mg/l	Algae	72 h	Pseudokirchneriella subcapitata	
maleic acid 110-16-7	EC10	11.8 mg/l	Algae	72 h	Pseudokirchneriella subcapitata	
maleic acid 110-16-7	EC10	44.6 mg/l	Bacteria	18 h		DIN 38412, part 8 (Pseudomonas Zellvermehrungshe mm-Test)

Persistence and degradability:

Hazardous components	Result	Route of	Degradability	Method
CAS-No.		application		

LOCTITE 660 RETAINING COMPOUND

V001.6

Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	readily biodegradable	aerobic	94.2 %	OECD Guideline 301 E (Ready biodegradability: Modified OECD Screening Test)
α, α-dimethylbenzyl hydroperoxide 80-15-9	not readily biodegradable.	aerobic	3 %	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
maleic acid 110-16-7	readily biodegradable	aerobic	97.08 %	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)

Bioaccumulative potential / Mobility in soil:

Hazardous components CAS-No.	LogPow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	0.97				20 °C	not specified
α, α-dimethylbenzyl hydroperoxide 80-15-9		9.1		calculation		OECD Guideline 305 (Bioconcentration: Flow- through Fish Test)
α, α-dimethylbenzyl hydroperoxide 80-15-9	1.6				25 °C	OECD Guideline 117 (Partition Coefficient (noctanol / water), HPLC Method)
maleic acid 110-16-7	-1.3				20 °C	OECD Guideline 107 (Partition Coefficient (noctanol / water), Shake Flask Method)
Acetic acid, 2- phenylhydrazide 114-83-0	0.74					not specified

Section 13. Disposal considerations

Waste disposal of product: Dispose of according to Federal, State and local governmental regulations.

Section 14. Transport information

Road and Rail Transport:

Dangerous Goods information: Not classified as Dangerous Goods according to the criteria of the

Australian Code for the Transport of Dangerous Goods by Road and

Rail (ADG Code).

Marine transport IMDG:

Not dangerous goods

Air transport IATA:

Not dangerous goods

Section 15. Regulatory information

SUSMP Poisons Schedule

None

V001.6

SDS No.: 164196

Section 16. Other information

Abbreviations/acronyms: ADGC - Australian Dangerous Goods Code

IATA-DGR: International Air Transport Association - Dangerous Goods Regulations

IMDG: International Maritime Dangerous Goods code

STEL - Short term exposure limit TWA - Time weighted average

AIIC - Australian Inventory of Industrial Chemicals (AIIC) AICIS - Australian Industrial Chemicals Introduction Scheme

Reason for issue: Reviewed SDS. Reissued with new date. involved chapters: 1-16

Date of previous issue: 20.10.2016

Disclaimer:

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel Australia Pty. Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel Australia Pty. Limited concerning the properties of the material.

The information contained in the Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel Australia Pty. Limited assumes no legal responsibility for reliance upon same. Henkel Australia Pty. Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Safety Data Sheet.

This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by either Commonwealth or State statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.

No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.