



Safety Data Sheet

Page 1 of 7

LOCTITE SI 596 RD known as LOCTITE SUPERFLEX RED RTV
80ML

SDS No. : 191177
V001.4
Date of issue: 03.09.2020

Section 1. Identification of the substance/preparation and of the company/undertaking

Product name: LOCTITE SI 596 RD known as LOCTITE SUPERFLEX RED RTV 80ML

Intended use: Sealant

Supplier:
Henkel Australia Pty Ltd
135-141 Canterbury Road
Kilsyth, Victoria, 3137
Australia

Phone: +61 (3) 9724 6444

Emergency information: 24 HOUR EMERGENCY CONTACT NUMBER: 1800 032 379

Section 2. Hazards identification

Classification of the substance or mixture

Hazardous according to the criteria of Safe Work Australia.

GHS Classification:

| <u>Hazard Class</u> | <u>Hazard Category</u> |
|------------------------|------------------------|
| Skin irritation | Category 2 |
| Serious eye irritation | Category 2A |

Hazard pictogram:



Signal word: Danger

Hazard statement(s): H315 Causes skin irritation.
H319 Causes serious eye irritation.

Precautionary Statement(s):

Prevention: P264 Wash thoroughly after handling.
P280 Wear protective gloves, clothing, eye and face protection.

Response:

P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P362 Take off contaminated clothing.
P337+P313 If eye irritation persists: Get medical advice/attention.

Dangerous Goods information:

Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

Section 3. Composition / information on ingredients

General chemical description: Mixture
Type of preparation: Acetoxy curing silicone

Identity of ingredients:

| Chemical ingredients | CAS-No. | Proportion |
|----------------------------|-----------|-------------|
| Silicon dioxide | 7631-86-9 | < 10 % |
| Diiron trioxide | 1309-37-1 | < 10 % |
| non hazardous ingredients~ | | 10- < 100 % |

Section 4. First aid measures

Ingestion: Do not induce vomiting.
Seek medical advice.

Skin: Rinse with running water and soap.
Obtain medical attention if irritation persists.

Eyes: Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

Inhalation: Move to fresh air. If symptoms persist, seek medical advice.

First Aid facilities: Eye wash

Section 5. Fire fighting measures

Suitable extinguishing media: Carbon dioxide, foam, powder
Fine water spray

Decomposition products in case of fire: carbon oxides.
Silica fume

Special protective equipment for fire-fighters: Wear self-contained breathing apparatus.

Additional fire fighting advice: In case of fire, keep containers cool with water spray.

Section 6. Accidental release measures

Personal precautions: Avoid contact with skin and eyes.
Ensure adequate ventilation.

Environmental precautions: Do not let product enter drains.

Clean-up methods: Scrape up as much material as possible.
Ensure adequate ventilation.

Store in a partly filled, closed container until disposal.

Section 7. Handling and storage

- Precautions for safe handling:** Use only in well-ventilated areas.
Vapours should be extracted to avoid inhalation.
- Conditions for safe storage:** Store in a cool, well-ventilated place.
Never allow product to get in contact with water during storage

Section 8. Exposure controls / personal protection

National exposure standards:

| Ingredient [Regulated substance] | form of exposure | TWA (ppm) | TWA (mg/m3) | Peak Limit. (ppm) | Peak Limit. (mg/m3) | STEL (ppm) | STEL (mg/m3) |
|--|------------------|-----------|-------------|-------------------|---------------------|------------|--------------|
| SILICA, AMORPHOUS; FUMED SILICA (RESPIRABLE DUST) 7631-86-9 | Respirable dust. | | 2 | | | | |
| FUMED SILICA (RESPIRABLE DUST) 7631-86-9 | Respirable dust. | | 2 | | | | |
| IRON OXIDE FUME (FE ₂ O ₃) (AS FE) 1309-37-1 | Fume. | | 5 | | | | |

None

- Engineering controls:** Use only with adequate ventilation.
- Eye protection:** Wear protective glasses.
- Skin protection:**
The use of chemical resistant gloves such as Nitrile is recommended.
Please note that in practice the working life of chemical resistant gloves may be considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed then the gloves should be replaced.
- Respiratory protection:** Use only in well-ventilated areas.
If inhalation risk exists, wear a respirator or air supplied mask complying with the requirements of AS/NZS 1715 and AS/NZS 1716.

Section 9. Physical and chemical properties

- Appearance:** Red
Liquid, Paste
- Odor:** Acetic acid
- pH:** Not applicable
- Specific gravity:** 1.01
- Flash point:** > 93 °C (> 199.4 °F)
- Vapor pressure:** 13 hPa
(; 21 °C (69.8 °F))
- Vapor density:** Heavier than air.
- Density:** 1.01 g/cm³
- Solubility in water:** Not soluble. Polymerizes in presence of water.

Section 10. Stability and reactivity

| | |
|--|--|
| Conditions to avoid: | Stable under normal conditions of storage and use. |
| Incompatible materials: | Acids. Bases. Oxidizing agents. Polymerises in presence of water. |
| Hazardous decomposition products: | Acetic acid is liberated slowly upon contact with moisture. |

Section 11. Toxicological information

| | |
|-------------------------|---|
| Health Effects: | |
| Ingestion: | Ingestion of large amounts may produce gastrointestinal disturbances including irritation, nausea, and diarrhea. |
| Skin: | May cause skin irritation. |
| Eyes: | Causes serious eye damage. Contact with the eyes may cause moderate to severe eye injury. Eye contact may result in corneal injury. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. |
| Inhalation: | Acetic acid produced during cure may irritate eyes, nose and throat. May irritate the nose and respiratory system. |
| Chronic effects: | No chronic health effects are expected from the intended use of these products or from foreseeable handling of them in the workplace. |

Acute toxicity:

| Hazardous components CAS-No. | Value type | Value | Route of application | Exposure time | Species | Method |
|---------------------------------|----------------------|---|------------------------------|------------------|----------------------|---|
| Silicon dioxide 7631-86-9 | LD50 LC50 LD50 | > 5,000 mg/kg > 2.08 mg/l > 5,000 mg/kg | oral inhalation dermal | 4 h | rat rat rabbit | OECD Guideline 401 (Acute Oral Toxicity) OECD Guideline 403 (Acute Inhalation Toxicity) not specified |
| Diiron trioxide 1309-37-1 | LD50 LC50 | > 5,000 mg/kg > 5 mg/l | oral inhalation | 4 h | rat rat | EU Method B.1 bis (Acute Oral Toxicity) OECD Guideline 403 (Acute Inhalation Toxicity) |

Skin corrosion/irritation:

| Hazardous components CAS-No. | Result | Exposure time | Species | Method |
|---------------------------------|----------------|------------------|---------|--|
| Silicon dioxide 7631-86-9 | not irritating | 4 h | rabbit | OECD Guideline 404 (Acute Dermal Irritation / Corrosion) |
| Diiron trioxide 1309-37-1 | not irritating | 4 h | rabbit | OECD Guideline 404 (Acute Dermal Irritation / Corrosion) |

Serious eye damage/irritation:

| Hazardous components CAS-No. | Result | Exposure time | Species | Method |
|---------------------------------|----------------|------------------|---------|---|
| Silicon dioxide 7631-86-9 | not irritating | | rabbit | OECD Guideline 405 (Acute Eye Irritation / Corrosion) |
| Diiron trioxide 1309-37-1 | not irritating | 24 h | rabbit | OECD Guideline 405 (Acute Eye Irritation / Corrosion) |

Germ cell mutagenicity:

| Hazardous components CAS-No. | Result | Type of study/ Route of administration | Metabolic activation/ Exposure time | Species | Method |
|---------------------------------|----------------------------------|--|--|---------|--|
| Silicon dioxide 7631-86-9 | negative negative negative | bacterial reverse mutation assay (e.g Ames test) mammalian cell gene mutation assay in vitro mammalian chromosome aberration test | with and without with and without with and without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) |
| Silicon dioxide 7631-86-9 | negative | inhalation | | rat | not specified |
| Diiron trioxide 1309-37-1 | negative negative negative | bacterial reverse mutation assay (e.g Ames test) in vitro mammalian chromosome aberration test mammalian cell gene mutation assay | with and without with and without with and without | | not specified OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) |
| Diiron trioxide 1309-37-1 | | | | | |

Repeated dose toxicity:

| Hazardous components CAS-No. | Result | Route of application | Exposure time/ Frequency of treatment | Species | Method |
|---------------------------------|--------------------------------|-------------------------|---|---------|--|
| Silicon dioxide 7631-86-9 | NOAEL=> 4,000 - 4,500 mg/kg | oral: feed | 13 weeksdaily | rat | equivalent or similar to OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents) |
| Silicon dioxide 7631-86-9 | NOAEL=1.3 mg/m3 | inhalation | 13 w6 h/d, 5 d/w | rat | equivalent or similar to OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day) |
| Diiron trioxide 1309-37-1 | | inhalation | 4 w6h/d, 5d/w | rat | OECD Guideline 412 (Repeated Dose Inhalation Toxicity: 28/14-Day) |

Section 12. Ecological information

General ecological information: Cured Loctite products are typical polymers and do not pose any immediate environmental hazards. In the cured state contribution of this product to Environmental Hazards is insignificant in comparison to articles in which it is used. Precautions required with respect to Environmental Hazards of articles in which this product is used should be considered.

Ecotoxicity: Do not empty into drains / surface water / ground water.

Toxicity:

| Hazardous components CAS-No. | Value type | Value | Acute Toxicity Study | Exposure time | Species | Method |
|---------------------------------|---------------|---------------|----------------------------|------------------|--|--|
| Silicon dioxide 7631-86-9 | LC50 | > 10,000 mg/l | Fish | 96 h | Brachydanio rerio (new name: Danio rerio) | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| Silicon dioxide 7631-86-9 | EL50 | > 1,000 mg/l | Daphnia | 24 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| Silicon dioxide 7631-86-9 | NOELR | 10,000 mg/l | Algae | 72 h | Desmodesmus subspicatus | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Silicon dioxide 7631-86-9 | EL50 | > 10,000 mg/l | Algae | 72 h | Desmodesmus subspicatus | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Silicon dioxide 7631-86-9 | EC0 | 10,000 mg/l | Bacteria | 30 min | Pseudomonas putida | DIN 38412, part 27 (Bacterial oxygen consumption test) |
| Diiron trioxide 1309-37-1 | LC50 | > 1,000 mg/l | Fish | 48 h | Leuciscus idus | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| Diiron trioxide 1309-37-1 | EC50 | > 100 mg/l | Daphnia | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| Diiron trioxide 1309-37-1 | EC0 | > 5,000 mg/l | Bacteria | 24 h | | not specified |

Bioaccumulative potential / Mobility in soil:

| Hazardous components CAS-No. | LogPow | Bioconcentration factor (BCF) | Exposure time | Species | Temperature | Method |
|---------------------------------|--------|----------------------------------|------------------|---------|-------------|---|
| Silicon dioxide 7631-86-9 | 0.53 | | | | | QSAR (Quantitative Structure Activity Relationship) |

Section 13. Disposal considerations

Waste disposal of product: Collection and delivery to recycling enterprise or other registered elimination institution. Cured rubber can be incinerated or landfilled following EPA and local regulations.

Disposal for uncleaned package: After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated. Disposal must be made according to official regulations.

Section 14. Transport information

Road and Rail Transport:

Dangerous Goods information: Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

Marine transport IMDG:

Not dangerous goods

Air transport IATA:

Not dangerous goods

Section 15. Regulatory information

SUSMP Poisons Schedule

None

AICS:

All components are listed or are exempt from listing on the Australian Inventory of Chemical Substances (AICS).

Section 16. Other information

Abbreviations/acronyms:

ADGC - Australian Dangerous Goods Code
IMDG: International Maritime Dangerous Goods code
IATA-DGR: International Air Transport Association – Dangerous Goods Regulations
GHS: Globally Harmonized System
CAS: Chemical Abstracts Service
OECD: Organization for Economic Cooperation and Development
LD 50: Lethal Dose 50%
LC 50: Lethal Concentration 50%

Reason for issue:

Reviewed MSDS. Reissued with new date. involved chapters: 2,3,8,16

Date of previous issue:

14.09.2015

Disclaimer:

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel Australia Pty. Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel Australia Pty. Limited concerning the properties of the material.

The information contained in the Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel Australia Pty. Limited assumes no legal responsibility for reliance upon same. Henkel Australia Pty. Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Safety Data Sheet.

This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by either Commonwealth or State statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.

No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.