

#### **Safety Data Sheet**

Page 1 of 8

LOCTITE 55 PIPE SEALING known as Loc 55 Pipe Sea Cod-150 MTR-REL

SDS No.: 168432 V001.5

Date of issue: 26.08.2021

#### Section 1. Identification of the substance/preparation and of the company/undertaking

Product name: LOCTITE 55 PIPE SEALING known as Loc 55 Pipe Sea Cod-150 MTR-REL

Intended use: Sealant

Supplier:

Henkel Australia Pty Ltd 135-141 Canterbury Road Kilsyth, Victoria, 3137 Australia

Phone: +61 (3) 9724 6444

**Emergency information:** 24 HOUR EMERGENCY CONTACT NUMBER: 1800 032 379

#### Section 2. Hazards identification

#### Classification of the substance or mixture

Hazardous according to the criteria of Safe Work Australia.

**GHS Classification:** 

Hazard ClassHazard CategoryRoute of ExposureCarcinogenicityCategory 1AInhalation

Hazard pictogram:

Signal word: Danger

**Hazard statement(s):** H350 May cause cancer.

**Precautionary Statement(s):** 

**Prevention:** P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P281 Use personal protective equipment as required.

**Response:** P308+P313 IF exposed or concerned: Get medical advice/attention.

**Storage:** P405 Store locked up.

**Disposal:** P501 Dispose of contents/container to an appropriate treatment and disposal facility in

accordance with applicable laws and regulations.

Page 2 of 8

SDS No.: 168432

V001.5

LOCTITE 55 PIPE SEALING known as Loc 55 Pipe Sea

Cod-150 MTR-REL

#### **Dangerous Goods information:**

Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

#### Section 3. Composition / information on ingredients

**General chemical description:** Mixture

**Type of preparation:** Coated Nylon Thread

**Identity of ingredients:** 

Chemical ingredients	CAS-No.	Proportion
Limestone	1317-65-3	30- < 60 %
Talc	14807-96-6	< 10 %
Titanium dioxide	13463-67-7	< 10 %
Quartz (SiO2), <1% respirable	14808-60-7	0.1-< 1 %
non hazardous ingredients~		30- <= 60 %

#### Section 4. First aid measures

**Ingestion:** In case of adverse health effects seek medical advice.

**Skin:** Rinse with running water and soap.

Eyes: None expected.

**Inhalation:** No specific treatment is necessary since material is not likely to be hazardous by

inhalation.

First Aid facilities: Normal washroom facilities

Medical attention and special

treatment:

Treat symptomatically and supportively.

#### **Section 5. Fire fighting measures**

Suitable extinguishing media: water, carbon dioxide, foam, powder

**Improper extinguishing media:** None known

Decomposition products in case of

fire:

carbon oxides.

Particular danger in case of fire: None

Special protective equipment for fire-fighters:

Keep unnecessary personnel away. Wear self-contained breathing apparatus.

#### Section 6. Accidental release measures

**Personal precautions:** See advice in section 8

**Environmental precautions:** No special environmental precautions required.

Page 3 of 8

SDS No.: 168432 V001.5

## LOCTITE 55 PIPE SEALING known as Loc 55 Pipe Sea

Cod-150 MTR-REL

Clean-up methods: Dispose of contaminated material as waste according to Section 13.

#### Section 7. Handling and storage

Precautions for safe handling: No particular measures required.

**Conditions for safe storage:** Store in a cool, dry place.

Keep container tightly sealed.

#### Section 8. Exposure controls / personal protection

#### National exposure standards:

Ingredient [Regulated substance]	form of exposure	TWA (ppm)	TWA (mg/m3)	Peak Limit. (ppm)	Peak Limit. (mg/m3)	STEL (ppm)	STEL (mg/m3)
Nuisance dusts, inhalable dust 1317-65-3	Inhalable dust.		10				
TALC, (CONTAINING NO ASBESTOS FIBRES) 14807-96-6			2.5				
TITANIUM DIOXIDE 13463-67-7	Inhalable dust.		10				
SILICA, CRYSTALLINE: QUARTZ (RESPIRABLE DUST) 14808-60-7	Respirable dust.		0.05				
QUARTZ (RESPIRABLE DUST) 14808-60-7	Respirable dust.		0.05				

**Engineering controls:** Ensure good ventilation/extraction.

**Eye protection:** None required in normal use.

**Skin protection:** Wear suitable protective clothing.

Suitable protective gloves.

**Respiratory protection:** If inhalation risk exists, wear a respirator or air supplied mask complying with the

requirements of AS/NZS 1715 and AS/NZS 1716.

#### Section 9. Physical and chemical properties

**Appearance:** white paste

Odor: characteristic

Specific gravity: 1.25

**Boiling point:**  $150 \, ^{\circ}\text{C} \, (302 \, ^{\circ}\text{F})$  **Flash point:**  $> 93 \, ^{\circ}\text{C} \, (> 199.4 \, ^{\circ}\text{F})$ 

(Closed cup)

**Vapor pressure:** < 0 mm hg

(; 20 °C (68 °F))

Vapor density: < 1

(Air = 1)

**VOC content (2004/42/EC)** 0.0 % (VOCV 814.018 VOC regulation CH)

Page 4 of 8

SDS No.: 168432 V001.5

# LOCTITE 55 PIPE SEALING known as Loc 55 Pipe Sea

Cod-150 MTR-REL

**VOC content:** 1 % 12.75 g/l

#### Section 10. Stability and reactivity

**Stability:** Stable under recommended storage conditions.

Conditions to avoid: Stable

**Incompatible materials:** Oxidizing agents.

Fluorine. Ammonium salts.

Heat, sunlight, UV light, contamination or an oxygen free atmosphere.

Hazardous decomposition

products:

carbon oxides.

#### Section 11. Toxicological information

**Health Effects:** 

**Ingestion:** Not expected to be harmful by ingestion.

Skin: May cause skin irritation.

Eyes: May cause irritation.

**Inhalation:** Not expected under normal conditions of use.

#### Acute toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time		
Limestone	LD50	> 5,000 mg/kg	oral		rat	not specified
1317-65-3	LD50	> 5,000 mg/kg			rat	not specified
			dermal			
Talc	LD50	> 5,000 mg/kg	oral		rat	OECD Guideline 423 (Acute
14807-96-6	LC50	> 2.1 mg/l	inhalation	4 h	rat	Oral toxicity)
	LD50	> 2,000 mg/kg	dermal		rat	OECD Guideline 403 (Acute
						Inhalation Toxicity)
						OECD Guideline 402 (Acute
						Dermal Toxicity)
Titanium dioxide	LD50	> 5,000 mg/kg	oral		rat	OECD Guideline 425 (Acute
13463-67-7	LC50	> 6.82 mg/l	inhalation	4 h	rat	Oral Toxicity: Up-and-Down
	LD50	>= 10,000	dermal		hamster	Procedure)
		mg/kg				not specified
						not specified
Quartz (SiO2), <1%	LD50	> 5,050 mg/kg	oral		rat	not specified
respirable	LD50	> 2,000 mg/kg			not specified	not specified
14808-60-7			dermal			

#### Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Limestone 1317-65-3	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Talc 14807-96-6	slightly irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Titanium dioxide 13463-67-7	not irritating	4 h	rabbit	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

SDS No.: 168432 V001.5

# LOCTITE 55 PIPE SEALING known as Loc 55 Pipe Sea Cod-150 MTR-REL

#### Serious eye damage/irritation:

Hazardous components	Result	Exposure	Species	Method
CAS-No.		time		
Limestone	not irritating		rabbit	OECD Guideline 405 (Acute
1317-65-3	-			Eye Irritation / Corrosion)
Talc	not irritating		rabbit	OECD Guideline 405 (Acute
14807-96-6	_			Eye Irritation / Corrosion)
Titanium dioxide	not irritating		rabbit	OECD Guideline 405 (Acute
13463-67-7	_			Eye Irritation / Corrosion)

#### Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
Limestone 1317-65-3	not sensitising	Mouse local lymphnod e assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Talc 14807-96-6	not sensitising	Guinea pig maximisat ion test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Titanium dioxide 13463-67-7	not sensitising	Mouse local lymphnod e assay (LLNA)	mouse	equivalent or similar to OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)

#### Germ cell mutagenicity:

Hazardous components	Result	Type of study /	Metabolic	Species	Method
CAS-No.		Route of	activation /		
		administration	Exposure time		
Limestone	negative	bacterial reverse	with and without		OECD Guideline 471
1317-65-3	negative	mutation assay (e.g	with and without		(Bacterial Reverse Mutation
	negative	Ames test)	with and without		Assay)
		in vitro mammalian			OECD Guideline 473 (In vitro
		chromosome			Mammalian Chromosome
		aberration test			Aberration Test)
		mammalian cell			OECD Guideline 476 (In vitro
		gene mutation assay			Mammalian Cell Gene
					Mutation Test)
Talc	negative	bacterial reverse	with and without		equivalent or similar to OECD
14807-96-6	negative	mutation assay (e.g	without		Guideline 471 (Bacterial
		Ames test)			Reverse Mutation Assay)
		in vitro mammalian			equivalent or similar to OECD
		cell transformation			Guideline 473 (In vitro Mammalian Chromosome
		assay			Aberration Test)
Talc		1		<b>.</b>	/
14807-96-6	negative	oral: gavage		rat	equivalent or similar to OECD Guideline 478 (Genetic
14807-90-0					Toxicology: Rodent Dominant
					Lethal Test)
Titanium dioxide	negative	bacterial reverse	with and without		OECD Guideline 471
13463-67-7	negative	mutation assay (e.g	with and without		(Bacterial Reverse Mutation
	negative	Ames test)	with and without		Assay)
		in vitro mammalian			OECD Guideline 473 (In vitro
		chromosome			Mammalian Chromosome
		aberration test			Aberration Test)
		mammalian cell			OECD Guideline 476 (In vitro
		gene mutation assay			Mammalian Cell Gene
					Mutation Test)
Titanium dioxide	negative	oral: gavage		mouse	OECD Guideline 474
13463-67-7					(Mammalian Erythrocyte
				1	Micronucleus Test)

Page 6 of 8

SDS No.: 168432 V001.5

# LOCTITE 55 PIPE SEALING known as Loc 55 Pipe Sea Cod-150 MTR-REL

### Repeated dose toxicity:

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
Limestone 1317-65-3	NOAEL=1,000 mg/kg	oral: gavage	48 ddaily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Talc 14807-96-6	NOAEL=100 mg/kg	oral: feed	101 d7 d/w	rat	equivalent or similar to OECD Guideline 452 (Chronic Toxicity Studies)
Titanium dioxide 13463-67-7	NOAEL=1,000 mg/kg	oral: gavage	90 ddaily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

### Section 12. Ecological information

SDS No.: 168432 V001.5

# LOCTITE 55 PIPE SEALING known as Loc 55 Pipe Sea Cod-150 MTR-REL

General ecological information:

Do not empty into drains / surface water / ground water.

#### **Toxicity:**

Hazardous components CAS-No.	Value type	Value	Acute Toxicity	Exposure time	Species	Method
C/15-110.	type		Study	tillic		
Limestone	LC50	> 10,000 mg/l	Fish	96 h	not specified	OECD Guideline
1317-65-3					•	203 (Fish, Acute
						Toxicity Test)
Limestone	EC50	> 1,000 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline
1317-65-3						202 (Daphnia sp.
						Acute
						Immobilisation
**	F.G.50	200 //		70.1		Test)
Limestone	EC50	> 200 mg/1	Algae	72 h	not specified	OECD Guideline
1317-65-3						201 (Alga, Growth
Limestone	EC50	> 1,000 mg/l	Bacteria	3 h	activated sludge of a	Inhibition Test) OECD Guideline
1317-65-3	ECSU	> 1,000 Hig/1	Bacteria	3 11	activated sludge of a predominantly domestic sewage	
1317-03-3					predominantly domestic sewage	Sludge, Respiration
						Inhibition Test)
Talc	LC50	100,000 mg/l	Fish	96 h	Brachydanio rerio (new name:	not specified
14807-96-6		- **,***8 -		, , ,	Danio rerio)	
Titanium dioxide	LC50	Toxicity > Water	Fish	48 h	Leuciscus idus	OECD Guideline
13463-67-7		solubility				203 (Fish, Acute
		·				Toxicity Test)
Titanium dioxide	EC50	Toxicity > Water	Daphnia	48 h	Daphnia magna	OECD Guideline
13463-67-7		solubility				202 (Daphnia sp.
						Acute
						Immobilisation
m: 1: 11	F.G.50	TD 11. 11.		70.1	B 11:1 : 1 : 1 : 1 : 1	Test)
Titanium dioxide	EC50	Toxicity > Water	Algae	72 h	Pseudokirchneriella subcapitata	OECD Guideline
13463-67-7		solubility				201 (Alga, Growth Inhibition Test)
Titanium dioxide	EC0	Toxicity > Water	Bacteria	24 h	Pseudomonas fluorescens	DIN 38412, part 8
13463-67-7	ECO	solubility	Dacteria	24 11	1 seudomonas muorescens	(Pseudomonas
13403-07-7		solubility				Zellvermehrungshe
						mm-Test)
Quartz (SiO2), <1% respirable	LC50	> 1,000  mg/l	Fish	96 h	not specified	OECD Guideline
14808-60-7		, ,			•	203 (Fish, Acute
						Toxicity Test)
Quartz (SiO2), <1% respirable	EC50	> 1,000 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline
14808-60-7						202 (Daphnia sp.
						Acute
						Immobilisation
	T. C. F.O.	1.000 #	1	<b>50.</b>		Test)
Quartz (SiO2), <1% respirable	EC50	> 1,000 mg/l	Algae	72 h	not specified	OECD Guideline
14808-60-7						201 (Alga, Growth
Quartz (SiO2), <1% respirable	EC0	> 1,000 mg/l	Bacteria	3 h	not specified	Inhibition Test) OECD Guideline
14808-60-7	ECU	/ 1,000 Hig/I	Dacteria	3 11	not specified	209 (Activated
14000-00-7						Sludge, Respiration
						Inhibition Test)
ı	l l		I	1	I	

#### Section 13. Disposal considerations

Waste disposal of product: Dispose of in accordance with local and national regulations.

Disposal for uncleaned package: Disposal for uncleaned package: Packaging that cannot be cleaned are to be disposed of in the same manner as the product. After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated. Disposal must be made according to official regulations.

#### Section 14. Transport information

Page 8 of 8

SDS No.: 168432 V001.5

# LOCTITE 55 PIPE SEALING known as Loc 55 Pipe Sea

Cod-150 MTR-REL

Road and Rail Transport:

Dangerous Goods information: Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and

Rail (ADG Code).

**Marine transport IMDG:** 

Not dangerous goods

Air transport IATA: Not dangerous goods

#### Section 15. Regulatory information

**SUSMP Poisons Schedule** None

#### Section 16. Other information

Abbreviations/acronyms: ADGC - Australian Dangerous Goods Code

IMDG: International Maritime Dangerous Goods code

IATA-DGR: International Air Transport Association - Dangerous Goods Regulations

AIIC - Australian Inventory of Industrial Chemicals (AIIC) AICIS - Australian Industrial Chemicals Introduction Scheme

Reason for issue: Reviewed MSDS. Reissued with new date. involved chapters: 1 - 16

Date of previous issue: 11.08.2016

Disclaimer:

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel Australia Pty. Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel Australia Pty. Limited concerning the properties of the material.

The information contained in the Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel Australia Pty. Limited assumes no legal responsibility for reliance upon same. Henkel Australia Pty. Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Safety Data Sheet.

This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by either Commonwealth or State statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.

No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for

additional assistance.