

## Safety Data Sheet

Page 1 of 9

LOCTITE PC 5070 TAPE known as Pipe Repair Kit TAPE

SDS No.: 157264

V001.1

Date of is sue: 17.06.2021

respiratory tract irritation

## Section 1. Identification of the substance/preparation and of the company/undertaking

**Product name:** LOCTITE PC 5070 TAPE known as Pipe Repair Kit TAPE

Intended use: Polyurethane adhesive

Supplier:

Henkel Australia Pty Ltd 135-141 Canterbury Road Kilsyth, Victoria, 3137 Australia

+61 (3) 9724 6444 Phone:

24 HOUR EMERGENCY CONTACT NUMBER: 1800 032 379 **Emergency information:** 

## Section 2. Hazards identification

#### Classification of the substance or mixture

Hazardous according to the criteria of Safe Work Australia.

#### **GHS Classification:**

Hazard Class	<b>Hazard Category</b>	Route of Exposure	Target organ
Acute toxicity	Category 4	Oral	
Acute toxicity	Category 4	Inhalation	
Skin irritation	Category 2		
Serious eye irritation	Category 2A		
Respiratory sensitizer	Category 1		
Skin sensitizer	Category 1		

Single exposure Target Organ Systemic Toxicant -

Target Organ Systemic Toxicant -

Carcinogenicity

Repeated exposure

Category 3 Category 2

Category 2

Hazard pictogram:



Signal word: Danger SDS No.: 157264 V001.1

# LOCTITE PC 5070 TAPE known as Pipe Repair Kit

**TAPE** 

**Hazard statement(s):** H302+H332 Harmful if swallowed or if inhaled.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation. H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

**Precautionary Statement(s):** 

**Prevention:** P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling.

P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves, eye protection, and face protection.

P281 Use personal protective equipment as required.

P285 In case of inadequate ventilation wear respiratory protection.

**Response:** P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor/... if you feel unwell.

P302+P352 IF ON SKIN: Wash with plenty of water.

P304+P340+P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention.

P362 Take off contaminated clothing.

Storage: P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

**Disposal:** P501 Dispose of contents/container to an appropriate treatment and disposal facility in

accordance with applicable laws and regulations.

#### **Dangerous Goods information:**

Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

## Section 3. Composition / information on ingredients

**General chemical description:** Mixture

Type of preparation: Coated Fiberglass tape

#### Identity of ingredients:

Chemical ingredients	CAS-No.	Proportion
Polypropylene glycol 4,4-diphenylmethane	9048-57-1	20- < 30 %
diisocyanateprepolymer		
4,4'- methylenediphenyl diisocyanate	101-68-8	5-< 10 %
Isocyanic acid, polymethylenepolyphenylene ester	9016-87-9	1-< 5 %
non hazardous ingredients~		60- 100%

#### Section 4. First aid measures

Page 3 of 9

SDS No.: 157264 V001.1

LOCTITE PC 5070 TAPE known as Pipe Repair Kit

**TAPE** 

**Ingestion:** Do not induce vomiting.

Have victim rinse mouth thoroughly with water.

Seek medical advice.

**Skin:** Immediately remove soiled or soaked clothing.

Immediately wash skin thoroughly with soap and water.

Seek medical advice.

Eyes: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Seek medical advice.

**Inhalation:** Move to fresh air.

Keep warm and in a quiet place.

Seek medical advice.

First Aid facilities: Eye wash and safety shower

Normal washroom facilities

Medical attention and special

treatment:

Treat symptomatically.

Exposed persons should be kept under medical observation for at least 48 hours because

delayed effects may occur.

## Section 5. Fire fighting measures

**Suitable extinguishing media:** Foam, dry chemical or carbon dioxide.

Improper extinguishing media: High pressure waterjet

Decomposition products in case of

Thermal decomposition can lead to release of irritating gases and vapors.

fire:

carbon monoxide Carbon dioxide. Oxides of nitrogen.

Isocy anate vapors

Special protective equipment for

Wear protective equipment.

fire-fighters:

Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA).

Additional fire fighting advice: In case of fire, keep containers cool with water spray.

## Section 6. Accidental release measures

**Personal precautions:** Wear protective equipment.

Danger of slipping on spilled product.

Avoid skin and eye contact. See advice in section 8

**Environmental precautions:** Do not empty into drains / surface water / ground water.

**Clean-up methods:** Remove with liquid-absorbing material (sand, peat, sawdust).

Dispose of contaminated material as waste according to Section 13.

Page 4 of 9

SDS No.: 157264 V001.1

LOCTITE PC 5070 TAPE known as Pipe Repair Kit

**TAPE** 

#### Section 7. Handling and storage

**Precautions for safe handling:** Avoid contact with eyes, skin and clothing.

Wash thoroughly after handling.

Wear suitable protective clothing, safety glasses and gloves.

**Conditions for safe storage:** Store in a cool, well-ventilated place.

## Section 8. Exposure controls / personal protection

#### National exposure standards:

Ingredient [Regulated substance]	form of exposure	TWA (ppm)	TWA (mg/m3)	Peak Limit. (ppm)	Peak Limit. (mg/m3)	STEL (ppm)	STEL (mg/m3)
ISOCYANATES, ALL (AS-NCO) 101-68-8			0.02				
ISOCYANATES, ALL (AS-NCO) 101-68-8							0.07
ISOCYANATES, ALL (AS-NCO) 9016-87-9			0.02				
ISOCYANATES, ALL (AS-NCO) 9016-87-9							0.07

Engineering controls: Use local ventilation if general ventilation is insufficient to maintain vapor concentration

below established exposure limits.

**Eye protection:** Safety goggles or safety glasses with side shields.

**Skin protection:** Wear suitable protective clothing.

The use of chemical resistant gloves such as Nitrile is recommended.

**Respiratory protection:** If inhalation risk exists, wear a respirator or air supplied mask complying with the

requirements of AS/NZS 1715 and AS/NZS 1716.

## Section 9. Physical and chemical properties

**Appearance:** White

Fiberglass cloth coated with viscous white resin

Odor: Odorless Specific gravity: 1.22

**Boiling point:** 650 °C (1202 °F) **Flash point:** 188 °C (370.4 °F)

(Pensky Martens closed cup)

Vapor pressure: 0.003 mm hg

(; 20 °C (68 °F))

Vapor density: 8.5

**Solubility in water:** Insoluble **VOC content:** < 3 %

(2010/75/EC)

## Section 10. Stability and reactivity

**Stability:** Stable under normal conditions of temperature and pressure.

Page 5 of 9

SDS No.: 157264 V001.1

# LOCTITE PC 5070 TAPE known as Pipe Repair Kit

**TAPE** 

**Conditions to avoid:** Moisture.

Keep away from open flames, hot surfaces and sources of ignition.

Avoid heating.

**Incompatible materials:** Water, Amines, Alkalis, Alcohols.

Reaction with water, formation of CO2

Hazardous decomposition

products:

Thermal decomposition can lead to release of irritating gases and vapors.

Carbon monoxide. carbon dioxide Oxides of nitrogen. Isocy anates.

## Section 11. Toxicological information

**Health Effects:** 

**Ingestion:** Harmful if swallowed.

Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

**Skin:** Irritating to skin.

Symptoms may include redness, edema, drying, defatting and cracking of the skin.

May cause skin sensitization.

**Eyes:** Causes eye irritation.

Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

**Inhalation:** May cause allergic respiratory reaction.

This product is irritating to the respiratory system.

Vapors may cause headaches, nausea, dizziness and respiratory tract irritation.

Carcinogenicity: Category 2 (Carcinogen), Suspected of causing cancer.

## Acute toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time		
4,4'- methylenediphenyl	LD50	> 2,000 mg/kg	oral		rat	other guideline:
diisocyanate	LD50	> 9,400  mg/kg			rabbit	OECD Guideline 402 (Acute
101-68-8			dermal			Dermal Toxicity)
Isocyanic acid,	LD50	$> 10,000 \mathrm{mg/kg}$	oral		rat	OECD Guideline 401 (Acute
polymethylenepolyphenyl	LD50	> 9,400 mg/kg			rat	Oral Toxicity)
ene ester			dermal			OECD Guideline 402 (Acute
9016-87-9						Dermal Toxicity)

#### Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
4,4'- methylenediphenyl diisocyanate 101-68-8	irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Isocyanic acid, polymethylenepolyphenyl ene ester 9016-87-9	irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

SDS No.: 157264 V001.1

LOCTITE PC 5070 TAPE known as Pipe Repair Kit TAPE

## Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
4,4'- methylenediphenyl diisocyanate 101-68-8	sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Isocyanic acid, polymethylenepolyphenyl ene ester 9016-87-9	sensitising	Skin sensitisati on	guinea pig	OECD Guideline 406 (Skin Sensitisation)

## Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study/ Route of administration	Metabolic activation / Exposure time	Species	Method
4,4'- methylenediphenyl diisocyanate 101-68-8	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		EU Method B.13/14 (Mutagenicity)
4,4'- methylenediphenyl diisocyanate 101-68-8	negative	inhalation		rat	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Isocyanic acid, polymethylenepolyphenyl ene ester 9016-87-9	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		EU Method B.13/14 (Mutagenicity)

## Repeated dose toxicity:

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
4,4'- methylenediphenyl diisocyanate 101-68-8	NOAEL=0.0002 mg/l	inhalation: aerosol	main: 2 y; satellite:1 y6 h/d; 5 d/w	rat	OECD Guideline 453 (Combined Chronic Toxicity/ Carcinogenicity Studies)
Isocyanic acid, polymethylenepolyphenyl ene ester 9016-87-9	NOAEL=0.0002 mg/l	inhalation: aerosol	2 y6 h per d, 5 d per week	rat	OECD Guideline 453 (Combined Chronic Toxicity/ Carcinogenicity Studies)

# Section 12. Ecological information

SDS No.: 157264 V001.1

# LOCTITE PC 5070 TAPE known as Pipe Repair Kit TAPE

**General ecological information:** Do not empty into drains, soil or bodies of water.

**Ecotoxicity:** Toxic to aquatic life.

Toxicity:

Hazardous components CAS-No.	Value type	Value	Acute Toxicity	Exposure time	Species	Method
4,4'- methylenediphenyl	LC50	> 1,000 mg/l	Study Fish	96 h	Danio rerio	OECD Guideline
diisocyanate	LC30	> 1,000 mg/1	FISH	90 11	Danio terio	203 (Fish, Acute
101-68-8						Toxicity Test)
4,4'- methylenediphenyl	EC50	129.7 mg/l	Daphnia	24 h	Daphnia magna	OECD Guideline
diisocyanate						202 (Daphniasp.
101-68-8						Acute
						Immobilisation
						Test)
4,4'- methylenediphenyl	EC50	> 1,640  mg/l	Algae	72 h	Scenedesmus subspicatus (new	OECD Guideline
diisocyanate					name: Desmodesmus	201 (Alga, Growth
101-68-8	NOELR	1 640/1	A 1	70 h	subspicatus)	Inhibition Test)
4,4'- methylenediphenyl diisocyanate	NOELK	1,640 mg/l	Algae	72 h	Scenedesmus subspicatus (new name: Desmodesmus	OECD Guideline 201 (Alga, Growth
101-68-8					subspicatus)	Inhibition Test)
4,4'- methylenediphenyl	EC50	> 100  mg/l	Bacteria	3 h	activated sludge	OECD Guideline
diisocyanate	2000	, 100 mg1	Bueteriu	0.11	uerr, area sraage	209 (Activated
101-68-8						Sludge, Respiration
						Inhibition Test)
Isocyanic acid,	LC50	> 1,000  mg/l	Fish	96 h	Brachydanio rerio (new name:	OECD Guideline
polymethylenepolyphenylene					Danio rerio)	203 (Fish, Acute
ester						Toxicity Test)
9016-87-9	EC50	. 1 000 /	D. I. I.	241	David a 'consequence	OECD C : LI
Isocyanic acid,	EC30	> 1,000  mg/l	Daphnia	24 h	Daphnia magna	OECD Guideline
polymethylenepolyphenylene ester						202 (Daphnia sp. Acute
9016-87-9						Immobilisation
7010 07 7						Test)
Isocyanic acid,	EC50	> 1,640  mg/l	Algae	72 h	Desmodesmus subspicatus	OECD Guideline
polymethylenepolyphenylene		, ,	Ü		1	201 (Alga, Growth
ester						Inhibition Test)
9016-87-9						
Isocyanic acid,	EC50	> 100  mg/l	Bacteria	3 h	activated sludge	OECD Guideline
polymethylenepolyphenylene						209 (Activated
ester						Sludge, Respiration
9016-87-9	l l		l	I		Inhibition Test)

## Persistence and degradability:

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
4,4'- methylenediphenyl diisocyanate 101-68-8	not readily biodegradable.	aerobic	0 %	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Isocyanic acid, polymethylenepolyphenylene ester 9016-87-9	not inherently biodegradable	aerobic	0 %	OECD Guideline 302 C (Inherent Biodegradability: Modified MITI Test (II))
Isocyanic acid, polymethylenepolyphenylene ester 9016-87-9	not readily biodegradable.	not specified	0 %	OECD 301 A - F

## ${\bf Bioaccumulative\ potential\ /\ Mobility\ in\ soil:}$

Haz ardous components	LogPow	Bioconcentration	Exposure	Species	Temperature	Method
CAS-No.		factor (BCF)	time			

Page 8 of 9

SDS No.: 157264 V001.1

# LOCTITE PC 5070 TAPE known as Pipe Repair Kit

**TAPE** 

4,4'- methylenediphenyl diisocyanate 101-68-8		92 - 200	28 d	Cyprinus carpio		OECD Guideline 305 E (Bioaccumulation: Flow- through Fish Test)
4,4'- methylenediphenyl diisocyanate 101-68-8	4.51				22 °C	OECD Guideline 117 (Partition Coefficient (noctanol/water), HPLC Method)
Isocyanic acid, polymethylenepolyphenylene ester 9016-87-9		200		Cyprinus carpio		OECD Guideline 305 (Bioconcentration: Flow- through Fish Test)

## **Section 13. Disposal considerations**

Waste disposal of product: In consultation with the responsible local authority, must be subjected to special treatment.

Follow all local, state, federal and provincial regulations for disposal.

**Disposal for uncleaned package:** Packaging that cannot be cleaned are to be disposed of in the same manner as the product.

## Section 14. Transport information

Road and Rail Transport:

Dangerous Goods information: Not classified as Dangerous Goods according to the criteria of the

Australian Code for the Transport of Dangerous Goods by Road and

Rail (ADG Code).

Marine transport IMDG:

Not dangerous goods

Air transport IATA:

Not dangerous goods

## Section 15. Regulatory information

SUSMP Poisons Schedule None

AIIC: All components are listed or are exempt from listing on the Australian Inventory of

Chemical Substances (AICIS).

## Section 16. Other information

Abbreviations/acronyms: ADGC - Australian Dangerous Goods Code

IMDG: International Maritime Dangerous Goods code

STEL - Short term exposure limit TWA - Time weighted average

IATA-DGR: International Air Transport Association - Dangerous Goods Regulations

AIIC - Australian Inventory of Industrial Chemicals (AIIC) AICIS - Australian Industrial Chemicals Introduction Scheme

**Reason for issue:** New Material Safety Data Sheet format. involved chapters: 1 - 16

Page 9 of 9

SDS No.: 157264 V001.1

LOCTITE PC 5070 TAPE known as Pipe Repair Kit

**TAPE** 

**Date of previous issue:** 07.04.2016

Disclaimer:

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel Australia Pty. Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel Australia Pty. Limited concerning the properties of the material.

The information contained in the Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel Australia Pty. Limited assumes no legal responsibility for reliance upon same. Henkel Australia Pty. Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Safety Data Sheet.

This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by either Commonwealth or State statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.

No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.