



Safety Data Sheet

LOCTITE LB 8014 FOOD GRADE ANTI SEIZE known as
LOCTITE FOOD GRADE A/S 8OZ AU

Page 1 of 9

SDS No. : 304659
V001.5

Date of issue: 11.08.2021

Section 1. Identification of the substance/preparation and of the company/undertaking

Product name: LOCTITE LB 8014 FOOD GRADE ANTI SEIZE known as LOCTITE FOOD GRADE A/S 8OZ AU

Intended use: Lubricant

Supplier:
Henkel Australia Pty Ltd
135-141 Canterbury Road
Kilsyth, Victoria, 3137
Australia

Phone: +61 (3) 9724 6444

Emergency information: 24 HOUR EMERGENCY CONTACT NUMBER: 1800 032 379

Section 2. Hazards identification

Classification of the substance or mixture

Hazardous according to the criteria of Safe Work Australia.

GHS Classification:

<u>Hazard Class</u>	<u>Hazard Category</u>
Skin irritation	Category 2
Serious eye damage/eye irritation	Category 1
Aspiration hazard	Category 1
Acute hazards to the aquatic environment	Category 3
Chronic hazards to the aquatic environment	Category 3

Hazard pictogram:



Signal word: Danger

Hazard statement(s): H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H412 Harmful to aquatic life with long lasting effects.

Precautionary Statement(s):
Prevention: P264 Wash hands thoroughly after handling.
P273 Avoid release to the environment.
P280 Wear protective gloves, eye protection, and face protection.

Response: P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor.
P302+P352 IF ON SKIN: Wash with plenty of water.
P305+P351+P338+P315 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. Get immediate medical advice/attention.
P331 Do NOT induce vomiting.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P362 Take off contaminated clothing.

Storage: P405 Store locked up.

Disposal: P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations.

Dangerous Goods information:

Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

Section 3. Composition / information on ingredients

General chemical description: Mixture
Mineral oil

Type of preparation: Lubricant

Identity of ingredients:

Chemical ingredients	CAS-No.	Proportion
White mineral oil (petroleum) (not cmr)	8042-47-5	10- < 30 %
Calcium dihydroxide	1305-62-0	10- < 30 %
Talc	14807-96-6	< 10 %
non hazardous ingredients~		30- <= 60 %

Section 4. First aid measures

Ingestion: Rinse mouth, do not induce vomiting, consult a doctor.

Skin: Immediately wash skin thoroughly with soap and water.
Seek medical advice.

Eyes: Immediately flush eyes with plenty of water for at least 15 minutes.
Immediate medical treatment necessary.

Inhalation: Move to fresh air. If symptoms persist, seek medical advice.

First Aid facilities: Eye wash
Normal washroom facilities

Medical attention and special treatment: Treat symptomatically.

Section 5. Fire fighting measures

Suitable extinguishing media: Carbon dioxide, foam, powder
Water spray or fog.

Improper extinguishing media: High pressure waterjet

Decomposition products in case of fire: Irritating and/or toxic fumes and gases may be emitted upon the product's decomposition.
Oxides of carbon.

Special protective equipment for fire-fighters: Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional fire fighting advice: In case of fire, keep containers cool with water spray.
Collect contaminated fire fighting water separately. It must not enter drains.

Section 6. Accidental release measures

Personal precautions: Use personal protective equipment as described in Section 8.

Environmental precautions: Do not empty into drains / surface water / ground water.

Clean-up methods: Absorb spill with inert material. Shovel material into appropriate container for disposal.
Dispose of contaminated material as waste according to Section 13.

Section 7. Handling and storage

Precautions for safe handling: Avoid skin and eye contact.
Refer to Section 8.
Ensure that workrooms are adequately ventilated.

Conditions for safe storage: Suitable material for containers: original container.
Store in a cool, dry, well-ventilated area.
Keep away from heat and direct sunlight.

Section 8. Exposure controls / personal protection

National exposure standards:

Ingredient [Regulated substance]	form of exposure	TWA (ppm)	TWA (mg/m3)	Peak Limit. (ppm)	Peak Limit. (mg/m3)	STEL (ppm)	STEL (mg/m3)
Oil mist, refined mineral 8042-47-5			5				
CALCIUM HYDROXIDE 1305-62-0			5				
TALC, (CONTAINING NO ASBESTOS FIBRES) 14807-96-6			2.5				

Engineering controls:	Ensure good ventilation/suction at the workplace.
Eye protection:	Wear chemical goggles and face shield.
Skin protection:	Use of an impervious apron is recommended. Nitrile rubber gloves should be worn. Please note that in practice the working life of chemical resistant gloves may be considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed then the gloves should be replaced.
Respiratory protection:	If inhalation risk exists, wear a respirator or air supplied mask complying with the requirements of AS/NZS 1715 and AS/NZS 1716.

Section 9. Physical and chemical properties

Appearance:	White Paste
Odor:	Mild
Specific gravity:	1.18
Flash point: (calculated)	154 °C (309.2 °F)
Solubility in water:	Insoluble
VOC content: (2010/75/EC)	< 3 %

Section 10. Stability and reactivity

Stability:	Stable under recommended storage conditions.
Conditions to avoid:	Excessive heat.
Incompatible materials:	Strong oxidizing agents.
Hazardous decomposition products:	In case of fire toxic gases can be released. Oxides of carbon.
Hazardous polymerization:	Will not occur.

Section 11. Toxicological information

Health Effects:**Ingestion:**

May cause gastrointestinal tract irritation if swallowed.

Skin:

Irritating to skin.

Symptoms may include redness, edema, drying, defatting and cracking of the skin.

Eyes:

Causes serious eye damage.

Contact with the eyes may cause moderate to severe eye injury. Eye contact may result in corneal injury. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

Inhalation:

May cause irritation to nose and throat.

Acute toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
White mineral oil (petroleum) (not cmr) 8042-47-5	LD50 LC50 LD50	> 5,000 mg/kg > 5 mg/l > 2,000 mg/kg	oral inhalation dermal	4 h	rat rat rabbit	OECD Guideline 401 (Acute Oral Toxicity) OECD Guideline 403 (Acute Inhalation Toxicity) OECD Guideline 402 (Acute Dermal Toxicity)
Calcium dihydroxide 1305-62-0	LD50 LD50	> 7,340 mg/kg > 2,500 mg/kg	oral dermal		rat rat	OECD Guideline 401 (Acute Oral Toxicity) OECD Guideline 402 (Acute Dermal Toxicity)
Talc 14807-96-6	LD50 LC50 LD50	> 5,000 mg/kg > 2.1 mg/l > 2,000 mg/kg	oral inhalation dermal	4 h	rat rat rat	OECD Guideline 423 (Acute Oral toxicity) OECD Guideline 403 (Acute Inhalation Toxicity) OECD Guideline 402 (Acute Dermal Toxicity)

Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
White mineral oil (petroleum) (not cmr) 8042-47-5	not irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Calcium dihydroxide 1305-62-0	irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Talc 14807-96-6	slightly irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
White mineral oil (petroleum) (not cmr) 8042-47-5	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Calcium dihydroxide 1305-62-0	Category 1 (irreversible effects on the eye)		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Talc 14807-96-6	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
White mineral oil (petroleum) (not cmr) 8042-47-5	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Talc 14807-96-6	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
White mineral oil (petroleum) (not cmr) 8042-47-5	negative negative	bacterial reverse mutation assay (e.g Ames test) mammalian cell gene mutation assay	with with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay) OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
White mineral oil (petroleum) (not cmr) 8042-47-5	negative	intraperitoneal		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Calcium dihydroxide 1305-62-0	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Talc 14807-96-6	negative negative	bacterial reverse mutation assay (e.g Ames test) in vitro mammalian cell transformation assay	with and without without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay) equivalent or similar to OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Talc 14807-96-6	negative	oral: gavage		rat	equivalent or similar to OECD Guideline 478 (Genetic Toxicology: Rodent Dominant Lethal Test)

Repeated dose toxicity:

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
White mineral oil (petroleum) (not cmr) 8042-47-5	NOAEL=>= 1,600 mg/kg	oral: feed	90 ddaily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Talc 14807-96-6	NOAEL=100 mg/kg	oral: feed	101 d7 d/w	rat	equivalent or similar to OECD Guideline 452 (Chronic Toxicity Studies)

Section 12. Ecological information

General ecological information: Do not empty into drains / surface water / ground water.**Ecotoxicity:** Harmful to aquatic life with long lasting effects.**Toxicity:**

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
White mineral oil (petroleum) (not cmr) 8042-47-5	LL50	> 100 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
White mineral oil (petroleum) (not cmr) 8042-47-5	EL50	> 100 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
White mineral oil (petroleum) (not cmr) 8042-47-5	NOELR	100 mg/l	Algae	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
White mineral oil (petroleum) (not cmr) 8042-47-5	IC50	> 100 mg/l	Bacteria	93 d	other:	other guideline:
Calcium dihydroxide 1305-62-0	LC50	50.6 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Calcium dihydroxide 1305-62-0	EC50	49.1 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Calcium dihydroxide 1305-62-0	EC50	184.57 mg/l	Algae	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Calcium dihydroxide 1305-62-0	NOEC	48 mg/l	Algae	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Calcium dihydroxide 1305-62-0	EC20	229.2 mg/l	Bacteria	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Talc 14807-96-6	LC50	100,000 mg/l	Fish	96 h	Brachydanio rerio (new name: Danio rerio)	not specified

Persistence and degradability:

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
White mineral oil (petroleum) (not cmr) 8042-47-5	not readily biodegradable.	aerobic	31.3 %	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)

Bioaccumulative potential / Mobility in soil:

Hazardous components CAS-No.	LogPow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
White mineral oil (petroleum) (not cmr) 8042-47-5	> 4					EU Method A.8 (Partition Coefficient)

Section 13. Disposal considerations**Waste disposal of product:** Collection and delivery to recycling enterprise or other registered elimination institution.**Recommended cleanser:** Suitable organic solvents**Disposal for uncleaned package:** Packaging that cannot be cleaned are to be disposed of in the same manner as the product.

Section 14. Transport information

Road and Rail Transport:

Dangerous Goods information: Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

Marine transport IMDG:

Not dangerous goods

Air transport IATA:

Not dangerous goods

Section 15. Regulatory information

SUSMP Poisons Schedule None

Section 16. Other information

Abbreviations/acronyms: ADGC - Australian Dangerous Goods Code
 IMDG: International Maritime Dangerous Goods code
 IATA-DGR: International Air Transport Association – Dangerous Goods Regulations
 STEL - Short term exposure limit
 TWA - Time weighted average
 AIIC - Australian Inventory of Industrial Chemicals (AIIC)
 AICIS - Australian Industrial Chemicals Introduction Scheme

Reason for issue: Reviewed SDS. Reissued with new date. involved chapters: 1 - 16

Date of previous issue: 25.07.2016

Disclaimer:

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel Australia Pty. Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel Australia Pty. Limited concerning the properties of the material.

The information contained in the Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel Australia Pty. Limited assumes no legal responsibility for reliance upon same. Henkel Australia Pty. Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Safety Data Sheet.

This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by either Commonwealth or State statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.

No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.

