

Safety Data Sheet

Page 1 of 8

SDS No.: 153559

V001.5

Date of issue: 23.07.2021

Section 1. Identification of the substance/preparation and of the company/undertaking

Product name: LOCTITE SF 7452 ACCELERATOR Tak Pak® 7452 Accelerator

Intended use: Primer, containing solvents

LOCTITE SF 7452 ACCELERATOR Tak Pak® 7452 Accelerator

Supplier:

Henkel Australia Pty Ltd 135-141 Canterbury Road Kilsyth, Victoria, 3137 Australia

Phone: +61 (3) 9724 6444

24 HOUR EMERGENCY CONTACT NUMBER: 1800 032 379 **Emergency information:**

Section 2. Hazards identification

Classification of the substance or mixture

Hazardous according to the criteria of Safe Work Australia.

GHS Classification:

Hazard Class Hazard Category

Flammable liquids Category 2 Serious eye irritation Category 2A Target Organ Systemic Toxicant -Category 3

Single exposure

Target organ

Central nervous system

Hazard pictogram:



Signal word: Danger

LOCTITE SF 7452 ACCELERATOR Tak Pak® 7452

Accelerator

Hazard statement(s): H225 Highly flammable liquid and vapor.

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

Repeated exposure may cause skin dryness or cracking.

Precautionary Statement(s):

Prevention: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment. P241 Use explosion-proof electrical/ventilating/lighting equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves, eye protection, and face protection.

Response: P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water [or shower].

P304+P340+P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for

extinction.

Storage: P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal: P501 Dispose of contents/container to an appropriate treatment and disposal facility in

accordance with applicable laws and regulations.

Dangerous Goods information:

Classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

Class or division:

3

Section 3. Composition / information on ingredients

General chemical description: Mixture

Type of preparation: Primer, containing solvents

Identity of ingredients:

Chemical ingredients	CAS-No.	Proportion
acetone	67-64-1	60- <= 100 %
N,N-Dimethyl-p-toluidine	99-97-8	< 1 %
non hazardous ingredients~		<= 10 %

Section 4. First aid measures

Page 3 of 8

SDS No.: 153559

V001.5 LOCTITE SF 7452 ACCELERATOR Tak Pak® 7452

Accelerator

Ingestion: Rinse out mouth, drink 1-2 glasses of water, do not induce vomiting.

Seek medical advice.

Skin: Rinse with running water and soap.

Seek medical advice.

Eyes: Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if

necessary.

Inhalation: Move to fresh air. If symptoms persist, seek medical advice.

Section 5. Fire fighting measures

Suitable extinguishing media: Foam, dry chemical or carbon dioxide.

Decomposition products in case of

fire:

Oxides of carbon.

Oxides of nitrogen.

Particular danger in case of fire: Vapors may accumulate in low or confined areas, travel considerable distance to source of

ignition, and flash back.

Closed containers may rupture (due to build up of pressure) when exposed to extreme

heat.

Special protective equipment for

fire-fighters:

Use water spray to keep fire exposed containers cool and disperse vapors.

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Hazchem code: •2YE

Section 6. Accidental release measures

Personal precautions: Avoid skin and eye contact.

Ensure adequate ventilation.

Environmental precautions: Do not let product enter drains.

Clean-up methods: For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for

disposal.

Section 7. Handling and storage

Precautions for safe handling: Use only in well-ventilated areas.

Vapours should be extracted to avoid inhalation. Keep away from sources of ignition - no smoking.

Conditions for safe storage: Store in a cool, well-ventilated place.

Keep away from heat and direct sunlight.

Section 8. Exposure controls / personal protection

National exposure standards:

Ingredient [Regulated substance]	form of exposure	TWA (ppm)	TWA (mg/m3)	Peak Limit. (ppm)	Peak Limit. (mg/m3)	STEL (ppm)	STEL (mg/m3)
ACETONE		500	1,185				
67-64-1							

Page 4 of 8

SDS No.: 153559 V001.5

LOCTITE SF 7452 ACCELERATOR Tak Pak® 7452

Accelerator

ACETONE			1,000	2,375
67-64-1				

Engineering controls: Use local ventilation if general ventilation is insufficient to maintain vapor concentration

below established exposure limits.

Eye protection: Wear protective glasses.

Skin protection: Wear suitable protective clothing.

Use of Butylor Nitrile Rubber gloves is recommended.

Please note that in practice the working life of chemical resistant gloves may be considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed

then the gloves should be replaced.

Respiratory protection: Use only in well-ventilated areas.

If inhalation risk exists, wear a respirator or air supplied mask complying with the

requirements of AS/NZS 1715 and AS/NZS 1716.

Section 9. Physical and chemical properties

Appearance: colourless liquid

Odor: Acetone Specific gravity: 0.7926

Boiling point: 57 °C (134.6 °F) **Flash point:** -17 °C (1.4 °F)

(Tagliabue closed cup)

Vapor pressure: 185 mm hg

 $(; 20~^{\circ}\text{C}~(68~^{\circ}\text{F}))$

Density: 0.79 g/cm3 **VOC content:** 100 %

(2010/75/EC)

Section 10. Stability and reactivity

Stability: Stable under recommended storage conditions.

Conditions to avoid: Heat, flames, sparks and other sources of ignition.

Incompatible materials: Reaction with strong acids.

Reacts with strong oxidants.

Hazardous decomposition

products:

Irritating organic vapours.

Section 11. Toxicological information

LOCTITE SF 7452 ACCELERATOR Tak Pak® 7452

Accelerator

Health Effects:

Ingestion: Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Central nervous system depression, including dizziness, drowsiness, fatigue, nausea, headache,

unconsciousness.

Skin: May cause irritation due to defatting of the skin.

Causes skin irritation.

Eyes: Causes eye irritation.

Symptoms can include irritation, redness, scratching of the cornea, and tearing.

Causes serious eye irritation.

Inhalation: May cause respiratory tract irritation.

Central nervous system depression, including dizziness, drowsiness, fatigue, nausea, headache,

unconsciousness.

Inhalation of vapors or mists of the product may be irritating to the respiratory system.

Acute toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
acetone	LD50	5,800 mg/kg	oral		rat	not specified
67-64-1	LC50	76 mg/l	inhalation	4 h	rat	not specified
	LD50	$> 15,688 \mathrm{mg/kg}$	dermal		rabbit	Draize Test

Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
acetone 67-64-1	not irritating		guinea pig	not specified

Serious eye damage/irritation:

Hazardous components	Result	Exposure	Species	Method
CAS-No.		time		
acetone	irritating		rabbit	OECD Guideline 405 (Acute
67-64-1				Eye Irritation / Corrosion)

Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
acetone	not sensitising	Guinea pig	guinea pig	not specified
67-64-1		maximisat		
		ion test		

Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study/ Route of administration	Metabolic activation / Exposure time	Species	Method
acetone 67-64-1	negative negative negative	bacterial reverse mutation assay (e.g Ames test) in vitro mammalian chromosome aberration test mammalian cell gene mutation assay	with and without with and without without		OECD Guideline 471 (Bacterial Reverse Mutation Assay) OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
acetone 67-64-1	negative	oral: drinking water		mouse	not specified

LOCTITE SF 7452 ACCELERATOR Tak Pak® 7452

Accelerator

Repeated dose toxicity:

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
acetone 67-64-1	NOAEL=900 mg/kg	oral: drinking water	13 wdaily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

Section 12. Ecological information

General ecological information:

Do not empty into drains / surface water / ground water., May cause long-term adverse effects in the aquatic environment.

Toxicity:

Hazardous components CAS-No.	Value type	Value	Acute Toxicity	Exposure time	Species	Method
			Study			
acetone	LC50	8,120 mg/l	Fish	96 h	Pimephales promelas	OECD Guideline
67-64-1						203 (Fish, Acute
						Toxicity Test)
acetone	EC50	8,800 mg/l	Daphnia	48 h	Daphnia pulex	OECD Guideline
67-64-1			_			202 (Daphnia sp.
						Acute
						Immobilisation
						Test)
acetone	NOEC	530 mg/l	Algae	8 d	Microcystis aeruginosa	DIN 38412-09
67-64-1		C			•	
acetone	EC10	1,000 mg/l	Bacteria	30 min	Pseudomonas putida	DIN 38412, part 27
67-64-1					•	(Bacterial oxygen
						consumption test)
N,N-Dimethyl-p-toluidine	LC50	46 mg/l	Fish	96 h	Fathead minnow (Pimephales	other guideline:
99-97-8		C			promelas)	

Persistence and degradability:

Hazardous components	Result	Route of	Degradability	Method
CAS-No.		application		
acetone	readily biodegradable	aerobic	81 - 92 %	EU Method C.4-E (Determination
67-64-1				of the "Ready"
				BiodegradabilityClosed Bottle
				Test)

Bioaccumulative potential/Mobility in soil:

Hazardous components CAS-No.	LogPow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
acetone 67-64-1	-0.24					OECD Guideline 107 (Partition Coefficient (noctanol/water), Shake Flask Method)
N,N-Dimethyl-p-toluidine 99-97-8	2.81				25 °C	not specified

Section 13. Disposal considerations

Waste disposal of product: Can be incinerated, when in compliance with local regulations

Collection and delivery to recycling enterprise or other registered elimination institution.

Dispose of in accordance with local and national regulations.

Disposal for uncleaned package: Disposal must be made according to official regulations.

LOCTITE SF 7452 ACCELERATOR Tak Pak® 7452

Accelerator

Section 14. Transport information

Road and Rail Transport:

Dangerous Goods information: Classified as Dangerous Goods according to the criteria of the

Australian Code for the Transport of Dangerous Goods by Road and

Rail (ADG Code).

UN no.: 1090

Proper shipping name: ACETONE (solution)

Class or division: 3

Packing group: II Hazchem code: •2YE

Emergency information: Refer to the Australian Emergency Response Guide Book

Marine transport IMDG:

UN no.: 1090

Proper shipping name: ACETONE (solution)

Class or division: 3 Packing group: II

EmS: F-E, S-D

Seawater pollutant:

Air transport IATA:

UN no.: 1090

Proper shipping name: Acetone (solution)

Section 15. Regulatory information

SUSMP Poisons Schedule None

AIIC: All components are listed or are exempt from listing on the Australian Inventory of

Chemical Substances (AICIS).

Section 16. Other information

Abbreviations/acronyms: ADGC - Australian Dangerous Goods Code

GHS: Globally Harmonized System

IATA-DGR: International Air Transport Association - Dangerous Goods Regulations

IMDG: International Maritime Dangerous Goods code

STEL - Short term exposure limit TWA - Time weighted average

AIIC - Australian Inventory of Industrial Chemicals (AIIC) AICIS - Australian Industrial Chemicals Introduction Scheme

Reason for issue: Reviewed MSDS. Reissued with new date. involved chapters: 1-16

Page 8 of 8

SDS No.: 153559 V001.5

LOCTITE SF 7452 ACCELERATOR Tak Pak® 7452 Accelerator

Date of previous issue: 10.06.2016

Disclaimer:

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel Australia Pty. Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel Australia Pty. Limited concerning the properties of

The information contained in the Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel Australia Pty. Limited assumes no legal responsibility for reliance upon same. Henkel Australia Pty. Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Safety Data Sheet.

This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by either Commonwealth or State statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.

No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.