

# Safety Data Sheet

Page 1 of 8

LOCTITE SI 596 known as Loc 596 Red RTV Sili gas-300ml

SDS No.: 168444

V001.4

Date of issue: 21.08.2020

# Section 1. Identification of the substance/preparation and of the company/undertaking

Product name: LOCTITE SI 596 known as Loc 596 Red RTV Sili gas-300ml

Intended use: Sealant

Supplier:

Henkel Australia Pty Ltd 135-141 Canterbury Road Kilsyth, Victoria, 3137 Australia

Phone: +61 (3) 9724 6444

**Emergency information:** 24 HOUR EMERGENCY CONTACT NUMBER: 1800 032 379

# Section 2. Hazards identification

#### Classification of the substance or mixture

Hazardous according to the criteria of Safe Work Australia.

### **GHS Classification:**

Hazard ClassHazard CategorySkin corrosionCategory 1BSerious eye damage/eye irritationCategory 1

Hazard pictogram:

TZ)

Signal word: Danger

SDS No.: 168444

V001.4

LOCTITE SI 596 known as Loc 596 Red RTV Sili gas-

300ml

**Hazard statement(s):** H314 Causes severe skin burns and eye damage.

**Precautionary Statement(s):** 

**Prevention:** P260 Do not breathe dusts or mists.

P264 Wash hands thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

**Response:** P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water [or shower].

P304+P340+P310 IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing. Immediately call a POISON CENTER or physician. P305+P351+P338+P315 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical

advice/attention.

P363 Wash contaminated clothing before reuse.

**Storage:** P405 Store locked up.

**Disposal:** P501 Dispose of contents/container to an appropriate treatment and disposal facility in

accordance with applicable laws and regulations.

#### **Dangerous Goods information:**

Classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

# Section 3. Composition / information on ingredients

**General chemical description:** Mixture

**Type of preparation:** Acetoxy curing silicone

Identity of ingredients:

Chemical ingredients	CAS-No.	Proportion
Hydrocarbon C11-25 dearomatized	64742-46-7	10- < 30 %
Methylsilanetriyl triacetate	4253-34-3	10- < 30 %
Triacetoxyethylsilane	17689-77-9	10- < 30 %
non hazardous ingredients~		10- < 70 %

# Section 4. First aid measures

**Ingestion:** Do not induce vomiting.

Seek medical advice.

**Skin:** Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eyes: Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if

necessary.

**Inhalation:** Move to fresh air. If symptoms persist, seek medical advice.

First Aid facilities: Eye wash

Normal washroom facilities

Page 3 of 8

SDS No.: 168444

V001.4

LOCTITE SI 596 known as Loc 596 Red RTV Sili gas-

300ml

# Section 5. Fire fighting measures

Suitable extinguishing media: Carbon dioxide, foam, powder

Fine water spray

Decomposition products in case of

fire:

carbon oxides. Silica fume

Special protective equipment for

fire-fighters:

Wear self-contained breathing apparatus.

**Additional fire fighting advice:** In case of fire, keep containers cool with water spray.

Hazchem code: 2X

#### Section 6. Accidental release measures

**Personal precautions:** Avoid contact with skin and eyes.

Ensure adequate ventilation.

**Environmental precautions:** Do not let product enter drains.

**Clean-up methods:** Scrape up as much material as possible.

Ensure adequate ventilation.

Store in a partly filled, closed container until disposal.

# Section 7. Handling and storage

**Precautions for safe handling:** Use only in well-ventilated areas.

Vapours should be extracted to avoid inhalation.

**Conditions for safe storage:** Store in a cool, well-ventilated place.

Never allow product to get in contact with water during storage

# Section 8. Exposure controls / personal protection

#### National exposure standards:

In gredient [Regulated substance]	form of exposure	TWA (ppm)	TWA (mg/m3)	Peak Limit.	Peak Limit. (mg/m3)	STEL (ppm)	STEL (mg/m3)
OIL MIST, REFINEDMINERAL			5				9 /
64742-46-7							

**Engineering controls:** Use only with adequate ventilation.

**Eye protection:** Wear protective glasses.

Skin protection:

The use of chemical resistant gloves such as Nitrile is recommended.

Please note that in practice the working life of chemical resistant gloves may be considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed

then the gloves should be replaced.

**Respiratory protection:** Use only in well-ventilated areas.

If inhalation risk exists, wear a respirator or air supplied mask complying with the

requirements of AS/NZS 1715 and AS/NZS 1716.

SDS No.: 168444

V001.4

LOCTITE SI 596 known as Loc 596 Red RTV Sili gas-

300ml

#### Section 9. Physical and chemical properties

Appearance: red
paste

Odor: Acetic acid

**Specific gravity:** 1.05 **Flash point:** > 93 °C (> 199.4 °F)

(Tagliabue closed cup)

Vapor pressure: < 10 mm hg

(; 20 °C (68 °F))

Solubility in water: Insoluble

# Section 10. Stability and reactivity

**Conditions to avoid:** Stable under normal conditions of storage and use.

**Incompatible materials:** Acids.

Bases.

Oxidizing agents.

Polymerises in presence of water.

Hazardous decomposition

products:

Acetic acid is liberated slowly upon contact with moisture.

# Section 11. Toxicological information

**Health Effects:** 

Ingestion: Ingestion of large amounts may produce gastrointestinal disturbances including irritation, nausea,

and diarrhea.

**Skin:** Causes skin burns.

Eyes: Contact with this product may cause severe eye damage.

**Inhalation:** Acetic acid produced during cure may irritate eyes, nose and throat.

**Chronic effects:** No chronic health effects are expected from the intended use of these products or from

foreseeable handling of them in the workplace.

#### Acute toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time		
Hydrocarbon C11-25	LD50	> 5,000 mg/kg	oral		rat	OECD Guideline 401 (Acute
dearomatized	LC50	> 5.266 mg/l	inhalation	4 h	rat	Oral Toxicity)
64742-46-7	LD50	$> 2,000 \mathrm{mg/kg}$	dermal		rabbit	not specified
						OECD Guideline 402 (Acute
						Dermal Toxicity)
Methylsilanetriyl	LD50	1,600 mg/kg	oral		rat	OECD Guideline 401 (Acute
triacetate						Oral Toxicity)
4253-34-3						
Triacetoxyethylsilane	LD50	1,460 mg/kg	oral		rat	OECD Guideline 401 (Acute
17689-77-9						Oral Toxicity)

SDS No.: 168444 V001.4

LOCTITE SI 596 known as Loc 596 Red RTV Sili gas- $300\mathrm{ml}$ 

# Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Methylsilanetriyl triacetate 4253-34-3	corrosive	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Triacetoxyethylsilane 17689-77-9	Category 1B (corrosive)	3 min	rabbit	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

# Serious eye damage/irritation:

Hazardous components	Result	Exposure	Species	Method
CAS-No.		time		
Methylsilanetriyl	Category 1 (irreversible effects on the eye)		rabbit	OECD Guideline 405 (Acute
triacetate				Eye Irritation / Corrosion)
4253-34-3				

# Respiratory or skin sensitization:

Hazardous components	Result	Test type	Species	Method
CAS-No.				
Methylsilanetriyl	not sensitising	Guinea pig	guinea pig	OECD Guideline 406 (Skin
triacetate		maximisat		Sensitisation)
4253-34-3		ion test		
Triacetoxyethylsilane	not sensitising	Guinea pig	guinea pig	OECD Guideline 406 (Skin
17689-77-9		maximisat		Sensitisation)
		ion test		

# Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study/ Route of administration	Metabolic activation / Exposure time	Species	Method
Methylsilanetriyl triacetate 4253-34-3	negative negative negative	bacterial reverse mutation assay (e.g Ames test) in vitro mammalian chromosome aberration test mammalian cell gene mutation assay	with and without with and without with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay) OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Triacetoxyethylsilane 17689-77-9	negative negative negative	bacterial reverse mutation assay (e.g Ames test) in vitro mammalian chromosome aberration test mammalian cell gene mutation assay	with and without with and without with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay) OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)

# Repeated dose toxicity:

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
Methylsilanetriyl triacetate 4253-34-3	NOAEL=50 mg/kg	oral: gavage	28-51 ddaily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

# Section 12. Ecological information

SDS No.: 168444 V001.4

# LOCTITE SI 596 known as Loc 596 Red RTV Sili gas-

300ml

General ecological information: Cured Loctite products are typical polymers and do not pose any immediate

environmental hazards., In the cured state contribution of this product to

Environmental Hazards is insignificant in comparison to articles in which it is used., Precautions required with respect to Environmental Hazards of articles in which this

product is used should be considered.

#### Toxicity:

Hazardous components	Value	Value	Acute	Exposure	Species	Method
CAS-No.	type		Toxicity	time		
			Study			
Hydrocarbon C11-25	LC50	> 10,000 mg/l	Fish	96 h	Pimephales promelas	OECD Guideline
dearomatized						203 (Fish, Acute
64742-46-7						Toxicity Test)
Methylsilanetriyl triacetate	LC50	> 110 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline
4253-34-3						203 (Fish, Acute
						Toxicity Test)
Triacetoxyethylsilane	LC50	251 mg/l	Fish	96 h	Brachydanio rerio (new name:	OECD Guideline
17689-77-9					Danio rerio)	203 (Fish, Acute
						Toxicity Test)
Triacetoxyethylsilane	EC50	168.7 mg/l	Daphnia	48 h	Daphnia magna	EU Method C.2
17689-77-9						(Acute Toxicity for
						Daphnia)
Triacetoxyethylsilane	EC50	> 1,562.5 mg/l	Algae	72 h	Pseudokirchneriella subcapitata	
17689-77-9						201 (Alga, Growth
						Inhibition Test)
Triacetoxyethylsilane	NOEC	40 mg/l	Algae	72 h	Pseudokirchneriella subcapitata	
17689-77-9						201 (Alga, Growth
1						Inhibition Test)

### Persistence and degradability:

Hazardous components	Result	Route of	Degradability	Method
CAS-No.		application		
Hydrocarbon C11-25	not readily biodegradable.	aerobic	30 %	OECD Guideline 301 D (Ready
dearomatized				Biodegradability: Closed Bottle
64742-46-7				Test)
Triacetoxyethylsilane	readily biodegradable	aerobic	74 %	EU Method C.4-A (Determination
17689-77-9				of the "Ready"
				BiodegradabilityDissolved
				Organic Carbon (DOC) Die-Away
				Test)

### Bioaccumulative potential / Mobility in soil:

Ī	Hazardous components	LogPow	Bioconcentration	Exposure	Species	Temperature	Method
	CAS-No.		factor (BCF)	time			
ſ	Triacetoxyethylsilane	0.74					not specified
	17689-77-9						

# Section 13. Disposal considerations

Waste disposal of product: Follow all local, state, federal and provincial regulations for disposal.

Cured rubber can be incinerated or landfilled following EPA and local regulations.

**Disposal for uncleaned package:** After use, tubes, cartons and bottles containing residual product should be disposed of as

chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

# Section 14. Transport information

SDS No.: 168444 V001.4

LOCTITE SI 596 known as Loc 596 Red RTV Sili gas-

300ml

#### Road and Rail Transport:

Dangerous Goods information: Classified as Dangerous Goods according to the criteria of the

Australian Code for the Transport of Dangerous Goods by Road and

Rail (ADG Code).

UN no.: 1760

Proper shipping name: CORROSIVE LIQUID, N.O.S.

(Ethyltriacetoxysilane, Methyltriacetoxysilane)

Class or division: 8
Packing group: III
Hazchem code: 2X

#### Marine transport IMDG:

UN no.: 1760

Proper shipping name: CORROSIVE LIQUID, N.O.S.

(Ethyltriacetoxysilane, Methyltriacetoxysilane)

Class or division: 8
Packing group: III
EmS: F-A,S-B

Seawater pollutant:

#### Air transport IATA:

UN no.: 1760

Proper shipping name: Corrosive liquid, n.o.s. (Ethyltriacetoxy silane, Methyltriacetoxy silane)

Class or division: 8
Packing group: III
Packing instructions (passenger) 852
Packing instructions (cargo) 856

# `Section 15. Regulatory information

SUSMP Poisons Schedule None

AICS: All components are listed or are exempt from listing on the Australian Inventory of

Chemical Substances (AICS).

# Section 16. Other information

Abbreviations/acronyms: ADGC - Australian Dangerous Goods Code

GHS: Globally Harmonized System CAS: Chemical Abstracts Service

OECD: Organization for Economic Cooperation and Development

LD 50: Lethal Dose 50% LC 50: Lethal Concentration 50%

IMDG: International Maritime Dangerous Goods code

IATA-DGR: International Air Transport Association – Dangerous Goods Regulations

**Reason for issue:** Reviewed SDS. Reissued with new date. involved chapters: 2,3,9,16

Page 8 of 8

SDS No.: 168444 V001.4

LOCTITE SI 596 known as Loc 596 Red RTV Sili gas-

300ml

Date of previous issue:

21.09.2015

Disclaimer:

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel Australia Pty. Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel Australia Pty. Limited concerning the properties of

The information contained in the Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel Australia Pty. Limited assumes no legal responsibility for reliance upon same. Henkel Australia Pty. Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Safety Data Sheet.

This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by either Commonwealth or State statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.

No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.