

Safety Data Sheet

Page 1 of 9

LOCTITE SF 790 CHISEL known as 790 Chisel Gasket Remove 510 gm

SDS No.: 153698 V001.3

Date of issue: 31.08.2020

Central nervous system

Section 1. Identification of the substance/preparation and of the company/undertaking

Product name: LOCTITE SF 790 CHISEL known as 790 Chisel Gasket Remove 510 gm

Intended use: Cleaner

Supplier:

Henkel Australia Pty Ltd 135-141 Canterbury Road Kilsyth, Victoria, 3137 Australia

Phone: +61 (3) 9724 6444

24 HOUR EMERGENCY CONTACT NUMBER: 1800 032 379 **Emergency information:**

Section 2. Hazards identification

Classification of the substance or mixture

Hazardous according to the criteria of Safe Work Australia.

GHS Classification:

Hazard Class Hazard Category Target organ

Flammable aerosols Category 2 Skin irritation Category 2 Serious eye irritation Category 2A Germ cell mutagenicity Category 1B Carcinogenicity Category 1A

Target Organ Systemic Toxicant -Category 2 Central nervous system

Single exposure

optic nerve

Target Organ Systemic Toxicant -

Single exposure

Category 3

Acute hazards to the aquatic environment

Category 3

Hazard pictogram:



Signal word: Danger SDS No.: 153698 V001.3

LOCTITE SF 790 CHISEL known as 790 Chisel Gasket

Remove 510 gm

Hazard statement(s): H223 Flammable aerosol.

H315 Causes skin irritation.

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

H340 May cause genetic defects.

H350 May cause cancer.

H371 May cause damage to organs. H402 Harmful to aquatic life.

Precautionary Statement(s):

Prevention: P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling.

P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves, eye protection, and face protection.

P281 Use personal protective equipment as required.

Response: P302+P352 IF ON SKIN: Wash with plenty of water.

P304+P340+P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention. P332+P313 If skin irritation occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention.

P362 Take off contaminated clothing.

Storage: P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal: P501 Dispose of contents/container to an appropriate treatment and disposal facility in

accordance with applicable laws and regulations.

Dangerous Goods information:

Classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

Section 3. Composition / information on ingredients

General chemical description: Mixture

Identity of ingredients:

Chemical ingredients	CAS-No.	Proportion
dichloromethane	75-09-2	60- < 100 %
Petroleum gases, liquified, sweetened	68476-86-8	10- < 30 %
methanol	67-56-1	1- < 10 %
non hazardous ingredients~		< 10 %

Page 3 of 9

SDS No.: 153698 V001.3

LOCTITE SF 790 CHISEL known as 790 Chisel Gasket

Remove 510 gm

Section 4. First aid measures

Ingestion: Do not induce vomiting.

Have victim rinse mouth thoroughly with water.

Get immediate medical attention.

Skin: Immediately flush skin with plenty of water (using soap, if available).

Seek medical advice.

Eyes: Immediately flush eyes with plenty of water for at least 15 minutes.

Get medical attention.

Inhalation: Move to fresh air in case of accidental inhalation of vapours.

Keep warm and in a quiet place.

Seek medical advice.

First Aid facilities: Eye wash and safety shower

Normal washroom facilities

Medical attention and special

treatment:

Treat symptomatically.

Section 5. Fire fighting measures

Suitable extinguishing media: Foam, dry chemical or carbon dioxide.

Water Fog

Decomposition products in case of

fire:

Thermal decomposition can lead to release of irritating gases and vapors.

Irritating organic vapours.

Phosgene.

Hydrogen chloride. Oxides of carbon.

Particular danger in case of fire: WARNING FLAMMABLE!

Vapours may accumulate in low or confined areas, travel considerable distance to source

of ignition, and flash back. Explosive rupture is possible.

Special protective equipment for

fire-fighters:

Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA).

Wear full protective clothing.

Additional fire fighting advice: In case of fire, keep containers cool with water spray.

Section 6. Accidental release measures

Personal precautions: Avoid contact with skin and eyes.

Wear impervious gloves and chemical splash goggles.

Avoid inhalation of vapor, fumes, dust and/or mist from the spilled material.

See advice in section 8

Environmental precautions: Do not empty into drains / surface water / ground water.

Clean-up methods: Wear appropriate personal protective equipment.

Ventilate area.

Eliminate all sources of ignition or flammables that may come into contact with a spill of

this material.

Absorb the spilled material with an inert absorbent (nonflammable) material.

Store in a closed container until ready for disposal.

Page 4 of 9

SDS No.: 153698 V001.3

LOCTITE SF 790 CHISEL known as 790 Chisel Gasket

Remove 510 gm

Section 7. Handling and storage

Precautions for safe handling: Keep away from heat, spark and flame.

Ensure adequate ventilation.

Wear suitable protective clothing, safety glasses and gloves.

Conditions for safe storage: Do not store or use near heat, spark, open flame or other sources of ignition.

Do not puncture, incinerate, or expose to temperatures above 48.9 $^{\circ}$ C (120 $^{\circ}$ F).

Store in a cool, dry place.

Section 8. Exposure controls / personal protection

National exposure standards:

Ingredient [Regulated substance]	form of	TWA (ppm)	TWA	Peak Limit.	Peak Limit.	STEL (ppm)	STEL
	exposure		(mg/m3)	(ppm)	(mg/m3)		(mg/m3)
METHYLENE CHLORIDE		50	174				
75-09-2							
METHYL ALCOHOL		200	262				
67-56-1							
METHYL ALCOHOL						250	328
67-56-1							

Engineering controls: Use only in well ventilated areas.

Use local exhaust ventilation if the potential for airborne exposure exists.

Eye protection: For eye protection, use tightly fitted safety goggles and a face-shield

Skin protection: Wear protective equipment.

The use of polyvinyl alcohol (PVA) gloves is recommended.

Protective clothing that covers arms and legs.

Please note that in practice the working life of chemical resistant gloves may be considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed

then the gloves should be replaced.

Respiratory protection: If inhalation risk exists, wear a respirator or air supplied mask complying with the

requirements of AS/NZS 1715 and AS/NZS 1716.

Section 9. Physical and chemical properties

Appearance: grey, to, Off white

Aerosol
Odor: Sharp, Solvent

Specific gravity: 0.789

Flash point: < 5 °C (< 41 °F) Flammability (solid, gas): Highly flammable.

Lower explosive limit: 1.5 %(V)
Upper explosive limit: 9.5 %(V)
Solubility in water: Slightly soluble
VOC content: 30 % 237 g/l

Section 10. Stability and reactivity

Conditions to avoid: Heat, flames, sparks and other sources of ignition.

Page 5 of 9

SDS No.: 153698 V001.3

LOCTITE SF 790 CHISEL known as 790 Chisel Gasket

Remove 510 gm

Incompatible materials: Strong oxidizing agents.

Potassium. Strong alkalis. Sodium. Reactive metals.

Hazardous decomposition

products:

Thermal decomposition can lead to release of irritating gases and vapors.

Hydrogen chloride. Oxides of carbon.

Irritating organic vapours.

Phosgene.

Hazardous polymerization: Will not occur.

Section 11. Toxicological information

Health Effects:

Ingestion: Harmful if swallowed.

Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Skin: This product is irritating to the skin.

Symptoms may include redness, edema, drying, defatting and cracking of the skin.

Eyes: Causes serious eye irritation.

Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Inhalation: Vapours may cause drowsiness and dizziness.

Inhalation of vapors may cause moderate to severe respiratory tract irritation.

Chronic effects: Studies on rodents have suggested that an ingredient in this product, when fed at high levels in the

diet, may have cancer-causing potential.

dichloromethane

75-09-2:

75-09-2: methanol

67-56-1:

The tumour risk cannot yet be evaluated conclusively, low tumour risk for the liver.

Neurological symptoms; irritation to the nasal mucous membranes through exposure to higher vapor concentrations; headaches, blurred vision and nausea; damage to the skin due to repeated

contact; prenatal toxic effects were seen in rats and mice.

Carcinogenicity: Category 1A (Carcinogen), May cause cancer.

Mutagenicity: Category 1B (Mutagen), This product contains an ingredient which has been associated with

mutagenicity effects.

Acute toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time		
dichloromethane	LD50	2,120 mg/kg	oral		rat	not specified
75-09-2	LC50	86 mg/l	inhalation	4 h	mouse	not specified
	LD50	> 2,000 mg/kg	dermal		rat	OECD Guideline 402 (Acute
						Dermal Toxicity)
methanol	Acute	300 mg/kg	oral			Expert judgement
67-56-1	toxicity					
	estimate					
	(ATE)					

Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
dichloromethane 75-09-2	irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
methanol 67-56-1	not irritating	20 h	rabbit	BASF Test

SDS No.: 153698 V001.3

LOCTITE SF 790 CHISEL known as 790 Chisel Gasket

Remove 510 gm

Serious eye damage/irritation:

Hazardous components	Result	Exposure	Species	Method
CAS-No.		time		
dichloromethane 75-09-2	irritating		rabbit	not specified
methanol	not irritating		rabbit	OECD Guideline 405 (Acute
67-56-1				Eye Irritation / Corrosion)

Respiratory or skin sensitization:

Hazardous components	Result	Test type	Species	Method
CAS-No.				
dichloromethane	not sensitising	Mouse	mouse	OECD Guideline 429 (Skin
75-09-2	_	local		Sensitisation: Local Lymph
		lymphnod		Node Assay)
		e assay		
		(LLNA)		
methanol	not sensitising	Guinea pig	guinea pig	OECD Guideline 406 (Skin
67-56-1		maximisat		Sensitisation)
		ion test		

Germ cell mutagenicity:

Hazardous components	Result	Type of study /	Metabolic	Species	Method
CAS-No.		Route of	activation /		
		administration	Exposure time		
dichloromethane	positive	bacterial reverse	with and without		OECD Guideline 471
75-09-2	positive	mutation assay (e.g	with and without		(Bacterial Reverse Mutation
		Ames test)			Assay)
		in vitro mammalian			OECD Guideline 473 (In vitro
		chromosome			Mammalian Chromosome
		aberration test			Aberration Test)
dichloromethane	negative	oral: gavage		mouse	OECD Guideline 474
75-09-2					(Mammalian Erythrocyte
					Micronucleus Test)
methanol	negative	bacterial reverse	with and without		OECD Guideline 471
67-56-1	negative	mutation assay (e.g	without		(Bacterial Reverse Mutation
	negative	Ames test)	with and without		Assay)
		in vitro mammalian			not specified
		cell micronucleus			equivalent or similar to OECD
		test			Guideline 476 (In vitro
		mammalian cell			Mammalian Cell Gene
		gene mutation assay			Mutation Test)
methanol	negative	intraperitoneal		mouse	equivalent or similar to OECD
67-56-1					Guideline 474 (Mammalian
					Erythrocyte Micronucleus
					Test)

Repeated dose toxicity:

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
dichloromethane 75-09-2	NOAEL=6 mg/kg	oral: drinking water	104 wdaily	rat	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
methanol 67-56-1	NOAEL=6.63 mg/l	inhalation	4 weeks6 h/d, 5 d/w	rat	not specified
methanol 67-56-1	NOAEL=0.13 mg/l	inhalation	12 m20 h/d	rat	equivalent or similar to OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

Section 12. Ecological information

SDS No.: 153698 V001.3

LOCTITE SF 790 CHISEL known as 790 Chisel Gasket

Remove 510 gm

General ecological information: Do not empty into drains / surface water / ground water.

Harmful to aquatic life with long lasting effects. **Ecotoxicity:**

Toxicity:

Hazardous components CAS-No.	Value type	Value	Acute Toxicity	Exposure time	Species	Method
			Study			
dichloromethane	LC50	193 mg/l	Fish	96 h	Pimephales promelas	OECD Guideline
75-09-2						203 (Fish, Acute
						Toxicity Test)
dichloromethane 75-09-2	NOEC	83 mg/l	Fish	28 d	Pimephales promelas	other guideline:
dichloromethane	EC50	27 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline
75-09-2						202 (Daphnia sp.
						Acute
						Immobilisation
						Test)
dichloromethane	EC50	> 660 mg/l	Algae	96 h	Selenastrum capricornutum	OECD Guideline
75-09-2					(new name: Pseudokirchneriella	
					subcapitata)	Inhibition Test)
dichloromethane	EC50	2,590 mg/l	Bacteria	40 min	activated sludge, domestic	OECD Guideline
75-09-2						209 (Activated
						Sludge, Respiration
	7.050	4.7.400 #		0.51		Inhibition Test)
methanol	LC50	15,400 mg/l	Fish	96 h	Lepomis macrochirus	EPA-660 (Methods
67-56-1						for Acute Toxicity
						Tests with Fish,
						Macroinvertebrates
.1 1	NOEG	7,000 //	F: 1	200.1	0 : 1:	and Amphibians)
methanol 67-56-1	NOEC	7,900 mg/l	Fish	200 h	Oryzias latipes	OECD Guideline
07-30-1						210 (fish early lite
methanol	EC50	18,260 mg/l	Daphnia	96 h	Daphnia magna	stage toxicity test) OECD Guideline
67-56-1	ECSU	18,200 Hig/I	Dapinna	90 11	Б арппа падпа	202 (Daphnia sp.
07-30-1						Acute
						Immobilisation
						Test)
methanol	EC50	22,000 mg/l	Algae	96 h	Selenastrum capricornutum	OECD Guideline
67-56-1	ECSO	22,000 mg/1	Aigae	90 II	(new name: Pseudokirchneriella	
07 30 1					subcapitata)	Inhibition Test)
methanol	IC50	> 1,000 mg/l	Bacteria	3 h	activated sludge of a	OECD Guideline
67-56-1	1030	/ 1,000 mg/1	Daciella	311	predominantly domestic sewage	
0, 30 1					predominantly domestic sewage	Sludge, Respiration
						Inhibition Test)
1	1 1		1	1	1	

Persistence and degradability:

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
dichloromethane 75-09-2	readily biodegradable	aerobic	68 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
methanol 67-56-1	readily biodegradable	aerobic	82 - 92 %	EU Method C.4-E (Determination of the "Ready" BiodegradabilityClosed Bottle Test)

Bioaccumulative potential / Mobility in soil:

Hazardous components	LogPow	Bioconcentration	Exposure	Species	Temperature	Method
CAS-No.		factor (BCF)	time			

Page 8 of 9

SDS No.: 153698 V001.3

LOCTITE SF 790 CHISEL known as 790 Chisel Gasket Remove 510 gm

dichloromethane 75-09-2		2 - 40	42 d	Cyprinus carpio	25 °C	OECD Guideline 305 (Bioconcentration: Flow- through Fish Test)
dichloromethane 75-09-2	1.25				20 °C	OECD Guideline 107 (Partition Coefficient (noctanol / water), Shake Flask Method)
methanol 67-56-1	-0.77					other guideline:

Section 13. Disposal considerations

Waste disposal of product: Do not puncture or incinerate pressurized containers.

Dispose of according to regulations.

Disposal for uncleaned package: Disposal must be made according to official regulations.

Section 14. Transport information

Road and Rail Transport:

Dangerous Goods information: Classified as Dangerous Goods according to the criteria of the

Australian Code for the Transport of Dangerous Goods by Road and

Rail (ADG Code).

UN no.: 1950
Proper shipping name: AEROSOLS
Class or division: 2.1 (6.1)

Packing group:

Emergency information: Refer to the Dangerous Goods - Initial Emergency Response Guide

HB 76.

Marine transport IMDG:

UN no.: 1950

Proper shipping name: AEROSOLS (Methylene chloride)

Class or division: 2.1 (6.1)

Packing group:

EmS: F-D, S-U

Seawater pollutant:

Air transport IATA:

UN no.: 1950

Proper shipping name: Aerosols, flammable, containing substances in Division 6.1, Packing

Group III

Class or division: 2.1 (6.1)

Packing group:

Packing instructions (passenger) 203 Packing instructions (cargo) 203

Section 15. Regulatory information

SUSMP Poisons Schedule 5

AICS: All components are listed or are exempt from listing on the Australian Inventory of

Chemical Substances (AICS).

Page 9 of 9

SDS No.: 153698 V001.3

LOCTITE SF 790 CHISEL known as 790 Chisel Gasket

Remove 510 gm

Section 16. Other information

Abbreviations/acronyms: ADGC - Australian Dangerous Goods Code

GHS: Globally Harmonized System CAS: Chemical Abstracts Service

OECD: Organization for Economic Cooperation and Development

LD 50: Lethal Dose 50%

LC 50: Lethal Concentration 50%

IMDG: International Maritime Dangerous Goods code

IATA-DGR: International Air Transport Association - Dangerous Goods Regulations

STEL - Short term exposure limit TWA - Time weighted average

Reason for issue: Reviewed SDS. Reissued with new date. involved chapters: 2,3,12,16

Date of previous issue: 10.09.2015

Disclaimer:

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel Australia Pty. Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel Australia Pty. Limited concerning the properties of the material

The information contained in the Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel Australia Pty. Limited assumes no legal responsibility for reliance upon same. Henkel Australia Pty. Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Safety Data Sheet.

This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by either Commonwealth or State statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.

No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.