



## Safety Data Sheet

Page 1 of 9

LOCTITE SI 5699 known as 5699 Grey High Performance RTV

SDS No. : 152852

V001.3

Date of issue: 27.04.2020

### Section 1. Identification of the substance/preparation and of the company/undertaking

**Product name:** LOCTITE SI 5699 known as 5699 Grey High Performance RTV

**Intended use:** Silicone sealant

**Supplier:**  
Henkel Australia Pty Ltd  
135-141 Canterbury Road  
Kilsyth, Victoria, 3137  
Australia

Phone: +61 (3) 9724 6444

**Emergency information:** 24 HOUR EMERGENCY CONTACT NUMBER: 1800 032 379

### Section 2. Hazards identification

#### Classification of the substance or mixture

Hazardous according to the criteria of Safe Work Australia.

#### GHS Classification:

<u>Hazard Class</u>	<u>Hazard Category</u>
Serious eye damage/eye irritation	Category 2A
Skin sensitizer	Category 1
Carcinogenicity	Category 2

#### Hazard pictogram:



#### Signal word:

Warning

**Hazard statement(s):** H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H351 Suspected of causing cancer.

**Precautionary Statement(s):**

**Prevention:** P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P264 Wash hands thoroughly after handling.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P280 Wear protective gloves, clothing, eye and face protection.

**Response:** P302+P352 IF ON SKIN: Wash with plenty of water.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308+P313 IF exposed or concerned: Get medical advice/attention.  
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
P337+P313 If eye irritation persists: Get medical advice/attention.  
P363 Wash contaminated clothing before reuse.

**Storage:** P405 Store locked up.

**Disposal:** P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

**Dangerous Goods information:**

Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

**Signal word:**

HAZARDOUS

**Section 3. Composition / information on ingredients**

**General chemical description:** Mixture  
**Type of preparation:** Silicone sealant

**Identity of ingredients:**

Chemical ingredients	CAS-No.	Proportion
Calcium carbonate	471-34-1	10- 30 %
Butan-2-one O,O',O''-(vinylsilyldiylidene)trioxime	2224-33-1	< 10 %
2-butanone oxime	96-29-7	< 3 %
non hazardous ingredients~		60- 100 %

**Section 4. First aid measures**

**Ingestion:** Do not induce vomiting.  
Have victim rinse mouth thoroughly with water.  
Seek medical advice.

**Skin:** Rinse with running water and soap.  
Seek medical advice.

<b>Eyes:</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Seek medical advice.
<b>Inhalation:</b>	Move to fresh air. If symptoms persist, seek medical advice.
<b>First Aid facilities:</b>	Eye wash and safety shower Normal washroom facilities
<b>Medical attention and special treatment:</b>	Treat symptomatically.

### Section 5. Fire fighting measures

<b>Suitable extinguishing media:</b>	Dry chemical. Carbon dioxide. foam
<b>Decomposition products in case of fire:</b>	Thermal decomposition can lead to release of irritating gases and vapors. Carbon monoxide. Carbon dioxide. Oxides of silicon. Formaldehyde.
<b>Special protective equipment for fire-fighters:</b>	Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA). Wear full protective clothing.

### Section 6. Accidental release measures

<b>Personal precautions:</b>	Avoid contact with skin and eyes. Wear protective equipment.
<b>Environmental precautions:</b>	Do not let product enter drains.
<b>Clean-up methods:</b>	Scrape up as much material as possible. Ensure adequate ventilation. Store in a partly filled, closed container until disposal.

### Section 7. Handling and storage

<b>Precautions for safe handling:</b>	Use only in well-ventilated areas. Vapours should be extracted to avoid inhalation. Wear protective equipment.
<b>Conditions for safe storage:</b>	Store only in the original container. Store in a cool, well-ventilated place.

### Section 8. Exposure controls / personal protection

**National exposure standards:**

- Engineering controls:** Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.
- Eye protection:** Safety goggles or safety glasses with side shields.
- Skin protection:** Use impermeable gloves and protective clothing as necessary to prevent skin contact. The use of chemical resistant gloves such as Nitrile is recommended. Please note that in practice the working life of chemical resistant gloves may be considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed then the gloves should be replaced.
- Respiratory protection:** If inhalation risk exists, wear a respirator or air supplied mask complying with the requirements of AS/NZS 1715 and AS/NZS 1716.

**Section 9. Physical and chemical properties**

- Appearance:** grey  
paste
- Odor:** odourless
- pH:** Not applicable
- Melting point / freezing point:** Not available.
- Specific gravity:** 1.5
- Boiling point:** > 200 °C (> 392 °F)
- Flash point:** > 93 °C (> 199.4 °F)
- Vapor pressure:** < 5 mm hg
- Vapor density:** Heavier than air.
- Density:** 1.5 g/cm<sup>3</sup>

**Section 10. Stability and reactivity**

- Stability:** Stable under normal conditions of temperature and pressure.
- Conditions to avoid:** Exposure to air or moisture over prolonged periods. Avoid temperatures above 150°C (302°F).
- Incompatible materials:** Acids and bases.  
Oxidizing agents.  
Polymerizes on contact with water.
- Hazardous decomposition products:** Thermal decomposition can lead to release of irritating gases and vapors.  
  
Carbon monoxide.  
Carbon dioxide.  
Oxides of silicon.  
Formaldehyde  
Methyl ethyl ketoxime formed during cure.  
Methanol is liberated slowly upon exposure to moisture.
- Hazardous polymerization:** Will not occur.

**Section 11. Toxicological information**

**Health Effects:****Ingestion:**

Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

**Skin:**

May cause mild skin irritation.

Symptoms may include redness, edema, drying, defatting and cracking of the skin.

May cause skin sensitization.

**Eyes:**

Causes serious eye irritation.

Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

**Inhalation:**

Inhalation of vapors or mists of the product may be irritating to the respiratory system.

**Carcinogenicity:**

Suspected of causing cancer.

**Acute toxicity:**

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Calcium carbonate 471-34-1	LD50 LC50 LD50	> 2,000 mg/kg > 3 mg/l > 2,000 mg/kg	oral inhalation dermal	4 h	rat rat rat	OECD Guideline 420 (Acute Oral Toxicity) OECD Guideline 403 (Acute Inhalation Toxicity) OECD Guideline 402 (Acute Dermal Toxicity)
Butan-2-one O,O',O''-( vinylsilylidyne)trioxime 2224-33-1	LD50 LD50	> 2,000 mg/kg > 2,009 mg/kg	oral  dermal		rat rat	OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure) OECD Guideline 402 (Acute Dermal Toxicity)
2-butanone oxime 96-29-7	LD50 Acute toxicity estimate (ATE) LD50	2,326 mg/kg 1,100 mg/kg > 1,000 mg/kg	oral  dermal dermal		rat  rabbit	OECD Guideline 401 (Acute Oral Toxicity) Expert judgement OECD Guideline 402 (Acute Dermal Toxicity)

**Skin corrosion/irritation:**

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Calcium carbonate 471-34-1	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
2-butanone oxime 96-29-7	slightly irritating	24 h	rabbit	not specified

**Serious eye damage/irritation:**

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Calcium carbonate 471-34-1	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
2-butanone oxime 96-29-7	Category 1 (irreversible effects on the eye)		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

**Respiratory or skin sensitization:**

Hazardous components CAS-No.	Result	Test type	Species	Method
Calcium carbonate 471-34-1	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Butan-2-one O,O',O''-( vinylsilylidyne)trioxime 2224-33-1	Sensitizing	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
2-butanone oxime 96-29-7	sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

**Germ cell mutagenicity:**

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Calcium carbonate 471-34-1	negative negative negative	bacterial reverse mutation assay (e.g Ames test) in vitro mammalian chromosome aberration test mammalian cell gene mutation assay	with and without with and without with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay) OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Butan-2-one O,O',O''- (vinylsilylidyne)trioxime 2224-33-1	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Butan-2-one O,O',O''- (vinylsilylidyne)trioxime 2224-33-1	negative	intraperitoneal		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
2-butanone oxime 96-29-7	negative negative negative	bacterial reverse mutation assay (e.g Ames test) mammalian cell gene mutation assay DNA damage and repair assay, unscheduled DNA synthesis in mammalian cells in vitro	with and without with		EPA OPPTS 870.5265 (The Salmonella typhimurium Bacterial Reverse Mutation Test) OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) OECD Guideline 482 (Genetic Toxicology: DNA Damage and Repair, Unscheduled DNA Synthesis in Mammalian Cells In Vitro)
2-butanone oxime 96-29-7	negative negative	oral: gavage oral: feed		rat Drosophila melanogaster	EPA OPPTS 870.5385 (In Vivo Mammalian Cytogenetic Tests: Bone Marrow Chromosomal Analysis) EPA OPPTS 870.5385 (In Vivo Mammalian Cytogenetic Tests: Bone Marrow Chromosomal Analysis)

**Repeated dose toxicity:**

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
Calcium carbonate 471-34-1	NOAEL=1,000 mg/kg	oral: gavage	48 ddaily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Butan-2-one O,O',O''- (vinylsilylidyne)trioxime 2224-33-1	NOAEL=10 mg/kg	oral: gavage		rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
2-butanone oxime 96-29-7	LOAEL=40 mg/kg	oral: gavage	13 wdaily	rat	not specified

**Section 12. Ecological information**

**General ecological information:**

Cured Loctite products are typical polymers and do not pose any immediate environmental hazards., Precautions required with respect to Environmental Hazards of articles in which this product is used should be considered., Do not empty into drains / surface water / ground water.

**Toxicity:**

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
Calcium carbonate 471-34-1	NOEC	14 mg/l	Algae	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
Butan-2-one O,O',O''-(vinylsilylidene)trioxime 2224-33-1	LC50	> 560 mg/l	Fish	96 h	Brachydanio rerio (new name: Danio rerio)	OECD Guideline 203 (Fish, Acute Toxicity Test)
Butan-2-one O,O',O''-(vinylsilylidene)trioxime 2224-33-1	NOEC	50 mg/l	Fish	14 d	Oryzias latipes	OECD Guideline 204 (Fish, Prolonged Toxicity Test: 14-day Study)
Butan-2-one O,O',O''-(vinylsilylidene)trioxime 2224-33-1	EC50	201 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Butan-2-one O,O',O''-(vinylsilylidene)trioxime 2224-33-1	EC50	94 mg/l	Algae	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Butan-2-one O,O',O''-(vinylsilylidene)trioxime 2224-33-1	NOEC	30 mg/l	Algae	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-butanone oxime 96-29-7	LC50	320 - 1,000 mg/l	Fish	96 h	Leuciscus idus	DIN 38412-15
2-butanone oxime 96-29-7	NOEC	50 mg/l	Fish	14 d	Oryzias latipes	OECD Guideline 204 (Fish, Prolonged Toxicity Test: 14-day Study)
2-butanone oxime 96-29-7	EC50	> 500 mg/l	Daphnia	48 h	Daphnia magna	EU Method C.2 (Acute Toxicity for Daphnia)
2-butanone oxime 96-29-7	EC50	11.8 mg/l	Algae	72 h	Scenedesmus capricornutum	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-butanone oxime 96-29-7	NOEC	2.56 mg/l	Algae	72 h	Scenedesmus capricornutum	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-butanone oxime 96-29-7	EC10	177 mg/l	Bacteria	17 h		DIN 38412, part 8 (Pseudomonas Zellvermehrungshe mm-Test)

**Persistence and degradability:**

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
Calcium carbonate 471-34-1	readily biodegradable	aerobic	90 %	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Butan-2-one O,O',O''-(vinylsilylidene)trioxime 2224-33-1	not readily biodegradable.	aerobic	26 %	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
2-butanone oxime 96-29-7	inherently biodegradable	aerobic	70 %	OECD Guideline 302 B (Inherent biodegradability: Zahn-Wellens/EMPA Test)

**Bioaccumulative potential / Mobility in soil:**

Hazardous components CAS-No.	LogPow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
------------------------------	--------	-------------------------------	---------------	---------	-------------	--------

Calcium carbonate 471-34-1	-2.12					QSAR (Quantitative Structure Activity Relationship)
2-butanone oxime 96-29-7		0.5 - 0.6	42 d	Oryzias latipes	25 °C	OECD Guideline 305 C (Bioaccumulation: Test for the Degree of Bioconcentration in Fish)
2-butanone oxime 96-29-7	0.65				25 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)

### Section 13. Disposal considerations

**Waste disposal of product:** Dispose of in accordance with local and national regulations. Contribution of this product to waste is very insignificant in comparison to article in which it is used

**Disposal for uncleaned package:** After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated. Disposal must be made according to official regulations.

### Section 14. Transport information

**Road and Rail Transport:**

Dangerous Goods information: Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

**Marine transport IMDG:**

Not dangerous goods

**Air transport IATA:**

Not dangerous goods

### Section 15. Regulatory information

**SUSMP Poisons Schedule** 6

**AICS:** All components are listed or are exempt from listing on the Australian Inventory of Chemical Substances (AICS).

### Section 16. Other information

**Abbreviations/acronyms:** ADGC - Australian Dangerous Goods Code  
GHS: Globally Harmonized System  
CAS: Chemical Abstracts Service  
LD 50: Lethal Dose 50%  
LC 50: Lethal Concentration 50%  
OECD: Organization for Economic Cooperation and Development  
IMDG: International Maritime Dangerous Goods code  
IATA-DGR: International Air Transport Association – Dangerous Goods Regulations  
STEL - Short term exposure limit  
TWA - Time weighted average

**Reason for issue:** Reviewed SDS. Reissued with new date. involved chapters: 1,2,15,16

---

**Date of previous issue:** 07.05.2015

**Disclaimer:**

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel Australia Pty. Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel Australia Pty. Limited concerning the properties of the material.

The information contained in the Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel Australia Pty. Limited assumes no legal responsibility for reliance upon same. Henkel Australia Pty. Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Safety Data Sheet.

This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by either Commonwealth or State statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.

No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.