

Safety Data Sheet

OSI HM270 Construction Silicone Sealant

Page 1 of 7

SDS No.: 175013

V001.3

Date of issue: 02.06.2020

Section 1. Identification of the substance/preparation and of the company/undertaking

Product name: OSI HM 270 Construction Silicone Sealant

Intended use: Silicone sealant

Supplier:

Henkel Australia Pty Ltd 135-141 Canterbury Road Kilsyth, Victoria, 3137 Australia

Phone: +61 (3) 9724 6444

Emergency information: 24 HOUR EMERGENCY CONTACT NUMBER: 1800 032 379

Section 2. Hazards identification

Classification of the substance or mixture

Hazardous according to the criteria of Safe Work Australia.

GHS Classification:

Hazard ClassHazard CategorySkin irritationCategory 2Serious eye irritationCategory 2

Hazard pictogram:

Signal word:

Danger

OSI HM270 Construction Silicone Sealant

Hazard statement(s): H315 Causes skin irritation.

H319 Causes serious eye irritation.

Precautionary Statement(s):

Prevention: P264 Wash hands thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response: P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P332+P313 If skin irritation occurs: Get medical attention. P337+P313 If eye irritation persists: Get medical attention.

P362 Take off contaminated clothing.

Disposal: P501 Dispose of contents/container to an appropriate treatment and disposal facility in

accordance with applicable laws and regulations, and product characteristics at time of

disposal.

Dangerous Goods information:

Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

Section 3. Composition / information on ingredients

General chemical description: Mixture

resins

Type of preparation: Acetoxy curing silicone

Identity of ingredients:

Chemical ingredients	CAS-No.	Proportion
Silicon dioxide	7631-86-9	< 10 %
Cyclosiloxanes, di-Me	69430-24-6	< 10 %
non hazardous ingredients~		< 85 %

Section 4. First aid measures

Ingestion: Do not induce vomiting.

Have victim rinse mouth thoroughly with water.

Seek medical advice.

Skin: In case of contact, immediately remove contaminated clothing and flush skin with copious

amounts of water. Seek medical advice.

Eyes: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Seek medical advice.

Inhalation: Move to fresh air.

Keep warm and in a quiet place.

Seek medical advice.

First Aid facilities: Eye wash and safety shower

Normal washroom facilities

V001.3

Medical attention and special

treatment:

Treat symptomatically.

Section 5. Fire fighting measures

Suitable extinguishing media: Carbon dioxide, foam, powder

fire:

Decomposition products in case of Thermal decomposition can lead to release of irritating gases and vapors.

carbon monoxide Carbon dioxide. Oxides of nitrogen. Formaldehy de

Special protective equipment for

fire-fighters:

Wear full protective clothing.

Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA).

Additional fire fighting advice: In case of fire, keep containers cool with water spray.

Section 6. Accidental release measures

Personal precautions: Avoid contact with skin and eyes.

> Ensure adequate ventilation. Wear protective equipment.

Environmental precautions: Do not let product enter drains.

Clean-up methods: Scrape up as much material as possible.

Ensure adequate ventilation.

Store in a partly filled, closed container until disposal.

Dispose of contaminated material as waste according to Section 13.

Section 7. Handling and storage

Precautions for safe handling: Ensure that workrooms are adequately ventilated.

Avoid contact with eyes, skin and clothing.

Wear suitable protective clothing, safety glasses and gloves.

Conditions for safe storage: Keep container tightly sealed.

Do not store or use near heat, spark, open flame or other sources of ignition.

Store in a cool, well-ventilated place.

Section 8. Exposure controls / personal protection

National exposure standards:

In gre dient [Regulated substance]	form of	TWA (ppm)	TWA	Peak Limit.	Peak Limit.	STEL (ppm)	STEL
	exposure		(mg/m3)	(ppm)	(mg/m3)		(mg/m3)
OIL MIST, REFINED MINERAL 64742-46-7			5				
ACETIC ACID 64-19-7						15	37
ACETIC ACID 64-19-7		10	25				

Page 4 of 7

SDS No.: 175013 V001.3

OSI HM270 Construction Silicone Sealant

SILICA, AMORPHOUS: FUMED SILICA (RESPIRABLE DUST) 7631-86-9	Respirable dust.	2		
FUMED SILICA (RESPIRABLE	Respirable	2		
DUST)	dust.			
7631-86-9				

Engineering controls: Ensure good ventilation/extraction.

Eye protection: For eye protection, use tightly fitted safety goggles and a face-shield

Skin protection: Wear suitable protective clothing.

Protective gloves made of rubber.

Respiratory protection: If inhalation risk exists, wear a respirator or air supplied mask complying with the

requirements of AS/NZS 1715 and AS/NZS 1716.

Section 9. Physical and chemical properties

Appearance: Clear to slightly hazy

homogeneous, paste

Specific gravity: 1.01

Flash point: $> 93 \, ^{\circ}\text{C} \, (> 199.4 \, ^{\circ}\text{F})$

Lower explosive limit: 4 %(V)
Upper explosive limit: 19.9 %(V)
Vapor pressure: < 10 mm hg

(; 20 °C (68 °F))

 Vapor density:
 Heavier than air.

 Density:
 1.01 g/cm3

 VOC content:
 3.0 % 30 g/l

Section 10. Stability and reactivity

Stability: Stable under recommended storage conditions.

Conditions to avoid: Extremes of temperature.

Humidity.

Incompatible materials: Strong oxidizing agents.

Polymerises in presence of water. Reaction with strong acids. Reaction with strong bases

Hazardous decomposition

products:

Thermal decomposition can lead to release of irritating gases and vapors.

Carbon monoxide. Carbon dioxide. Oxides of nitrogen.

At higher temperatures (>150C) may release formaldehyde (traces). Acetic acid is liberated slowly upon contact with moisture.

Section 11. Toxicological information

Health Effects:

Ingestion: Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Skin: Causes skin irritation.

Symptoms may include redness, edema, drying, defatting and cracking of the skin.

May cause skin sensitization.

Eyes: Causes serious eye damage.

Contact with the eyes may cause moderate to severe eye injury. Eye contact may result in corneal injury. Symptoms may include discomfort or pain, excess blinking and tear production, with

marked redness and swelling of the conjunctiva.

Inhalation: Inhalation of vapors or mists of the product may be irritating to the respiratory system.

Acute toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time		
Silicon dioxide	LD50	> 5,000 mg/kg	oral		rat	OECD Guideline 401 (Acute
7631-86-9	LC50	> 2.08 mg/l	inhalation	4 h	rat	Oral Toxicity)
	LD50	$> 5,000 \mathrm{mg/kg}$	dermal		rabbit	OECD Guideline 403 (Acute
						Inhalation Toxicity)
						not specified
Cyclosiloxanes, di-Me 69430-24-6	LD50	> 2,400 mg/kg	dermal		rat	not specified

Skin corrosion/irritation:

Hazardous components	Result	Exposure	Species	Method
CAS-No.		time		
Silicon dioxide	not irritating	4 h	rabbit	OECD Guideline 404 (Acute
7631-86-9	-			Dermal Irritation / Corrosion)

Serious eye damage/irritation:

Hazardous components	Result	Exposure	Species	Method
CAS-No.		time		
Silicon dioxide	not irritating		rabbit	OECD Guideline 405 (Acute
7631-86-9				Eye Irritation / Corrosion)

Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study/ Route of	Metabolic activation/	Species	Method
CAS-No.		administration	Exposure time		
Silicon dioxide 7631-86-9	negative negative negative	bacterial reverse mutation assay (e.g Ames test) mammalian cell gene mutation assay in vitro mammalian chromosome aberration test	with and without with and without with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay) OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Silicon dioxide 7631-86-9	negative	inhalation		rat	not specified

Repeated dose toxicity:

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
Silicon dioxide 7631-86-9	NOAEL=>4,000 - 4,500 mg/kg	oral: feed	13 weeksdaily	rat	equivalent or similar to OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Silicon dioxide 7631-86-9	NOAEL=1.3 mg/m3	inhalation	13 w6 h/d, 5 d/w	rat	equivalent or similar to OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)

Section 12. Ecological information

General ecological information: Do not e

Do not empty into drains / surface water / ground water.

Toxicity:

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
Silicon dioxide	LC50	> 10,000 mg/l	Fish	96 h	Brachydanio rerio (new name:	OECD Guideline
7631-86-9		, ,			Danio rerio)	203 (Fish, Acute
					,	Toxicity Test)
Silicon dioxide	EL50	> 1,000 mg/l	Daphnia	24 h	Daphnia magna	OECD Guideline
7631-86-9						202 (Daphnia sp.
						Acute
						Immobilisation
						Test)
Silicon dioxide	NOELR	10,000 mg/l	Algae	72 h	Desmodesmus subspicatus	OECD Guideline
7631-86-9						201 (Alga, Growth
C.1. 1 1	EL 50	10.000 //		70.1		Inhibition Test)
Silicon dioxide	EL50	> 10,000 mg/l	Algae	72 h	Desmodesmus subspicatus	OECD Guideline
7631-86-9						201 (Alga, Growth
Silicon dioxide	EC0	10,000 mg/l	Bacteria	30 min	Daaydamanaa nytida	Inhibition Test) DIN 38412, part 27
7631-86-9	ECU	10,000 mg1	Dacteria	30 11111	Pseudomonas putida	(Bacterial oxygen
7031-80-9						consumption test)
Cyclosiloxanes, di-Me	LC50	> 3,000 mg/l	Fish	96 h	Leuciscus idus	OECD Guideline
69430-24-6	Leso	> 5,000 mg1	1 1311) o n	Ecuciscus idus	203 (Fish, Acute
07130 21 0						Toxicity Test)
Cyclosiloxanes, di-Me	EC 50	> 10,000 mg/l	Bacteria	3 h		OECD Guideline
69430-24-6						209 (Activated
						Sludge, Respiration
						Inhibition Test)

Bioaccumulative potential / Mobility in soil:

Hazardous components CAS-No.	LogPow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
Silicon dioxide 7631-86-9	0.53					QSAR (Quantitative Structure Activity Relationship)

Section 13. Disposal considerations

Waste disposal of product: Dispose of in accordance with local and national regulations.

Disposal for uncleaned package: After use, tubes, cartons and bottles containing residual product should be disposed of as

chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

Section 14. Transport information

Road and Rail Transport:

Dangerous Goods information: Not classified as Dangerous Goods according to the criteria of the

Australian Code for the Transport of Dangerous Goods by Road and

Rail (ADG Code).

Marine transport IMDG:

Not dangerous goods

Air transport IATA:

Not dangerous goods

Section 15. Regulatory information

SUSMP Poisons Schedule None

AICS: All components are listed or are exempt from listing on the Australian Inventory of

Chemical Substances (AICS).

Section 16. Other information

Abbreviations/acronyms: ADGC - Australian Dangerous Goods Code

GHS: Globally Harmonized System CAS: Chemical Abstracts Service

IMDG: International Maritime Dangerous Goods code

IATA-DGR: International Air Transport Association - Dangerous Goods Regulations

STEL - Short term exposure limit TWA - Time weighted average

Reason for issue: Reviewed SDS. Reissued with new date. involved chapters: 1,2,3,16

Date of previous issue: 22.05.2015

Disclaimer:

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel Australia Pty. Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel Australia Pty. Limited concerning the properties of the material.

The information contained in the Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel Australia Pty. Limited assumes no legal responsibility for reliance upon same. Henkel Australia Pty. Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Safety Data Sheet.

This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by either Commonwealth or State statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.

No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.