

Revision Number: 004.0 Issue date: 09/04/2019

# 1. PRODUCT AND COMPANY IDENTIFICATION

LOCTITE LB 8036 ANTI-SIEZE, WHITE IDH number: Product name: 302678

known as White Hi-Temp Anti-Seize

Product type/use: Lubricant Item number: 34518 Restriction of Use: None identified Region: Canada **Contact information:** 

Company address:

Henkel Canada Corporation Meadowpine Boulevard 2515 Mississauga, Ontario L5N 6C3 Telephone: +1 (905) 814-6511

MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711

TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

# 2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW				
DANGER:	CAUSES SKIN IRRITATION.			
	CAUSES SERIOUS EYE DAMAGE.			

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
SERIOUS EYE DAMAGE	1

# PICTOGRAM(S)



#### **Precautionary Statements**

Prevention: Wash affected area thoroughly after handling. Wear protective gloves, eye protection, and face

protection.

IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several Response:

minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation

occurs: Get medical attention. Take off contaminated clothing.

Storage: Not prescribed Disposal: Not prescribed

8 % of the mixture consists of ingredient(s) of unknown acute toxicity.

Classification complies with Canadian Hazardous Products Regulations (WHMIS 2015) and is consistent with the provision of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Weight %*

IDH number: 302678 Product name: LOCTITE LB 8036 ANTI-SIEZE, WHITE known as White Hi-Temp Anti-Seize

White mineral oil (petroleum), highly refined	8042-47-5	30 - 60
White mineral oil~		10 - 30
Calcium oxide	1305-78-8	5 - 10
Aluminum, tri-m-oxotris(2-propanolato)tri-, cyclo, reaction products with benzoic acid and stearic acid	68411-54-1	5 - 10
Calcium fluoride	7789-75-5	5 - 10
Mica	12001-26-2	5 - 10
Titanium dioxide	13463-67-7	1 - 5
Quartz (SiO2)	14808-60-7	0.1 - 1

<sup>\*</sup> Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

### 4. FIRST AID MEASURES

Inhalation: Move to fresh air. If symptoms persist, seek medical advice.

Skin contact: Remove contaminated clothing and footwear. Immediately flush skin with

plenty of water (using soap, if available). If symptoms develop and persist, get

medical attention. Wash clothing before reuse.

Eye contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. Get medical attention.

**Ingestion:** Get medical attention. Do not induce vomiting. Aspiration may cause

pulmonary edema and pneumonitis.

Symptoms: See Section 11.

# 5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

**Special firefighting procedures:** Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear. In case of fire, keep containers cool with water spray.

Unusual fire or explosion hazards: None

IDH number: 302678

Hydrogen sulfide. Oxides of carbon. Oxides of nitrogen. Oxides of

phosphorus. Oxides of zinc.

# 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:**Do not allow product to enter sewer or waterways.

Clean-up methods: Scrape up as much material as possible. Clean residue with soap and water.

Store in a closed container until ready for disposal. Refer to Section 8

"Exposure Controls / Personal Protection" prior to clean up.

# 7. HANDLING AND STORAGE

**Handling:** Use only with adequate ventilation. Prevent contact with eyes, skin and

clothing. Do not breathe vapor and mist. Wash thoroughly after handling.

Keep container closed.

Storage: Keep in a cool, well ventilated area.

Shelf Life Statement: Not available.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
White mineral oil (petroleum), highly refined	5 mg/m3 TWA Inhalable fraction.	5 mg/m3 TWA mist 5 mg/m3 PEL Mist.	None	None
White mineral oil~	5 mg/m3 TWA mist 10 mg/m3 STEL mist	5 mg/m3 TWA mist	None	None
Calcium oxide	2 mg/m3 TWA	5 mg/m3 PEL	None	None
Aluminum, tri-m-oxotris(2-propanolato)tri-, cyclo, reaction products with benzoic acid and stearic acid	1 mg/m3 TWA Respirable fraction.	None	None	None
Calcium fluoride	2.5 mg/m3 TWA (as F)	2.5 mg/m3 PEL (as F) 2.5 mg/m3 TWA Dust.	None	None
Mica	3 mg/m3 TWA Respirable fraction.	20 MPPCF TWA	None	None
Titanium dioxide	10 mg/m3 TWA	15 mg/m3 PEL Total dust. 15 MPPCF TWA Respirable fraction. 15 mg/m3 TWA Total dust. 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction.	None	None
Quartz (SiO2)	0.025 mg/m3 TWA Respirable fraction.	0.05 mg/m3 TWA (Respirable dust.) (Respirable dust.) 0.025 mg/m3 OSHA_ACT (Respirable dust.) 0.05 mg/m3 PEL Respirable dust. 2.4 MPPCF TWA Respirable. 0.1 mg/m3 TWA Respirable.	None	None

Engineering controls: General room ventilation is usually adequate. Local exhaust ventilation is

recommended when general ventilation is not sufficient to control airborne

contamination below occupational exposure limits.

Respiratory protection: Observe OSHA regulations for respirator use (29 CFR 1910.134). Use NIOSH

approved respirator if there is potential to exceed exposure limit(s).

**Eye/face protection:** Safety goggles or safety glasses with side shields. Safety showers and eye

wash stations should be available.

**Skin protection:**Use chemical resistant, impermeable clothing including gloves and either an

apron or body suit to prevent skin contact.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Solid, Paste Physical state: Color: Off white Odor: Mild Odor threshold: Not available. pH: Not applicable Vapor pressure: Not available. Boiling point/range: Not available. Melting point/ range: Not available. Specific gravity: Vapor density: 1.116 Not available. Flash point: Not applicable Flammable/Explosive limits - lower: Not determined Flammable/Explosive limits - upper: Not determined Autoignition temperature: Not determined Flammability: Not applicable **Evaporation rate:** Not determined Solubility in water: Insoluble

Partition coefficient (n-octanol/water):

VOC content:

Viscosity:

Not determined
0.4 %; 4.7 g/l
Not available.

Not available.

Not available.

# 10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions of storage and use.

Hazardous reactions: Will not occur.

**Hazardous decomposition** Oxides of carbon. Hydrocarbons. Oxides of nitrogen. Oxides of phosphorus. Oxides of zinc.

**products:** Hydrogen sulfide.

Incompatible materials: Oxidizing agents.

Reactivity: Not available.

IDH number: 302678

Conditions to avoid: Prolonged exposure to heat.

### 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

#### Potential Health Effects/Symptoms

Inhalation: This product has low volatility and is not expected to cause respiratory tract irritation during

normal conditions of use. Abrasion of cured material such as by sanding or grinding could release respirable particles of silica quartz, a cancer hazard by inhalation. Normal use of this

product causes no such release.

**Skin contact:** Causes skin irritation.

**Eye contact:** Causes serious eye damage.

Ingestion: Not expected under normal conditions of use. May cause gastrointestinal tract irritation if

swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
White mineral oil (petroleum), highly refined	None	Irritant
White mineral oil~	None	Irritant
Calcium oxide	None	Irritant, Corrosive, Eyes
Aluminum, tri-m-oxotris(2-propanolato)tri-, cyclo, reaction products with benzoic acid and stearic acid	None	No Records
Calcium fluoride	Oral LD50 (Rat) = 4,250 mg/kg	Teeth, Muscle, Respiratory
Mica	None	Lung
Titanium dioxide	None	Irritant, Respiratory, Some evidence of carcinogenicity
Quartz (SiO2)	None	Immune system, Lung, Some evidence of carcinogenicity

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
White mineral oil (petroleum), highly refined	No	No	No
White mineral oil~	No	No	No
Calcium oxide	No	No	No
Aluminum, tri-m-oxotris(2-propanolato)tri-, cyclo, reaction products with benzoic acid and stearic acid	No	No	No
Calcium fluoride	No	No	No
Mica	No	No	No
Titanium dioxide	No	Group 2B	No
Quartz (SiO2)	Known To Be Human Carcinogen.	Group 1	Yes

# 12. ECOLOGICAL INFORMATION

Ecological information: Not available.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Follow all local, state, federal and provincial regulations for disposal.

### 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

Canada Transportation of Dangerous Goods - Ground

IDH number: 302678

Proper shipping name: Not regulated

Hazard class or division:
Identification number:
Packing group:
None

#### International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated

Hazard class or division: None Identification number: None Packing group: None

#### Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated

Hazard class or division:
Identification number:
Packing group:
None

### 15. REGULATORY INFORMATION

#### **Canada Regulatory Information**

CEPA DSL/NDSL Status: Contains one or more components listed on the Non-Domestic Substances List. All other

components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities.

Please contact Regulatory Affairs for additional details.

#### **United States Regulatory Information**

IDH number: 302678

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

#### 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 2

Prepared by: Product Safety and Regulatory Affairs

**Issue date:** 09/04/2019

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on the Canadian Hazardous Products Regulations (WHMIS 2015) and provides information in accordance with Canadian law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.