ITW POLYMERS & FLUIDS

Chemwatch: 27-9806

Version No: 15.1

Safety Data Sheet according to Work Health and Safety Regulations (Hazardous Chemicals) 2023 and ADG requirements

Issue Date: 08/11/2023 Print Date: 26/09/2024 S.GHS.AUS.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

Product name	Rocol Easyline EDGE 750mL Aerosol, All Colours - From 23.06.20	
Chemical Name	lot Applicable	
Synonyms	Not Available	
Proper shipping name	AEROSOLS	
Chemical formula	Not Applicable	
Other means of identification	UFI:7800-D0RN-W00U-DDRD	

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Professional use, industrial use; industrial; reserved for professional use.
--------------------------	--

Details of the manufacturer or supplier of the safety data sheet

Registered company name	ITW POLYMERS & FLUIDS	ITW Polymers & Fluids (NZ)
Address	100 Hassall Street, Wetherill Park NSW 2164 Australia	Unit 2/38 Trugood Drive, East Tamaki, Auckland 2013 New Zealand
Telephone	+61 2 9757 8800	0800 476 265
Fax	+61 2 9757 3855	+64 9 273 6489
Website	www.itwpf.com.au	www.itwpf.co.nz
Email	Not Available	Not Available

Emergency telephone number

Association / Organisation	CHEMWATCH EMERGENCY RESPONSE (24/7)	ITW Polymers & Fluids (NZ)	CHEMWATCH EMERGENCY RESPONSE (24/7)
Emergency telephone numbers	+61 1800 951 288	0800 2436 2255	+61 1800 951 288
Other emergency telephone numbers	+61 3 9573 3188	Not Available	+61 3 9573 3188

Once connected and if the message is not in your preferred language then please dial 01

SECTION 2 Hazards identification

Classification of the substance or mixture

HAZARDOUS CHEMICAL. DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

Poisons Schedule	Not Applicable		
Classification ^[1]	Aerosols Category 1, Skin Corrosion/Irritation Category 2, Serious Eye Damage/Eye Irritation Category 2A, Specific Target Organ Toxicity - Single Exposure (Narcotic Effects) Category 3		
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI		

Label elements

Hazard pictogram(s)



Signal word Danger

Hazard statement(s)

H222+H229	Extremely flammable aerosol. Pressurized container: may burst if heated.	
H315	Causes skin irritation.	
H319	Causes serious eye irritation.	
H336	May cause drowsiness or dizziness.	
AUH044	Risk of explosion if heated under confinement.	

Precautionary statement(s) General

P101	If medical advice is needed, have product container or label at hand.	
P102	Keep out of reach of children.	
P103	Read carefully and follow all instructions.	

Precautionary statement(s) Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
P211	Do not spray on an open flame or other ignition source.	
P251	Do not pierce or burn, even after use.	
P271	Use only outdoors or in a well-ventilated area.	

Precautionary statement(s) Response

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P312	Call a POISON CENTER/doctor/physician/first aider/if you feel unwell.	
P337+P313	If eye irritation persists: Get medical advice/attention.	
P302+P352	IF ON SKIN: Wash with plenty of water.	

Precautionary statement(s) Storage

P405	Store locked up.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.

Precautionary statement(s) Disposal

P501

Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
95-47-6	5-15	<u>o-xylene</u>
67-64-1	5-10	acetone
107-98-2	2.4-10	propylene glycol monomethyl ether - alpha isomer
124-38-9	1-2.4	carbon dioxide
115-10-6	10-30	dimethyl ether
Legend: 1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L * EU IOELVs available		

SECTION 4 First aid measures

Description of first aid measures

Eye Contact

If aerosols come in contact with the eyes:

• Immediately hold the eyelids apart and flush the eye continuously for at least 15 minutes with fresh running water.

Issue Date: 08/11/2023 Print Date: 26/09/2024

	 Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	 If solids or aerosol mists are deposited upon the skin: Flush skin and hair with running water (and soap if available). Remove any adhering solids with industrial skin cleansing cream. DO NOT use solvents. Seek medical attention in the event of irritation.
Inhalation	 If aerosols, fumes or combustion products are inhaled: Remove to fresh air. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. If breathing is shallow or has stopped, ensure clear airway and apply resuscitation, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor.
Ingestion	Not considered a normal route of entry.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Firefighting measures

Extinguishing media

SMALL FIRE:

Water spray, dry chemical or CO2

LARGE FIRE:

Water spray or fog.

Special hazards arising from the substrate or mixture

Fire Incompatibility Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition m result	ıay
---	-----

Advice for firefighters

Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. May be violently or explosively reactive. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water course.
Fire/Explosion Hazard	 Liquid and vapour are highly flammable. Severe fire hazard when exposed to heat or flame. Vapour forms an explosive mixture with air. Severe explosion hazard, in the form of vapour, when exposed to flame or spark. Combustion products include: carbon monoxide (CO) carbon dioxide (CO2) other pyrolysis products typical of burning organic material. Contains low boiling substance: Closed containers may rupture due to pressure buildup under fire conditions.
HAZCHEM	Not Applicable

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Wear protective clothing, impervious gloves and safety glasses. Shut off all possible sources of ignition and increase ventilation.
Major Spills	 Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. May be violently or explosively reactive.

Wear breathing apparatus plus protective gloves.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Safe handling	 Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps.
Other information	 Store in original containers in approved flammable liquid storage area. DO NOT store in pits, depressions, basements or areas where vapours may be trapped. No smoking, naked lights, heat or ignition sources. Keep containers securely sealed. Keep dry to avoid corrosion of cans. Corrosion may result in container perforation and internal pressure may eject contents of can

Conditions for safe storage, including any incompatibilities

Suitable container	 Aerosol dispenser. Check that containers are clearly labelled.
Storage incompatibility	Avoid reaction with oxidising agents

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	o-xylene	Xylene (o-, m-, p- isomers)	80 ppm / 350 mg/m3	655 mg/m3 / 150 ppm	Not Available	Not Available
Australia Exposure Standards	acetone	Acetone	500 ppm / 1185 mg/m3	2375 mg/m3 / 1000 ppm	Not Available	Not Available
Australia Exposure Standards	propylene glycol monomethyl ether - alpha isomer	Propylene glycol monomethyl ether	100 ppm / 369 mg/m3	553 mg/m3 / 150 ppm	Not Available	Not Available
Australia Exposure Standards	carbon dioxide	Carbon dioxide in coal mines	12500 ppm / 22500 mg/m3	54000 mg/m3 / 30000 ppm	Not Available	Not Available
Australia Exposure Standards	carbon dioxide	Carbon dioxide	5000 ppm / 9000 mg/m3	54000 mg/m3 / 30000 ppm	Not Available	Not Available
Australia Exposure Standards	dimethyl ether	Dimethyl ether	400 ppm / 760 mg/m3	950 mg/m3 / 500 ppm	Not Available	Not Available

Emergency Limits

Ingredient	TEEL-1	TEEL-2		TEEL-3
o-xylene	130 ppm	920 ppm		2500* ppm
acetone	Not Available	Not Available		Not Available
propylene glycol monomethyl ether - alpha isomer	100 ppm	160 ppm		660 ppm
dimethyl ether	3,000 ppm	3800* ppm		7200* ppm
Ingredient	Original IDLH		Revised IDLH	
o-xylene	900 ppm		Not Available	
acetone	2,500 ppm		Not Available	
propylene glycol monomethyl ether - alpha isomer	Not Available		Not Available	
carbon dioxide	40,000 ppm		Not Available	
dimethyl ether	Not Available		Not Available	

Exposure controls

Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to

	provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.
Individual protection measures, such as personal protective equipment	
Eye and face protection	 No special equipment for minor exposure i.e. when handling small quantities. OTHERWISE: For potentially moderate or heavy exposures: Safety glasses with side shields. NOTE: Contact lenses pose a special hazard; soft lenses may absorb irritants and ALL lenses concentrate them.
Skin protection	See Hand protection below
Hands/feet protection	 No special equipment needed when handling small quantities. OTHERWISE: For potentially moderate exposures: Wear general protective gloves, eg. light weight rubber gloves. For potentially heavy exposures: Wear chemical protective gloves, eg. PVC. and safety footwear.
Body protection	See Other protection below
Other protection	No special equipment needed when handling small quantities. OTHERWISE: • Overalls. • Skin cleansing cream. • Eyewash unit.

Respiratory protection

Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Aerosols, in common with most vapours/ mists, should never be used in confined spaces without adequate ventilation. Aerosols, containing agents designed to enhance or mask smell, have triggered allergic reactions in predisposed individuals.

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Coloured highly flammable liquid with characteristic odour	r.	
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Characteristic	Partition coefficient n- octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	<0	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	<0	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	HIGHLY FLAMMABLE.	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Not Available	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available
Heat of Combustion (kJ/g)	Not Available	Ignition Distance (cm)	Not Available
Flame Height (cm)	Not Available	Flame Duration (s)	Not Available

Enclosed Space Ignition Time Equivalent (s/m3)	Not Available	Enclosed Space Ignition Deflagration Density (g/m3)	Not Available
---	---------------	---	---------------

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	 Elevated temperatures. Presence of open flame. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

Inhaled	There is strong evidence to suggest that this material can cause, if inhaled once, very serious, irreversible damage of organs. The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss or reflexes, lack of co-ordination, and vertigo. Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco-ordination. WARNING:Intentional misuse by concentrating/inhaling contents may be lethal.		
Ingestion	There is strong evidence to suggest that this material can cause, if swallowed once, very serious, irreversible damage of organs. Accidental ingestion of the material may be damaging to the health of the individual. Considered an unlikely route of entry in commercial/industrial environments		
Skin Contact	This material can cause inflammation of the skin on contact in some persons. There is strong evidence to suggest that this material, on a single contact with skin, can cause very serious, irreversible damage of organs. Repeated exposure may cause skin cracking, flaking or drying following normal handling and use. Skin contact with the material may damage the health of the individual; systemic effects may result following absorption. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.		
Eye	This material can cause eye irritation and damage in some persons. The liquid produces a high level of eye discomfort and is capable of causing pain and severe conjunctivitis. Corneal injury may develop, with possible permanent impairment of vision, if not promptly and adequately treated.		
Chronic	Long-term exposure to respiratory irritants may result in airways problems. Toxic: danger of serious damage to health by prolonged exposu This material can cause serious damage if one is exposed to it f which can produce severe defects. Ample evidence from experiments exists that there is a suspicio Based on experience with animal studies, exposure to the mater levels which do not cause significant toxic effects to the mother. Substance accumulation, in the human body, may occur and ma occupational exposure. Chronic solvent inhalation exposures may result in nervous syst WARNING : Aerosol containers may present pressure related ha	re through inhalation, in contact with skin and if swallowed. or long periods. It can be assumed that it contains a substance n this material directly reduces fertility. rial may result in toxic effects to the development of the foetus, at ay cause some concern following repeated or long-term em impairment and liver and blood changes. [PATTYS]	
Rocol Easyline EDGE	ΤΟΧΙΟΙΤΥ	IRRITATION	
750mL Aerosol, All Colours - From 23.06.20	Not Available	Not Available	
	ΤΟΧΙΟΙΤΥ	IRRITATION	
o-xylene	Dermal (rabbit) LD50: >4350 mg/kg ^[1]	Eye: adverse effect observed (irritating) ^[1]	
	Inhalation (Rat) LC50: 5922 ppm4h ^[1]	Skin: adverse effect observed (irritating) ^[1]	

IRRITATION

Eye (human): 500 ppm - irritant

Oral (Rat) LD50: 3523 mg/kg^[1]

Dermal (rabbit) LD50: 20000 mg/kg^[2]

TOXICITY

acetone

	· · · · -		
Oral (Rat) LD50: 5800 mg/kg ^[2]	Eye (rabbit): 3.95 mg - SEVERE		
	Eye: adverse effect observed (irritating) ^[1]		
	Skin (rabbit): 500 mg/24hr - mild		
	Skin (rabbit):395mg (open) - mild		
	Skin: no adverse effect observed (not irritating) ^[1]		
ΤΟΧΙΟΙΤΥ	IRRITATION		
dermal (rat) LD50: >2000 mg/kg ^[1]	Eye (rabbit) 230 mg mild		
Inhalation (Rat) LC50: >6 mg/l4h ^[2]	Eye (rabbit) 500 mg/24 h mild		
Oral (Rat) LD50: 3739 mg/kg ^[2]	Eye (rabbit): 100 mg SEVERE		
	Eye: no adverse effect observed (not irritating) ^[1]		
	Skin (rabbit) 500 mg open - mild		
	Skin: no adverse effect observed (not irritating) ^[1]		
ΤΟΧΙΟΙΤΥ	IRRITATION		
Not Available	Not Available		
ΤΟΧΙΟΙΤΥ	IRRITATION		
Inhalation (Rat) LC50: >20000 ppm4h ^[1]	Skin: no adverse effect observed (not irritating) ^[1]		
1. Value obtained from Europe ECHA Registered Sub	stances - Acute toxicity 2. Value obtained from manufacturer's SDS.		
	TOXICITY dermal (rat) LD50: >2000 mg/kg ^[1] Inhalation (Rat) LC50: >6 mg/l4h ^[2] Oral (Rat) LD50: 3739 mg/kg ^[2] TOXICITY Not Available TOXICITY Inhalation (Rat) LC50: >20000 ppm4h ^[1]		

O-XYLENE	Paternal effects recorded.					
ACETONE	The material may cause skin irritation after prolonged or repeated exposure and r the production of vesicles, scaling and thickening of the skin. For acetone: The acute toxicity of acetone is low. Acetone is not a skin irritant or sensitizer, but the eye. Animal testing shows acetone may cause anaemia. Studies in humans h of 2375 mg/m3 does not negatively impact an individual's emotional regulation, but	it removes fat from the skin, and it also irritates ave shown that exposure to acetone at a level				
PROPYLENE GLYCOL MONOMETHYL ETHER - ALPHA ISOMER	NOTE: For PGE - mixed isomers: Exposure of pregnant rats and rabbits to the su at concentrations up to 3000 ppm. Foetotoxic effects were seen in rats but not in was noted in both species. For propylene glycol ethers (PGEs): Typical propylene glycol ethers include propylene glycol n-butyl ether (PnB); dipro glycol methyl ether acetate (DPMA) and tripropylene glycol methyl ether (TPM). Testing of a wide variety of propylene glycol ethers has shown that propylene glyce ethers of the ethylene series. The common toxicities associated with the lower more series, such as adverse effects on the reproductive organs, the developing embry seen with the commercial-grade propylene glycol ethers. In the ethylene series, n produces and alkoxyacetic acid. The reproductive and developmental toxicities of ethylene series are due specifically to the formation of methoxyacetic and ethoxya Longer chain homologues in the ethylene series are not associated with reproduct	rabbits at this concentration; maternal toxicity opylene glycol n-butyl ether (DPnB); dipropylene col-based ethers are less toxic than some olecular weight homologues of the ethylene vo and foetus, blood or thymus gland, are not netabolism of the terminal hydroxyl group i the lower molecular weight homologues in the acetic acids.				
Acute Toxicity	× Carcinogenicity	×				
Acute Toxicity Skin Irritation/Corrosion	 X Carcinogenicity ✓ Reproductivity 	×				
Skin Irritation/Corrosion Serious Eye	Reproductivity	×				

— Data available to make classification

SECTION 12 Ecological information

Toxicity

Rocol Easyline EDGE 750mL Aerosol, All

Value

Colours - From 23.06.20	Not Available	Not Available	Not Available	vailable Not Available	
	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	72h	Algae or other aquatic plants	4.7mg/L	4
o-xylene	EC50	48h	Crustacea	0.78- 2.51mg/l	4
	LC50	96h	Fish	2.6mg/l	2
	NOEC(ECx)	73h	Algae or other aquatic plants	0.44mg/l	2
	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	72h	Algae or other aquatic plants	5600- 10000mg/L	4
	EC50	48h	Crustacea	6098.4mg/L	5
acetone	NOEC(ECx)	12h	Fish	0.001mg/L	4
	LC50	96h	Fish	3744.6- 5000.7mg/L	4
	EC50	96h	Algae or other aquatic plants	9.873- 27.684mg/l	4
	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	72h	Algae or other aquatic plants	>500mg/l	2
propylene glycol	EC50(ECx)	168h	Algae or other aquatic plants	quatic plants >1000mg/l	
monomethyl ether - alpha	EC50	48h	Crustacea	23300mg/l	1
isomer	LC50	96h	Fish	>2000mg/l	Not Available
	EC50	96h	Algae or other aquatic plants	>1000mg/l	2
	Endpoint	Test Duration (hr)	Species	Value	Source
carbon dioxide	LC50	96h	Fish	35mg/l	1
	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	48h	Crustacea	>4400mg/L	2
dimethyl ether	NOEC(ECx)	48h	Crustacea	>4000mg/l	1
	LC50	96h	Fish	1783.04mg/l	2
	EC50	96h	Algae or other aquatic plants	154.917mg/l	2
Legend:		1. IUCLID Toxicity Data 2. Europe otox database - Aquatic Toxicity D	e ECHA Registered Substances - Ecotoxicologic		

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. **DO NOT** discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
o-xylene	HIGH (Half-life = 360 days)	LOW (Half-life = 1.83 days)
acetone	LOW (Half-life = 14 days)	MEDIUM (Half-life = 116.25 days)
propylene glycol monomethyl ether - alpha isomer	LOW (Half-life = 56 days)	LOW (Half-life = 1.7 days)
carbon dioxide	LOW	LOW
dimethyl ether	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
o-xylene	LOW (BCF = 219)
acetone	LOW (BCF = 0.69)
propylene glycol monomethyl ether - alpha isomer	LOW (BCF = 2)
carbon dioxide	LOW (LogKOW = 0.83)
dimethyl ether	LOW (LogKOW = 0.1)

Mobility in soil

Ingredient	Mobility
o-xylene	LOW (Log KOC = 443.1)
acetone	HIGH (Log KOC = 1.981)
propylene glycol monomethyl ether - alpha isomer	HIGH (Log KOC = 1)
carbon dioxide	HIGH (Log KOC = 1.498)
dimethyl ether	HIGH (Log KOC = 1.292)

SECTION 13 Disposal considerations

Waste treatment methods

	 DO NOT allow wash water from cleaning or process equipment to enter drains. 				
	It may be necessary to collect all wash water for treatment before disposal.				
	In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.				
Product / Packaging	Where in doubt contact the responsible authority.				
disposal	Consult State Land Waste Management Authority for disposal.				
	Discharge contents of damaged aerosol cans at an approved site.				
	 Allow small quantities to evaporate. 				
	DO NOT incinerate or puncture aerosol cans.				

SECTION 14 Transport information

Labels Required

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (ADG)

14.1. UN number or ID number	1950			
14.2. UN proper shipping name	AEROSOLS	EROSOLS		
14.3. Transport hazard class(es)	Class Subsidiary Hazard	2.1 Not Applicable		
14.4. Packing group	Not Applicable			
14.5. Environmental hazard	Not Applicable			
14.6. Special precautions for user	Special provisions Limited quantity	63 190 277 327 344 381 1000ml		

Air transport (ICAO-IATA / DGR)

14.1. UN number	1950						
14.2. UN proper shipping name	Aerosols, flammable						
14.3. Transport hazard class(es)	ICAO/IATA Class ICAO / IATA Subsidiary Hazard ERG Code	2.1 Not Applicable 10L					
14.4. Packing group	Not Applicable						
14.5. Environmental hazard	Not Applicable						

14.6. Special precautions for user	Special provisions	A145 A167 A802
	Cargo Only Packing Instructions	203
	Cargo Only Maximum Qty / Pack	150 kg
	Passenger and Cargo Packing Instructions	203
	Passenger and Cargo Maximum Qty / Pack	75 kg
	Passenger and Cargo Limited Quantity Packing Instructions	Y203
	Passenger and Cargo Limited Maximum Qty / Pack	30 kg G

Sea transport (IMDG-Code / GGVSee)

14.1. UN number	1950			
14.2. UN proper shipping name	AEROSOLS			
14.3. Transport hazard class(es)	IMDG Class IMDG Subsidiary Ha	IMDG Class2.1IMDG Subsidiary HazardNot Applicable		
14.4. Packing group	Not Applicable	Not Applicable		
14.5 Environmental hazard	Not Applicable			
14.6. Special precautions for user	EMS NumberF-D , S-USpecial provisions63 190 277 327 344 381 959Limited Quantities1000 ml			

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
o-xylene	Not Available
acetone	Not Available
propylene glycol monomethyl ether - alpha isomer	Not Available
carbon dioxide	Not Available
dimethyl ether	Not Available

14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
o-xylene	Not Available
acetone	Not Available
propylene glycol monomethyl ether - alpha isomer	Not Available
carbon dioxide	Not Available
dimethyl ether	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

o-xylene is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5 Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6 Australian Inventory of Industrial Chemicals (AIIC)

acetone is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5

Australian Inventory of Industrial Chemicals (AIIC)

propylene glycol monomethyl ether - alpha isomer is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals Australian Inventory of Industrial Chemicals (AIIC)

carbon dioxide is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

FEI Equine Prohibited Substances List - Controlled Medication

FEI Equine Prohibited Substances List (EPSL)

dimethyl ether is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5

Australian Inventory of Industrial Chemicals (AIIC)

Additional Regulatory Information

Not Applicable

National Inventory Status

National Inventory	Status Yes		
Australia - AIIC / Australia Non-Industrial Use			
Canada - DSL	Yes		
Canada - NDSL	No (o-xylene; acetone; propylene glycol monomethyl ether - alpha isomer; carbon dioxide; dimethyl ether)		
China - IECSC	Yes		
Europe - EINEC / ELINCS / NLP	Yes		
Japan - ENCS	Yes		
Korea - KECI	Yes		
New Zealand - NZIoC	Yes		
Philippines - PICCS	Yes		
USA - TSCA	Yes		
Taiwan - TCSI	Yes		
Mexico - INSQ	Yes		
Vietnam - NCI	Yes		
Russia - FBEPH	Yes		
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.		

SECTION 16 Other information

Revision Date	08/11/2023
Initial Date	01/11/2009

SDS Version Summary

Version	Date of Update	Sections Updated
14.1	24/07/2023	Toxicological information - Acute Health (eye), Toxicological information - Acute Health (inhaled), Hazards identification - Classification, Composition / information on ingredients - Ingredients, Identification of the substance / mixture and of the company / undertaking - Synonyms
15.1	08/11/2023	Physical and chemical properties - Appearance, Toxicological information - Chronic Health, Hazards identification - Classification, Composition / information on ingredients - Ingredients, Identification of the substance / mixture and of the company / undertaking - Supplier Information, Identification of the substance / mixture and of the company / undertaking - Synonyms, Identification of the substance / mixture and of the company / undertaking - Synonyms, Identification of the substance / mixture and of the company / undertaking - Synonyms, Identification of the substance / mixture and of the company / undertaking - Synonyms, Identification of the substance / mixture and of the company / undertaking - Use, Name

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.