# **Epirez Multi-Purpose Epoxy Concrete Repair (Multi II) Base ITW POLYMERS & FLUIDS**

Chemwatch: 5137-55 Version No: 9.1

Safety Data Sheet according to Work Health and Safety Regulations (Hazardous Chemicals) 2023 and ADG requirements

Issue Date: **10/03/2023**Print Date: **01/10/2024**S.GHS.AUS.EN

## SECTION 1 Identification of the substance / mixture and of the company / undertaking

#### **Product Identifier**

Product name	Epirez Multi-Purpose Epoxy Concrete Repair (Multi II) Base	
Chemical Name	Not Applicable	
Synonyms	Not Available	
Proper shipping name	pping name  ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains bisphenol A/ diglycidyl ether polymer, high molecular weight)	
Chemical formula	Not Applicable	
Other means of identification	Not Available	

#### Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Base component of a two-part epoxy concrete repair system.  Use according to manufacturer's directions.  Requires that the two parts be mixed by hand or mixer before use, in accordance with manufacturers directions. Mix only as much as is required. <b>Do not</b> return the mixed material to the original containers  The use of a quantity of material in an unventilated or confined space may result in increased exposure and an irritating atmosphere developing.
--------------------------	---

## Details of the manufacturer or supplier of the safety data sheet

Registered company name	ITW POLYMERS & FLUIDS	ITW Polymers & Fluids (NZ)
Address 100 Hassall Street, Wetherill Park NSW 2164 Australia		Unit 2/38 Trugood Drive, East Tamaki, Auckland 2013 New Zealand
Telephone	+61 2 9757 8800	0800 476 265
Fax	+61 2 9757 3855	+64 9 273 6489
Website www.itwpf.com.au		www.itwpf.co.nz
Email Not Available		Not Available

#### **Emergency telephone number**

Association / Organisation	CHEMWATCH EMERGENCY RESPONSE (24/7)	ITW Polymers & Fluids (NZ)	CHEMWATCH EMERGENCY RESPONSE (24/7)
Emergency telephone numbers	+61 1800 951 288	0800 2436 2255	+61 1800 951 288
Other emergency telephone numbers	+61 3 9573 3188	Not Available	+61 3 9573 3188

Once connected and if the message is not in your preferred language then please dial 01

## **SECTION 2 Hazards identification**

## Classification of the substance or mixture

HAZARDOUS CHEMICAL. DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

Poisons Schedule	S5
Classification <sup>[1]</sup>	Skin Corrosion/Irritation Category 2, Sensitisation (Skin) Category 1, Serious Eye Damage/Eye Irritation Category 2A, Hazardous to the Aquatic Environment Long-Term Hazard Category 2
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

Chemwatch: 5137-55 Version No: 9.1

#### Epirez Multi-Purpose Epoxy Concrete Repair (Multi II) Base

Issue Date: 10/03/2023 Print Date: 01/10/2024

#### Label elements

## Hazard pictogram(s)





Signal word

Warning

#### Hazard statement(s)

H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H319	Causes serious eye irritation.	
H411	Toxic to aquatic life with long lasting effects.	

#### Precautionary statement(s) General

P101	If medical advice is needed, have product container or label at hand.	
P102	Keep out of reach of children.	
P103	Read carefully and follow all instructions.	

## Precautionary statement(s) Prevention

P280	Wear protective gloves, protective clothing, eye protection and face protection.	
P261	Avoid breathing mist/vapours/spray.	
P273	Avoid release to the environment.	
P264	Wash all exposed external body areas thoroughly after handling.	

## Precautionary statement(s) Response

P302+P352	IF ON SKIN: Wash with plenty of water and soap.	
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.	
P337+P313	If eye irritation persists: Get medical advice/attention.	

## Precautionary statement(s) Storage

Not Applicable

## Precautionary statement(s) Disposal

P501	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.
------	--

## **SECTION 3 Composition / information on ingredients**

## **Substances**

See section below for composition of Mixtures

## **Mixtures**

CAS No	%[weight]	Name
25068-38-6	10-30	bisphenol A/ diglycidyl ether polymer, high molecular weight
68609-97-2	<10	(C12-14)alkylglycidyl ether
Not Available	balance	other ingredients not contributing to the classification
Legend:  1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L * EU IOELVs available		

#### **SECTION 4 First aid measures**

## Description of first aid measures

Eye	Contac
-----	--------

If this product comes in contact with the eyes:

▶ Wash out immediately with fresh running water.

Chemwatch: 5137-55 Issue Date: 10/03/2023 Page 3 of 10 Version No: 9.1 Print Date: 01/10/2024

## Epirez Multi-Purpose Epoxy Concrete Repair (Multi II) Base

	<ul> <li>Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>Seek medical attention without delay; if pain persists or recurs seek medical attention.</li> <li>Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>			
Skin Contact	If skin contact occurs:  Immediately remove all contaminated clothing, including footwear.  Flush skin and hair with running water (and soap if available).  Seek medical attention in event of irritation.			
Inhalation	<ul> <li>If fumes or combustion products are inhaled remove from contaminated area.</li> <li>Lay patient down. Keep warm and rested.</li> <li>Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> <li>Transport to hospital, or doctor.</li> </ul>			
Ingestion	<ul> <li>For advice, contact a Poisons Information Centre or a doctor at once.</li> <li>Urgent hospital treatment is likely to be needed.</li> <li>If swallowed do NOT induce vomiting.</li> <li>If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>Observe the patient carefully.</li> <li>Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.</li> <li>Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li> <li>Transport to hospital or doctor without delay.</li> </ul>			

## Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## **SECTION 5 Firefighting measures**

## **Extinguishing media**

- ▶ Foam.
- Dry chemical powder.
- ▶ BCF (where regulations permit).

Fire Incompatibility

Carbon dioxide.

## Special hazards arising from the substrate or mixture

dvice for firefighters	
Fire Fighting	<ul> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>Wear breathing apparatus plus protective gloves.</li> <li>Prevent, by any means available, spillage from entering drains or water course.</li> <li>Use water delivered as a fine spray to control fire and cool adjacent area.</li> </ul>
Fire/Explosion Hazard	<ul> <li>Combustible.</li> <li>Slight fire hazard when exposed to heat or flame.</li> <li>Heating may cause expansion or decomposition leading to violent rupture of containers.</li> <li>On combustion, may emit toxic fumes of carbon monoxide (CO).</li> <li>Combustion products include:         <ul> <li>carbon dioxide (CO2)</li> </ul> </li> <li>aldehydes</li> <li>other pyrolysis products typical of burning organic material.</li> <li>May emit poisonous fumes.</li> <li>May emit corrosive fumes.</li> </ul>
HAZCHEM	•3Z

Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may

#### **SECTION 6 Accidental release measures**

## Personal precautions, protective equipment and emergency procedures

See section 8

## **Environmental precautions**

See section 12

## Methods and material for containment and cleaning up

**Minor Spills** 

▶ Clean up all spills immediately.

Chemwatch: 5137-55 Page 4 of 10

Issue Date: 10/03/2023 Version No: 9.1 Print Date: 01/10/2024 Epirez Multi-Purpose Epoxy Concrete Repair (Multi II) Base

Avoid breathing vapours/ aerosols/ or dusts and avoid contact with skin and eyes. ▶ Control personal contact with the substance, by using protective equipment. ▶ Contain and absorb spill with sand, earth, inert material or vermiculite.

- ▶ Clear area of personnel and move upwind.
- ▶ Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- ▶ Prevent, by any means available, spillage from entering drains or water course.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

## **SECTION 7 Handling and storage**

**Major Spills** 

## Precautions for safe handling

Safe handling	<ul> <li>Avoid all personal contact, including inhalation.</li> <li>Wear protective clothing when risk of exposure occurs.</li> <li>Use in a well-ventilated area.</li> <li>Prevent concentration in hollows and sumps.</li> </ul>
Other information	<ul> <li>Store in original containers.</li> <li>Keep containers securely sealed.</li> <li>Store in a cool, dry, well-ventilated area.</li> <li>Store away from incompatible materials and foodstuff containers.</li> </ul>

## Conditions for safe storage, including any incompatibilities

Suitable container	<ul> <li>Polyethylene or polypropylene container.</li> <li>Packing as recommended by manufacturer.</li> <li>Check all containers are clearly labelled and free from leaks.</li> </ul>
Storage incompatibility	Avoid reaction with oxidising agents

### **SECTION 8 Exposure controls / personal protection**

#### **Control parameters**

Occupational Exposure Limits (OEL)

## INGREDIENT DATA

Not Available

Ingredient	Original IDLH	Revised IDLH
bisphenol A/ diglycidyl ether polymer, high molecular weight	Not Available	Not Available
(C12-14)alkylglycidyl ether	Not Available	Not Available

## Occupational Exposure Banding

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
bisphenol A/ diglycidyl ether polymer, high molecular weight	E	≤ 0.01 mg/m³
(C12-14)alkylglycidyl ether	E ≤ 0.1 ppm	
Notes:	Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.	

#### **Exposure controls**

#### General exhaust is adequate under normal operating conditions. Appropriate engineering Refer also to protective measures for the other component used with the product. Read both SDS before using; store and attach controls SDS together. Individual protection measures, such as personal protective equipment Safety glasses with side shields. ► Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent] Eye and face protection Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.

Page **5** of **10** Issue Date: 10/03/2023

Print Date: 01/10/2024

Chemwatch: 5137-55 Version No: 9.1

#### Epirez Multi-Purpose Epoxy Concrete Repair (Multi II) Base

Skin protection	See Hand protection below			
Hands/feet protection	When handling liquid-grade epoxy resins wear chemically protective gloves , boots and aprons.  The performance, based on breakthrough times ,of:  Ethyl Vinyl Alcohol (EVAL laminate) is generally excellent  Butyl Rubber ranges from excellent to good  Nitrile Butyl Rubber (NBR) from excellent to fair.  Neoprene from excellent to fair  Polyvinyl (PVC) from excellent to poor  As defined in ASTM F-739-96  Excellent breakthrough time > 480 min  Good breakthrough time > 20 min  Fair breakthrough time < 20 min  Poor glove material degradation  Gloves should be tested against each resin system prior to making a selection of the most suitable type. Systems include both the resin and any hardener, individually and collectively)  DO NOT use cotton or leather (which absorb and concentrate the resin), natural rubber (latex), medical or polyethylene gloves (which absorb the resin).  NOTE:  The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.  Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.			
Body protection	See Other protection below			
Other protection	Overalls. P.V.C apron. Barrier cream.			

## **Respiratory protection**

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

▶ Skin cleansing cream.

## **SECTION 9 Physical and chemical properties**

Information on basic physical and chemical properties

## Appearance Thick white paste with a characteristic odour; does not mix with water.

Physical state	Free-flowing Paste	Relative density (Water = 1)	1.4
Odour	Not Available	Partition coefficient n- octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	>100 (PMCC)	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available
Heat of Combustion (kJ/g)	Not Available	Ignition Distance (cm)	Not Available
Flame Height (cm)	Not Available	Flame Duration (s)	Not Available
Enclosed Space Ignition Time Equivalent (s/m3)	Not Available	Enclosed Space Ignition Deflagration Density (g/m3)	Not Available

## **SECTION 10 Stability and reactivity**

Chemwatch: 5137-55 Page 6 of 10 Version No: 9.1 Epirez Multi-Purpose Epoxy Concrete Repair (Multi II) Base

Chemical stability	Product is considered stable and hazardous polymerisation will not occur.	
Possibility of hazardous reactions	See section 7	
Conditions to avoid	See section 7	
Incompatible materials	See section 7	
Hazardous decomposition products	See section 5	

#### **SECTION 11 Toxicological information**

#### Information on toxicological effects

Inhaled	The material is not thought to produce respiratory irritation (as classified by EC Directives using animal models). Nevertheless inhalation of the material, especially for prolonged periods, may produce respiratory discomfort and occasionally, distress.			
Ingestion	Accidental ingestion of the material may be damaging to the health of the individual.  Ingestion may result in nausea, abdominal irritation, pain and vomiting			
Skin Contact	Skin contact with the material may damage the health of the individual; systemic effects may result following absorption.  The material may accentuate any pre-existing dermatitis condition  Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects.  Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.  The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.			
Eye	This material can cause eye irritation and damage in some persons.			
Chronic	Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.  There is some evidence that inhaling this product is more likely to cause a sensitisation reaction in some persons compared to the general population.  Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population.			

Epirez Multi-Purpose	TOXICITY	IRRITATION
Epoxy Concrete Repair (Multi II) Base	Not Available	Not Available
hianhanal A/ dighyaidyl	TOXICITY	IRRITATION
bisphenol A/ diglycidyl ether polymer, high	dermal (rat) LD50: >1200 mg/kg <sup>[2]</sup>	Eye (rabbit): 100 mg - mild
molecular weight	Oral (Mouse) LD50; >500 mg/kg <sup>[2]</sup>	
	TOXICITY	IRRITATION
	Oral (Rat) LD50: >10000 mg/kg <sup>[2]</sup>	Eye (rabbit): mild [Ciba]
		Eye: adverse effect observed (irritating) <sup>[1]</sup>
		Skin (guinea pig): sensitiser
(C12-14)alkylglycidyl ether		Skin (human): Irritant
		Skin (human): non- sensitiser
		Skin (rabbit): moderate
		Skin : Moderate
		Skin: adverse effect observed (irritating) <sup>[1]</sup>

Legend:

1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

#### BISPHENOL A/ DIGLYCIDYL ETHER POLYMER, HIGH **MOLECULAR WEIGHT**

for RTECS No: SL 6475000: (liquid grade) Equivocal tumourigen by RTECS criteria Somnolence, dyspnea, peritonitis The chemical structure of hydroxylated diphenylalkanes or bisphenols consists of two phenolic rings joined together through a bridging carbon. This class of endocrine disruptors that mimic oestrogens is widely used in industry, particularly in plastics. Bisphenol A (BPA) and some related compounds exhibit oestrogenic activity in human breast cancer cell line MCF-7, but there were remarkable differences in activity. Several derivatives of BPA exhibited significant thyroid hormonal activity towards rat pituitary cell line GH3, which releases growth hormone in a thyroid hormone-dependent manner. However, BPA and several other derivatives did not show such activity.

The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.

Animal testing over 13 weeks showed bisphenol A diglycidyl ether (BADGE) caused mild to moderate, chronic, inflammation of

Issue Date: 10/03/2023

Print Date: 01/10/2024

Chemwatch: **5137-55** Page **7** of **10** 

Version No: 9.1

#### Epirez Multi-Purpose Epoxy Concrete Repair (Multi II) Base

Issue Date: **10/03/2023**Print Date: **01/10/2024** 

Reproductive and Developmental Toxicity: Animal testing showed BADGE given over several months caused reduction in body weight but had no reproductive effects. Cancer-causing potential: It has been concluded that bisphenol A diglycidyl ether cannot be classified with respect to its cancercausing potential in humans. Genetic toxicity: Laboratory tests on genetic toxicity of BADGE have so far been negative. Immunotoxicity: Animal testing suggests regular injections of diluted BADGE may result in sensitization. Consumer exposure: Comsumer exposure to BADGE is almost exclusively from migration of BADGE from can coatings into food. Testing has not found any evidence of hormonal disruption. Oxiranes (including glycidyl ethers and alkyl oxides, and epoxides) share many common characteristics with respect to animal toxicology. One such oxirane is ethyloxirane; data presented here may be taken as representative. (C12-14)ALKYLGLYCIDYL For 1,2-butylene oxide (ethyloxirane): **ETHER** In animal testing, ethyloxirane increased the incidence of tumours of the airways in animals exposed via inhalation. However, tumours were not observed in mice chronically exposed via skin. Two structurally related substances, oxirane (ethylene oxide) and methyloxirane (propylene oxide), which are also direct-acting alkylating agents, have been classified as causing cancer. **BISPHENOL A/** DIGLYCIDYL ETHER The following information refers to contact allergens as a group and may not be specific to this product. POLYMER, HIGH Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The **MOLECULAR WEIGHT &** pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic (C12-14)ALKYLGLYCIDYL skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. **ETHER** 

Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion	<b>✓</b>	Reproductivity	×
Serious Eye Damage/Irritation	<b>✓</b>	STOT - Single Exposure	×
Respiratory or Skin sensitisation	<b>✓</b>	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×

Legend: 

∠ − Data either not available or does not fill the criteria for classification

√ − Data available to make classification

## **SECTION 12 Ecological information**

#### Toxicity

Epirez Multi-Purpose Epoxy Concrete Repair (Multi II) Base	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
bisphenol A/ diglycidyl	Endpoint	Test Duration (hr)	Species	Value	Source
ether polymer, high	EC50	48h	Crustacea	Crustacea ~2mg/l	
molecular weight	EC50(ECx)	48h	Crustacea	~2mg/l	2
	Endpoint	Test Duration (hr)	Species	Value	Source
(040.44)-!!!!!	EC50	48h	Crustacea	6.07mg/l	2
(C12-14)alkylglycidyl ether	LC50	96h	Fish	>5000mg/l	2
	EC50(ECx)	48h	Crustacea	6.07mg/l	2
Legend:			ECHA Registered Substances - Ecotox ta 5. ECETOC Aquatic Hazard Assessi	,	

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. **DO NOT** discharge into sewer or waterways.

## Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients

## Bioaccumulative potential

Ingredient	Bioaccumulation
	No Data available for all ingredients

#### Mobility in soil

Chemwatch: 5137-55 Version No: 9.1

#### Epirez Multi-Purpose Epoxy Concrete Repair (Multi II) Base

Issue Date: 10/03/2023 Print Date: 01/10/2024

Ingredient	Mobility
	No Data available for all ingredients

## **SECTION 13 Disposal considerations**

#### Waste treatment methods

Product / Packaging disposal

- Recycle wherever possible or consult manufacturer for recycling options.
- ▶ Consult State Land Waste Management Authority for disposal.
- Material may be disposed of by controlled burning in an approved incinerator or buried in an approved landfill.
- Prior to disposal in a landfill the material should be mixed with the other component and reacted to render the material inert.

#### **SECTION 14 Transport information**

## **Labels Required**



#### **Marine Pollutant**



HAZCHEM

•3Z

#### Land transport (ADG)

14.1. UN number or ID number	3082		
14.2. UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains bisphenol A/ diglycidyl ether polymer, high molecular weight)		
14.3. Transport hazard class(es)	Class Subsidiary Hazard	9 Not Applicable	
14.4. Packing group	III		
14.5. Environmental hazard	Environmentally hazardous		
14.6. Special precautions for user	Special provisions 274 331 335 375 AU01  Limited quantity 5 L		

Environmentally Hazardous Substances meeting the descriptions of UN 3077 or UN 3082  $\,$ 

are not subject to this Code when transported by road or rail in;

- (a) packagings;
- (b) IBCs; or
- (c) any other receptacle not exceeding 500 kg(L).
- Australian Special Provisions (SP AU01) ADG Code 7th Ed.

## Air transport (ICAO-IATA / DGR)

14.1. UN number	3082			
14.2. UN proper shipping name	Environmentally hazardous substance, liquid, n.o.s. (contains bisphenol A/ diglycidyl ether polymer, high molecular weight)			
	ICAO/IATA Class	9		
14.3. Transport hazard class(es)	ICAO / IATA Subsidiary Hazard	Not Applicable		
0.000(00)	ERG Code	9L		
14.4. Packing group	III			
14.5. Environmental hazard	Environmentally hazardous			
14.6. Special precautions for user	Special provisions		A97 A158 A197 A215	
101 4001	Cargo Only Packing Instructions		964	
	Cargo Only Maximum Qty / Pack		450 L	

Chemwatch: **5137-55** Page **9** of **10** 

Version No: 9.1

#### Epirez Multi-Purpose Epoxy Concrete Repair (Multi II) Base

Issue Date: **10/03/2023**Print Date: **01/10/2024** 

Passenger and Cargo Packing Instructions	964
Passenger and Cargo Maximum Qty / Pack	450 L
Passenger and Cargo Limited Quantity Packing Instructions	Y964
Passenger and Cargo Limited Maximum Qty / Pack	30 kg G

#### Sea transport (IMDG-Code / GGVSee)

14.1. UN number	3082		
14.2. UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains bisphenol A/ diglycidyl ether polymer, high molecular weight)		
14.3. Transport hazard class(es)	IMDG Class     9       IMDG Subsidiary Hazard     Not Applicable		
14.4. Packing group			
14.5 Environmental hazard	Marine Pollutant		
14.6. Special precautions for user	EMS Number F-A , S-F Special provisions 274 335 969 Limited Quantities 5 L		

#### 14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

#### 14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
bisphenol A/ diglycidyl ether polymer, high molecular weight	Not Available
(C12-14)alkylglycidyl ether	Not Available

## 14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
bisphenol A/ diglycidyl ether polymer, high molecular weight	Not Available
(C12-14)alkylglycidyl ether	Not Available

## **SECTION 15 Regulatory information**

## Safety, health and environmental regulations / legislation specific for the substance or mixture

## bisphenol A/ diglycidyl ether polymer, high molecular weight is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5

Australian Inventory of Industrial Chemicals (AIIC)

Chemical Footprint Project - Chemicals of High Concern List

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

## (C12-14)alkylglycidyl ether is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australian Inventory of Industrial Chemicals (AIIC)

Chemical Footprint Project - Chemicals of High Concern List

## **Additional Regulatory Information**

Not Applicable

#### **National Inventory Status**

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes

Issue Date: 10/03/2023 Chemwatch: 5137-55 Page 10 of 10 Version No: 9.1 Print Date: 01/10/2024

## Epirez Multi-Purpose Epoxy Concrete Repair (Multi II) Base

National Inventory	Status
Canada - DSL	Yes
Canada - NDSL	No (bisphenol A/ diglycidyl ether polymer, high molecular weight; (C12-14)alkylglycidyl ether)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	No (bisphenol A/ diglycidyl ether polymer, high molecular weight; (C12-14)alkylglycidyl ether)
Vietnam - NCI	Yes
Russia - FBEPH	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

## **SECTION 16 Other information**

Revision Date	10/03/2023
Initial Date	16/03/2006

### **SDS Version Summary**

Version	Date of Update	Sections Updated
8.1	23/12/2022	Classification review due to GHS Revision change.
9.1	10/03/2023	Classification change due to full database hazard calculation/update.

#### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.