# **Epirez Supaflow HF Grout ITW POLYMERS & FLUIDS**

Chemwatch: 4531-3 Version No: 8.1

Safety Data Sheet according to Work Health and Safety Regulations (Hazardous Chemicals) 2023 and ADG requirements

Issue Date: **10/03/2023**Print Date: **02/10/2024**S.GHS.AUS.EN

# SECTION 1 Identification of the substance / mixture and of the company / undertaking

#### **Product Identifier**

Product name	Epirez Supaflow HF Grout	
Chemical Name	Not Applicable	
Synonyms	Not Available	
Chemical formula	Not Applicable	
Other means of identification	Not Available	

# Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Used as a precision non-shrink cement grout after mixing with water.

# Details of the manufacturer or supplier of the safety data sheet

Registered company name	ITW POLYMERS & FLUIDS	ITW Polymers & Fluids (NZ)
Address 100 Hassall Street, Wetherill Park NSW 2164 Australia		Unit 2/38 Trugood Drive, East Tamaki, Auckland 2013 New Zealand
<b>Telephone</b> +61 2 9757 8800		0800 476 265
Fax +61 2 9757 3855		+64 9 273 6489
Website www.itwpf.com.au		www.itwpf.co.nz
Email Not Available		Not Available

# **Emergency telephone number**

Association / Organisation	CHEMWATCH EMERGENCY RESPONSE (24/7)	ITW Polymers & Fluids (NZ)	CHEMWATCH EMERGENCY RESPONSE (24/7)
Emergency telephone numbers	+61 1800 951 288	0800 2436 2255	+61 1800 951 288
Other emergency telephone numbers	+61 3 9573 3188	Not Available	+61 3 9573 3188

Once connected and if the message is not in your preferred language then please dial 01

# **SECTION 2 Hazards identification**

# Classification of the substance or mixture

HAZARDOUS CHEMICAL. NON-DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

Poisons Schedule	Not Applicable		
Classification [1] Skin Corrosion/Irritation Category 2, Serious Eye Damage/Eye Irritation Category 2A, Specific Target Organ Toxicity - Si Exposure (Respiratory Tract Irritation) Category 3, Specific Target Organ Toxicity - Repeated Exposure Category 2			
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI		

# Label elements

Hazard pictogram(s)





**Epirez Supaflow HF Grout** 

Issue Date: 10/03/2023 Print Date: 02/10/2024

Signal word	Warning
-------------	---------

# Hazard statement(s)

Version No: 8.1

H315	Causes skin irritation.	
H319	H319 Causes serious eye irritation.	
H335	H335 May cause respiratory irritation.	
H373 May cause damage to organs through prolonged or repeated exposure.		

# Precautionary statement(s) General

P101	If medical advice is needed, have product container or label at hand.	
P102	Keep out of reach of children.	
P103	Read carefully and follow all instructions.	

# Precautionary statement(s) Prevention

P260	Do not breathe dust/fume.	
P271	Use only outdoors or in a well-ventilated area.	
P280	Wear protective gloves, protective clothing, eye protection and face protection.	
P264 Wash all exposed external body areas thoroughly after handling.		

# Precautionary statement(s) Response

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P312	Call a POISON CENTER/doctor/physician/first aider/if you feel unwell.	
P337+P313	If eye irritation persists: Get medical advice/attention.	
P302+P352	IF ON SKIN: Wash with plenty of water.	

# Precautionary statement(s) Storage

P405	Store locked up.	
P403+P233 Store in a well-ventilated place. Keep container tightly closed.		

# Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

# **SECTION 3 Composition / information on ingredients**

# **Substances**

See section below for composition of Mixtures

# **Mixtures**

CAS No	%[weight]	Name
65997-15-1	30-60	portland cement
14808-60-7.	30-60	graded sand
Not Available	1-10 Ingredients determined not to be hazardous	
Legend:  1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L * EU IOELVs available		

# **SECTION 4 First aid measures**

Description of first aid mea	If this product comes in contact with the eyes:  • Wash out immediately with fresh running water.  • Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.  • Seek medical attention without delay; if pain persists or recurs seek medical attention.  • Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs:  If skin contact occurs:  If skin contact occurs:

Issue Date: 10/03/2023 Chemwatch: 4531-3 Page 3 of 9 Version No: 8.1 Print Date: 02/10/2024

# **Epirez Supaflow HF Grout**

	<ul> <li>Flush skin and hair with running water (and soap if available).</li> <li>Seek medical attention in event of irritation.</li> </ul>
Inhalation	<ul> <li>If dust is inhaled, remove from contaminated area.</li> <li>Encourage patient to blow nose to ensure clear passage of breathing.</li> <li>If irritation or discomfort persists seek medical attention.</li> </ul>
Ingestion	<ul> <li>If swallowed do NOT induce vomiting.</li> <li>If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>Observe the patient carefully.</li> <li>Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.</li> <li>Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li> <li>Seek medical advice.</li> </ul>

# Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

# **SECTION 5 Firefighting measures**

# **Extinguishing media**

- ▶ There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

# Special hazards arising from the substrate or mixture

Fire Incompatibility None known.

dvice for firefighters	
Fire Fighting	<ul> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>Wear breathing apparatus plus protective gloves in the event of a fire.</li> <li>Prevent, by any means available, spillage from entering drains or water courses.</li> <li>Use fire fighting procedures suitable for surrounding area.</li> </ul>
Fire/Explosion Hazard	<ul> <li>Non combustible.</li> <li>Not considered a significant fire risk, however containers may burn.</li> <li>Combustion products include:</li> <li>silicon dioxide (SiO2)</li> <li>May emit corrosive fumes.</li> </ul>
HAZCHEM	Not Applicable

# **SECTION 6 Accidental release measures**

# Personal precautions, protective equipment and emergency procedures

See section 8

# **Environmental precautions**

See section 12

# Methods and material for containment and cleaning up

Minor Spills	<ul> <li>Clean up all spills immediately.</li> <li>Avoid breathing dust and contact with skin and eyes.</li> <li>Wear protective clothing, gloves, safety glasses and dust respirator.</li> <li>Use dry clean up procedures and avoid generating dust.</li> </ul>
Major Spills	Moderate hazard.  CAUTION: Advise personnel in area.  Alert Emergency Services and tell them location and nature of hazard.  Control personal contact by wearing protective clothing.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

# **SECTION 7 Handling and storage**

Precautions for safe nandling				
Safe handling	<ul> <li>Avoid all personal contact, including inhalation.</li> <li>Wear protective clothing when risk of exposure occurs.</li> <li>Use in a well-ventilated area.</li> <li>Prevent concentration in hollows and sumps.</li> </ul>			
Other information	▶ Store in original containers.			

Chemwatch: 4531-3 Pag

**Epirez Supaflow HF Grout** 

Page **4** of **9**Issue Date: **10/03/2023**Print Date: **02/10/2024** 

- ▶ Keep containers securely sealed.
- Store in a cool, dry area protected from environmental extremes.
- Store away from incompatible materials and foodstuff containers.

# Conditions for safe storage, including any incompatibilities

#### Suitable container

- ▶ Lined metal can, lined metal pail/ can.
- Plastic pail.
- Polyliner drum.
- ▶ Packing as recommended by manufacturer.

# Storage incompatibility

- Avoid strong acids, acid chlorides, acid anhydrides and chloroformates.
- Avoid contact with copper, aluminium and their alloys.
- Segregate from alcohol, water.

# **SECTION 8 Exposure controls / personal protection**

# **Control parameters**

Version No: 8.1

#### Occupational Exposure Limits (OEL)

#### INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	portland cement	Portland cement	10 mg/m3	Not Available	Not Available	(a) This value is for inhalable dust containing no asbestos and < 1% crystalline silica.
Australia Exposure Standards	graded sand	Quartz (respirable dust)	0.05 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	graded sand	Silica - Crystalline: Quartz (respirable dust)	0.05 mg/m3	Not Available	Not Available	Not Available

Ingredient	Original IDLH	Revised IDLH
portland cement	5,000 mg/m3	Not Available
graded sand	25 mg/m3 / 50 mg/m3	Not Available

#### **Exposure controls**

# Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

#### Individual protection measures, such as personal protective equipment











# Eye and face protection

- Safety glasses with side shields.
- ► Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent]
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy
  document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.

#### Skin protection

See Hand protection below

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.

#### Hands/feet protection

Personal hygiene is a key element of effective hand care.

Experience indicates that the following polymers are suitable as glove materials for protection against undissolved, dry solids, where abrasive particles are not present.

- polychloroprene.
- nitrile rubber.
- ▶ butyl rubber.

# **Body protection**

# See Other protection below

#### Other protection

- Overalls.
- P.V.C apron.
- Barrier cream.
- Skin cleansing cream.

**Epirez Supaflow HF Grout** 

Page 5 of 9 Issue Date: 10/03/2023 Print Date: 02/10/2024

# Respiratory protection

Type -P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

# **SECTION 9 Physical and chemical properties**

# Information on basic physical and chemical properties

Appearance	Grey powder with no odour; insoluble in water. Hardens after reaction with water.					
Physical state	Divided Solid	Relative density (Water = 1)	1.91			
Odour	Not Available	Partition coefficient n- octanol / water	Not Available			
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Applicable			
pH (as supplied)	Not Applicable	Decomposition temperature (°C)	Not Applicable			
Melting point / freezing point (°C)	Not Applicable	Viscosity (cSt)	Not Applicable			
Initial boiling point and boiling range (°C)	Not Applicable	Molecular weight (g/mol)	Not Applicable			
Flash point (°C)	Not Applicable	Taste	Not Available			
Evaporation rate	Not Applicable	Explosive properties	Not Available			
Flammability	Not Applicable	Oxidising properties	Not Available			
Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Applicable			
Lower Explosive Limit (%)	Not Applicable	Volatile Component (%vol)	Not Applicable			
Vapour pressure (kPa)	Not Applicable	Gas group	Not Available			
Solubility in water	Reacts	pH as a solution (1%)	Not Available			
Vapour density (Air = 1)	Not Applicable	VOC g/L	Not Available			
Heat of Combustion (kJ/g)	Not Available	Ignition Distance (cm)	Not Available			
Flame Height (cm)	Not Available	Flame Duration (s)	Not Available			
Enclosed Space Ignition Time Equivalent (s/m3)	Not Available	Enclosed Space Ignition Deflagration Density (g/m3)	Not Available			

# **SECTION 10 Stability and reactivity**

Reactivity	See section 7
Chemical stability	Product is considered stable and hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

# **SECTION 11 Toxicological information**

# Information on toxicological effects

Inhaled	The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.  Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled.  If prior damage to the circulatory or nervous systems has occurred or if kidney damage has been sustained, proper screenings should be conducted on individuals who may be exposed to further risk if handling and use of the material result in excessive exposures.  Effects on lungs are significantly enhanced in the presence of respirable particles.
Ingestion	The material has <b>NOT</b> been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.
Skin Contact	This material can cause inflammation of the skin on contact in some persons.  The material may accentuate any pre-existing dermatitis condition

Version No: 8.1 **Epirez Supaflow HF Grout**  Issue Date: 10/03/2023 Print Date: 02/10/2024

Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. Evidence exists, or practical experience predicts, that the material may cause eye irritation in a substantial number of individuals. Eve Prolonged eye contact may cause inflammation characterised by a temporary redness of the conjunctiva (similar to windburn). Long-term exposure to respiratory irritants may result in airways disease, involving difficulty breathing and related whole-body problems Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. Chronic Overexposure to the breathable dust may cause coughing, wheezing, difficulty in breathing and impaired lung function. Chronic symptoms may include decreased vital lung capacity and chest infections. Repeated exposures in the workplace to high levels of fine-divided dusts may produce a condition known as pneumoconiosis, which is the lodgement of any inhaled dusts in the lung, irrespective of the effect. This is particularly true when a significant number of particles less than 0.5 microns (1/50000 inch) are present. TOXICITY IRRITATION **Epirez Supaflow HF Grout** Not Available Not Available

TOXICITY IRRITATION portland cement Not Available Not Available TOXICITY IRRITATION graded sand Not Available Oral (Rat) LD50: 500 mg/kg<sup>[2]</sup>

Legend:

1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to **Epirez Supaflow HF Grout** irritants may produce conjunctivitis. The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The PORTLAND CEMENT pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a nonallergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic **Epirez Supaflow HF Grout** individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the

& PORTLAND CEMENT

irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia.

**PORTLAND CEMENT & GRADED SAND** 

No significant acute toxicological data identified in literature search.

Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion	<b>~</b>	Reproductivity	×
Serious Eye Damage/Irritation	<b>~</b>	STOT - Single Exposure	•
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	•
Mutagenicity	×	Aspiration Hazard	×

Legend:

🗶 – Data either not available or does not fill the criteria for classification

- Data available to make classification

# **SECTION 12 Ecological information**

#### **Toxicity**

Epirez Supaflow HF Grout	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
	Endpoint	Test Duration (hr)	Species	Value	Source
portland cement	Not Available	Not Available	Not Available	Not Available	Not Available
graded sand	Endpoint	Test Duration (hr)	Species	Value	Source

Chemwatch: 4531-3

Page 7 of 9 Issue Date: 10/03/2023 Version No: 8.1 Print Date: 02/10/2024 **Epirez Supaflow HF Grout** 

	Not Available	Not Available	Not Available	Not Available	Not Available		
Legend:	4. US EPA, E	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data					

DO NOT discharge into sewer or waterways.

#### Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air	
	No Data available for all ingredients	No Data available for all ingredients	

#### Bioaccumulative potential

Ingredient	Bioaccumulation	
	No Data available for all ingredients	

#### Mobility in soil

Ingredient	Mobility	
	No Data available for all ingredients	

#### **SECTION 13 Disposal considerations**

#### Waste treatment methods

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction
- Reuse
- Recycling
- ▶ Disposal (if all else fails)

# Product / Packaging disposal

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use.

- DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- ▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Where in doubt contact the responsible authority.
- ▶ Recycle wherever possible or consult manufacturer for recycling options.
- ▶ Consult State Land Waste Management Authority for disposal.
- Bury residue in an authorised landfill.
- ▶ Recycle containers if possible, or dispose of in an authorised landfill.

# **SECTION 14 Transport information**

# **Labels Required**

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

# 14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

# 14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
portland cement	Not Available
graded sand	Not Available

Chemwatch: 4531-3

Page 8 of 9

Epirez Supaflow HF Grout

Issue Date: **10/03/2023**Print Date: **02/10/2024** 

# 14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
portland cement	Not Available
graded sand	Not Available

# **SECTION 15 Regulatory information**

#### Safety, health and environmental regulations / legislation specific for the substance or mixture

# portland cement is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

#### graded sand is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australia Model Work Health and Safety Regulations - Hazardous chemicals (other than lead) requiring health monitoring

Australian Inventory of Industrial Chemicals (AIIC)

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 1: Carcinogenic to humans

International Agency fsor Research on Cancer (IARC) - Agents Classified by the IARC Monographs

# **Additional Regulatory Information**

Not Applicable

Version No: 8.1

#### **National Inventory Status**

National Inventory	Status	
Australia - AIIC / Australia Non-Industrial Use	Yes	
Canada - DSL	Yes	
Canada - NDSL	No (portland cement; graded sand)	
China - IECSC	Yes	
Europe - EINEC / ELINCS / NLP	Yes	
Japan - ENCS	No (portland cement)	
Korea - KECI	Yes	
New Zealand - NZIoC	Yes	
Philippines - PICCS	No (portland cement)	
USA - TSCA	Yes	
Taiwan - TCSI	Yes	
Mexico - INSQ	Yes	
Vietnam - NCI	Yes	
Russia - FBEPH	Yes	
Legend:	Yes = All CAS declared ingredients are on the inventory  No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.	

# **SECTION 16 Other information**

R	evision Date	10/03/2023
	Initial Date	29/03/2005

# **SDS Version Summary**

Version	Date of Update	Sections Updated
7.1	23/12/2022	Classification review due to GHS Revision change.
8.1	10/03/2023	Classification change due to full database hazard calculation/update.

# Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

Chemwatch: 4531-3 Page 9 of 9 Issue Date: 10/03/2023 Version No: 8.1 Print Date: 02/10/2024

**Epirez Supaflow HF Grout** 

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.