

TECHNICAL DATA SHEET

Dy-Mark (Aust) Pty Ltd

PO Box 1556 Toowong 4066

Phone: 1300 396 275 Fax: 1300 360 440

www.dymark.com.au



Dy-Mark SPRAY & MARK WATER-BASED



Dy-Mark Spray & Mark Water-Based is a low toxicity marking paint that features an advanced UV resistant formula and a 360°C valve for any angle application. Water-Based Spray & Mark is a workplace friendly paint ideal for; construction, landscaping and civil works applications. **Spray & Mark** is suitable for use with the **Long Arm Handle** and **2-Wheel Spot Marking Handle**, also available from Dy-Mark.

DIRECTIONS FOR USE

Suitable Surfaces:

Concrete, bitumen, steel, timber and grass.

Ideal Application Temperature:

Between 5°C and 40°C. Avoid use in windy conditions.

Before Spraying:

Shake can for at least 45 seconds **AFTER** the mixing ball begins to rattle. Shake the can occasionally during use.

Application:

Hold the can **UPRIGHT** or in the **INVERTED** position and spray with the nozzle approximately 10-15cm from the surface. Adjust the spray width by moving closer or further away from the surface to be sprayed.

Coverage:

Will produce 200 'X' marks, 80-100m in a 50mm continuous line.

Drying Time:

Touch dry in 5 minutes at 25°C.

Drying will be slower in cold and humid conditions, in the absence of ventilation or where heavy film build is applied.

After Spraying:

Prevent blocking by holding the can **UPRIGHT** and spraying until only clear gas escapes. Also **wipe spray tip** of nozzle clean. **Clean up** wet paint with **Dy-Mark Acetone** or **General Purpose Thinner**.

Caution:

Painted surfaces may become slippery when wet. Refer to disclaimer on page 3.

TECHNICAL DATA SHEET

Dy-Mark (Aust) Pty Ltd

PO Box 1556 Toowong 4066

Phone: 1300 396 275 Fax: 1300 360 440

www.dymark.com.au



TECHNICAL DATA

Size:	350g Aerosol
Colour:	4 Standard and 3 Fluoro colours
Finish:	Matt
Consistency:	Liquid
Propellant:	Dimethyl Ether

STORAGE

Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°C. Store in a well ventilated place.

DISPOSAL

Dispose of contents/container according to regional regulations.

FIRST AID/SAFETY INFORMATION

Please refer to Safety Data Sheet before use. Safety data sheets are available for download from our website www.dymark.com.au or from following QR code:



Call a POISON CENTRE: Australia 13 11 26, New Zealand 0800 764 766 or doctor/physician if you feel unwell.

Intentional misuse by deliberately inhaling contents can be harmful or fatal.

KEEP OUT OF REACH OF CHILDREN.

TECHNICAL DATA SHEET

Dy-Mark (Aust) Pty Ltd

PO Box 1556 Toowong 4066

Phone: 1300 396 275 Fax: 1300 360 440

www.dymark.com.au



DISCLAIMER

The information provided within this Technical Data Sheet is intended as a guide only. The slip resistance and performance of this product depends on many factors outside the control of Dy-Mark; including surface preparation, surface-specific conditions, surface types, correct application and environmental conditions.

Dy-Mark recommends customers undertake their own risk assessment prior to use to determine the suitability of the product for the particular use intended. Some factors to consider:

- Slip resistance required
- Surface type
- Volume of traffic
- Potential exposure to any surface contaminants eg. Water, solvents or chemicals

It is essential that a sample of the product be applied to the intended area of use to ensure it is acceptable in appearance and finish and that it performs on the specific surface.

For further information please contact the Dy-Mark Sales and Customer Support Centre on 1300 396 275.