



## PRODUCT INFORMATION

June 2017 Update

# 5060AN Hi Speed Refuelling Drum Pump

The 5060AN hi speed refuelling drum pump is easy to use and with little effort is capable of delivering up to 110 litres per minute or best in class delivery rates of 1.1 litres per rotation.

Supplied complete with 2.6 metres of antistatic, UV & fuel resistant hose, spout, in-built spout holster, heavy duty bung adaptor and 3-piece telescopic downtube, the 5060AN is suitable for use with 60L & 205L drums and IBC's.

The 5060AN also features a PPR covered handle grip designed to reduce operator fatigue during high volume fuel transfer.

Suitable for the fast and efficient transfer of diesel fuel, petrol, light oils up to SAE30 and kerosene the 5060AN incorporates a lockable handle to help minimise the possibility of unauthorised fuel transfer.

### PRODUCT SPECIFICATIONS, FEATURES AND BENEFITS

High volume easy to use pump delivers up to 110 L/min

Delivery rates of 1.1 litres per rotation

Lockable handle minimises the possibility of unauthorised fuel transfer

New PPR covered handle grip reduces operator fatigue

New and improved rubber seal above the bung adaptor reduces the possibility of fuel contamination

Supplied complete with 2.6m of UV and fuel resistant hose, spout, in built spout holster, 3-piece telescopic downtube and heavy duty bung adaptor

3-piece telescopic downtube suits 60L & 205L drums and IBC's

Steel springs on the hose assembly reduce the possibility of premature hose failure

Suitable for the transfer of diesel fuel, petrol, light oils up to SAE30 and kerosene

### ORDERING INFORMATION

#### 5060AN

Hi speed refuelling drum pump

