



PRODUCT INFORMATION

July 2013

501A Rotary Drum Pump

The 501A rotary drum pump is suitable for the transfer of oil, diesel and petrol from 60L and 205L drums and bulk tanks. It's cast alloy body construction ensures a long working life and smooth operation.

The 501A rotary drum pump vanes make it suitable for the transfer of unleaded and leaded petrol and can syphon fuels and lubes in reverse. The 501A comes complete with 2.2m of anti static fuel hose, spout, spout holster and 2" BSP bung adaptor & delivers up to 18 L/min or 0.26L per rotation when pumping diesel fuel.



PRODUCT SPECIFICATIONS, FEATURES AND BENEFITS

Suitable for the transfer of diesel, petrols, kerosene, lube oil and machine oil

2" BSP bung adaptor

Hose: anti static fuel hose

Delivery rates of up to 18 L/min or 0.26L per rotation

Cast alloy body construction

Can syphon and transfer fuels and lubes in reverse

Weight: 3.6 kg

Length: 1300mm (4.3ft)

Delivery tube: 31.8mm (1¼") OD

Hose: 19.05mm (¾") ID x 2.2m

Includes 2.2m of farm tank hose, bung adaptor, rubber gasket, a four chamber rotor assembly, spout and spout holster

ORDERING INFORMATION

501A
Rotary Drum Pump

