


A Rubber Single Line Welding Hose (A108)



Application:	Used for use with all types of welding and cutting equipment in workshops, shipyards, construction sites and manufacturing industries.
Tube:	NR / SBR
Reinforcing:	Polyester
Cover:	Red - Acetylene / Blue - Oxy SBR / EPDM
Temperature:	-25°C to 75°C
Special Features:	<ul style="list-style-type: none"> Ozone and abrasion resistant cover confirms to AS1335 Minimum cut length of 5 mtrs, charges apply for cutting hose.

Part No.	Dimensions (mm)		Working Pressure		BP PSI	Bend Radius (mm)	Weight kg/mtr	Coil Lengths	Price \$ per mtr
	ID	OD	PSI	MPa					
Red									
A108005R	5	12	217	1.5	870	60 ¹	0.15	2 x 100M Reels	3.22
A108006R	6	13	217	1.5	870	72 ¹	0.17	2 x 100M Reels	3.87
A108010R	10	16	217	1.5	870	120 ¹	0.19	2 x 100M Reels	5.51
Blue									
A108005B	5	12	217	1.5	870	60 ¹	0.15	2 x 100M Reels	3.22
A108006B	6	13	217	1.5	870	72 ¹	0.17	2 x 100M Reels	3.87
A108010B	10	16	217	1.5	870	120 ¹	0.19	2 x 100M Reels	5.51

Price Group: HR
DB21

Rubber Twin Line Welding Hose (A109)




Application:	Used for use with all types of welding and cutting equipment in workshops, shipyards, construction sites and manufacturing industries.
Tube:	NR/SBR
Reinforcing:	Polyester
Cover:	Red - Acetylene / Blue - Oxy SBR / EPDM
Temperature:	-25°C to 75°C
Special Features:	<ul style="list-style-type: none"> Oil mist resistant Ozone and abrasion resistant cover confirms to AS1335 Minimum cut length of 5 mtrs, charges apply for cutting hose.

Part No.	Dimensions (mm)		Working Pressure		BP PSI	Bend Radius (mm)	Weight kg/mtr	Coil Lengths	Price \$ per mtr
	ID	OD	PSI	MPa					
A109005	5	12	217	1.5	870	60 ¹	.30	2 x 100M Reels	6.61

Price Group: HR
DB22

Welding Hose Assemblies (A109)



Application:	Crimped twin line welding hose. Oxy acetylene assembly
Tube:	Oil resistant synthetic rubber
Cover:	Smooth red & blue
Temperature Range:	-25°C to 75°C
Standards:	Hose assemblies complies AS1335:1995 Hose fittings complies AS4267:1995
Hose:	A109 twin line welding hose

Part No.	Dimensions (mm)		Working Pressure		BP PSI	Bend Radius (mm)	Weight kg/mtr	Coil Lengths	Price \$ per mtr
	ID	OD	PSI	MPa					
A1195CRIMP	5	12	217	1.5	870	60	0.30	5.0	119.94
A11975CRIMP	5	12	217	1.5	870	60	0.30	7.5	136.91
A11910CRIMP	5	12	217	1.5	870	60	0.30	10.0	158.93
A11915CRIMP	5	12	217	1.5	870	60	0.30	15.0	224.17
A11920CRIMP	5	12	217	1.5	870	60	0.30	20.0	237.79

Price Group: HR
DB25

¹ Denotes figure is calculated as theoretical.

Complete hose data specification sheets are available upon request.