

### 3 Way Standard Brass Ball Valve, L & T Port

<b>Design:</b>	Lever operated
<b>End Connection:</b>	Screwed Female BSP
<b>Body Material:</b>	Nickel-plated brass
<b>Seat &amp; Trim:</b>	PTFE seats
<b>Temperature:</b>	Air: -15°C to 150°C Water: 0°C to 150°C without steam
<b>Application:</b>	Domestic water services, heating and air-conditioning plants, compressed air systems. Available with a T or L-drilled ball.

Size		Working Pressure		L Port		T Port	
inch	mm	PSI	MPa	Part No.	Price \$	Part No.	Price \$
¼	6	360	2.5	BBV3WL006	101.51	BBV3WT006	101.51
⅜	10	360	2.5	BBV3WL010	101.51	BBV3WT010	101.51
½	15	360	2.5	BBV3WL012	101.51	BBV3WT012	101.51
¾	20	360	2.5	BBV3WL020	170.23	BBV3WT020	170.23
1	25	360	2.5	BBV3WL025	224.07	BBV3WT025	224.07
1¼	32	360	2.5	BBV3WL032	352.86	BBV3WT032	288.23
1½	40	360	2.5	BBV3WL040	457.90	BBV3WT040	489.79
2	50	360	2.5	BBV3WL050	676.87	BBV3WT050	676.87

Price Group: SD

AR01



### Ball Valve Bibcock without Hose Connection

<b>Design:</b>	Lever Tap
<b>End Connection:</b>	ISO228 (equivalent to DIN259 and BS2779)
<b>Body Materials:</b>	Nickel-plated brass
<b>Temperature:</b>	-20°C to 80°C
<b>Pressure:</b>	Max 220 PSI
<b>Application:</b>	Water, irrigation

Size		Part No.	Working Pressure		Price \$
inch	mm		PSI	MPa	
½ x ¾	15 x 20	BB015020	220	1.5	19.92
¾ x ¾	20 x 20	BB020	220	1.5	17.68

Price Group: SD

FP08



art.178

### Brass Ball Valve - Lever Operated Nozzle

<b>Design:</b>	Brass ball valve, complete with lever operated nozzle to suit 20mm hose.
<b>End Connection:</b>	¾" Hosetail
<b>Body Materials:</b>	Brass
<b>Temperature:</b>	-10° to 110°C
<b>Application:</b>	Water, irrigation

Size		Part No.	Price \$
inch	mm		
¾	20	FFS-HRN-BALL	33.48

Price Group: FE

FP08

