

Painted Rigid Roll Grooved Couplings

Application:	For hot water and potable water. Not for use with hydrocarbons, eg petroleum, kerosene and diesel.
Design:	The Dixon™ 402R Rigid Coupling has been designed for the Fire Protection Industry and provides rigidity for valve connections, fire sprinkler systems and long straight pipe runs. The tongue and recess design of the coupling adjusts to allow for standard pipe and roll or cut groove tolerances, positively clamping the pipe to resist flexural and torsional loads. Hot dip galvanised finish. Other materials available on request
Material:	Housing - Ductile Iron to ASTM-A536 EPDM (Black) Ductile Iron to ASTM-A536
Temperature:	-30° to 110°C
Markings:	Style 5
Compatibility:	Interchangeable with Fig 10
Approvals:	UL No. EX4390

Available while stocks last!



Size NB	Size (inch)	Part No.	WP		Approvals		Price \$
			PSI	MPa	UL	FM	
32	1¼	FWP-402R-42	300	2	×	×	9.37
40	1½	FWP-402R-48	300	2	×	✓	9.82
50	2	FWP-402R-60	300	2	✓	✓	10.58
65	2½	FWP-402R-76	300	2	✓	✓	12.69
80	3	FWP-402R-88	300	2	✓	✓	19.41
100	4	FWP-402R-114	300	2	✓	✓	28.97
150	6	FWP-402R-165	300	2	✓	✓	52.81
200	8	FWP-402R-219	300	2	✓	✓	117.90

Price Group: SD
CG08

Gaskets for Roll Grooved Couplings

Nitrile			
Size NB	Size (inch)	Part No.	Price \$
40	1½	GAS-RG-N40	5.23
50	2	GAS-RG-N50	6.79
65	2½	GAS-RG-N65	7.36
80	3	GAS-RG-N80	12.25
100	4	GAS-RG-N100	17.11
150	6	GAS-RG-N150	30.81

Price Group: SD
GA02

EPDM			
Size NB	Size (inch)	Part No.	Price \$
50	2	GAS-RG-60-E	6.79
65	2½	GAS-RG-76-E	7.36
80	3	GAS-RG-88-E	12.25
100	4	GAS-RG-114-E	17.11
150	6	GAS-RG-165-E	31.11
200	8	GAS-RG-219-E	46.59

Price Group: SD
GA03

