

P3 POWERLUBE®

PORTABLE, ENCLOSED GREASING SYSTEM (P3-OS2)

10 Year Warranty

*conditions apply

PRODUCT OVERVIEW

The P3 POWERLUBE™ is a premium quality, reliable, 50:1 air-operated greasing system that is excellent for high volume grease users that have many applications and require continuous high pressure greasing.

This portable grease dispensing system is suitable for 12.5 - 25kg pails and is equipped with a low air consumption motor that doesn't need to be lubricated due to the use of modern polymer materials.

Users will save on power and the oily mist and mess associated with air operated equipment is gone.

Suitable for underground coal mine applications.

FEATURES & BENEFITS

50:1 Ratio Air Motor

Delivers up to 460g/min for fast, efficient greasing. Instant delivery of up to 50 times applied air pressure

B2 Booster Gun

Boosts pressure up to 10,000psi to clear blocked grease nipples

360° ZSB Swivel

Improves manoeuvrability and offers easier one-handed operation

KY Supergrip Coupler

Positive no-leak connection ensures grease reaches the bearing

4m High Pressure Grease Hose

Allows access to hard to reach applications

Fully Repairable

Provides a much longer service life

Quiet Air Motor Design

Meets all industry noise level standards. Doesn't require air-line lubricator. Zinc components suitable for underground mining applications.

Adjustable Collar System

To accommodate different height 12.5kg - 25kg grease pails

Rubber-Edged Follower Plate

Wipes container clean & prevents air pockets & contamination

Fully Sealed With Grease Strainer

Delivers clean contamination free grease to the application

Trolley With Castor Wheels

Allows greasing system to easily be moved to application



TECHNICAL SPECIFICATIONS

P6001 (50:1) Air-operated pump

4m x 6mm ID delivery hose

Compatible with 12.5kg - 25kg pails

Grease viscosity up to NLGI No.2

Output 460g/min (at pump)

Maximum pump output pressure: 51,700kPa (7,500psi)

Maximum gun output pressure: 68,900kPa (10,000psi)

Maximum air pressure: 150psi

Minimum air pressure: 60psi

Pump inlet/outlet: 1/4" NPT (F)

Minimum compressor size: 0.08m³/min (3cfm)

OPTIONAL ACCESSORIES

PACKAGE INCLUDES

P6001 pump unit

Lid & rubber edged follower plate

Enclosed trolley with 4x castor wheels

4m high pressure hose

B2 booster gun

KY Supergrip coupler

ZSB high pressure swivel

Instruction manual

For more information visit www.macnaught.com.au/p3-os2

MACNAUGHT Pty Ltd
41-49 Henderson Street
Turrella, NSW, 2205
Australia

T +61 2 9567 0401
F +61 2 9597 7773
E info@macnaught.com.au
W www.macnaught.com.au

MACNAUGHT USA Inc
614 South Ware Boulevard
Tampa, Florida, 33619
United States

T +1813 628 5506
F +1509 694 8495
E info@macnaughtusa.com
W www.macnaughtusa.com