

ANCHOR LACQUER PAINT



PAINTS OF DISTINCTION

Description

Anchor Lacquer Spray paint is a fast drying, superior quality brilliant gloss hi-build lacquer for most surfaces. It has a drying time of around 5 minutes which is dependent on the ambient temperature. Best results are obtained at 20 -25°C.

It has excellent overcoat ability - blemishes can be re-coated immediately.

Colours have long lasting qualities due to excellent UV stability. The use of premium grade solvents, polymers & pigments ensure unparalleled results with excellent coverage.

Application

Anchor lacquer Paint can be used for

- Metal surfaces including gutters & fascia's.
- Wood surfaces .
- Plastics.
- Fibreglass.
- Masonry



Specification

Propellant, a blend of Hydrocarbons & Dimethyl Ether

Directions

Ideal temperature 20°C – 25°C. Degrease metals and grind them smoothly. Prime the surface first with the appropriate Anchor Undercoat. Ensure the surface is clean & free from dust. Shake the can vigorously for at least one minutes after hearing clearly the audible striking of the metal ball. Apply the spray crosswise from a distance of approx. 25-30cm.

ANCHOR LACQUER PAINT

**PAINTS OF DISTINCTION**

The surface is dry after 5-7 minutes depending on the temperature. Allow 10 minutes between coats. 2 – 3 coats are desirable.

Surface Preparation

Ensure the surface is clean & free from dust. A quality wax & grease remover can be used.

Packaging

12 Units per carton

1152 per pallet

Storage/Shelf Life

Store in a cool place out of the sun. Do not store above 50°C

Health & Safety

Aerosols should be completely empty before disposing. Recycle empty can if facility is available. Ensure adequate ventilation when using in enclosed areas. Keep away from heat, flames or sources of ignition.

Limitations

Avoid applying at temperatures below 10°C or in damp conditions. When applying at temperatures above 30°C, do a test spray to ensure the desired finish is achieved.

Disclaimer

CW Brands Pty Ltd believes that the information in this technical data sheet is an accurate description of the typical uses of the product. The data and statements are based on our research and development work and is to the best of our knowledge true and accurate. The user must ensure of the product(s) in their application prior to use in particular to determine its performance, efficiency and safety. The use of this product is beyond the manufacturer's control, and liability is restricted to the replacement of material proven faulty. The manufacturer is not responsible for any loss or damage arising from incorrect usage.

ANCHOR LACQUER PAINT

**PAINTS OF DISTINCTION**

Products conform solely to the information contained in this and other related Campbells Wholesale Pty Ltd publications. Wholesale Pty Ltd reserves the right to make changes to specifications and information related to the products at any time. Users are asked to check that the literature in their possession is the latest issue. Statements contained herein should not be considered as a warranty of any kind, expressed or implied in describing the performance or suitability of the product for a particular application. No liability is accepted for infringement of any patents or any other intellectual property right.