

Key Facts

- High quality TIG rod
- Suitable for a range of Stainless steel including: 302, 304, 308, 316, 318, 347, 410 and 410

Description

316L offers excellent resistance to general corrosion from organic and inorganic acids. Its metal deposits show good resistance to inter-crystalline corrosion and high temperatures due to it low carbon content.

Recommended Shielding Gas

100% Argon

Classification, Approvals & Conformances

AWS A5.9 ER316L A.B.S.AWS A5.9: ER316/316L ASME IX F No. 6 QPL-19933: MIL-316L Certified by CWB - AWS A5.9 ASME SFA 5.9 ER316/ER316L

Welding Positions

All positions

Applications

Suitable for welding 302, 304/304L, 308, 318, 347, 410 and 430 grades of stainless steel.

- Food processing equipment
- Water processing filtration plants
- General stainless steel fabrications

Typical Analysis/Composition Ni -Mn -Mo -S - Sulphur Nickel Manganese Molybdenum 11.0 -1.0 - 2.52.0 - 3.0< 0.03 14.0 Cr -C – P -Si - Silicon Chromium Carbon Phosphorus 18.0 - 20.0 < 0.03 0.30 - 0.65< 0.03 Cu -Copper < 0.75

Typical Weld Mechanical Properties

Yield Strength:	420 MPa
Tensile Strength:	590 MPa
Elongation:	45%

Packaging & Ordering Information Part Weight Size Number 1.0mm 300065 5kg 1.2mm 1kg 300066H 300066 1.2mm 5kg 300067H 1.6mm 1kg 300067 1.6mm 5kg 1kg 2.4mm 300068H 2.4mm 300068 5kg 3.2mm 1kg 300069H 3.2mm 5kg 300069

Disclaimer: The above information is provided as a guide; actual welding current and voltage will depend on the welding machine characteristics, which will vary from model to model. Other variables include run length and size, plate thickness, operator technique and gas type (if used). The user must evaluate the process, application and recommended professional advice. Under no circumstance will Dynaweld or its affiliates be liable for misuse or application of products this is entirely up to the user's ability.