

TESTED & COMMERCIAL CHAIN

BEAVER GRADE 80 (T) LIFTING CHAIN – B-ALLOY



BEAVER GRADE 80 (T) LIFTING CHAIN


Beaver Grade 80 (T) Chain, manufactured from heat treated alloy steel and is ideal for heavy duty lifting applications. It meets Australian standards AS 2321, Short-Link Chain for Lifting Purposes. It is high strength, rugged, versatile and low-weight.

- Quality testing is done throughout the manufacturing process
- Beaver Grade 80 Chain also carries markings in accordance with Australian standards, stamped at intervals along its entire length for easy identification

GRADE T(80) ALLOY CHAIN – TO AS 2321

Load Rated – 6 - 32mm

Code	W.L.L Tonne	Nominal Size mm	S mm	R mm	F mm	Finish	UOM	Metres Per 100(kg)
148006	1.20	6	6	18	22.2	Self Colour	Metre	115
148007	1.60	7	7	21	25.9	Self Colour	Metre	90
148008	2.00	8	8	24	29.6	Self Colour	Metre	71
148010	3.20	10	10	30	37	Self Colour	Metre	45
148013	5.40	13	13	39	48.1	Self Colour	Metre	26
148016	8.20	16	16	48	59.2	Self Colour	Metre	17
148020	12.8	20	20	60	74	Self Colour	Metre	11
148022	16.00	22	22	66	81.4	Self Colour	Metre	9
148026	20.60	26	26	78	96.2	Self Colour	Metre	6
148032	31.50	32	32	96	118	Self Colour	Metre	4



Metres per drum are subject to + or - 10% on actual metreage