



## PRODUCT DATA SHEET

# TECHNICAL INFORMATION

## LOCTITE BRAKE & PARTS CLEANER

### DESCRIPTION

LOCTITE Brake & Parts Cleaner is specifically formulated for removing oil, grease, brake fluids, oxidized oils (gum) and asphalt from all types of brakes and other automotive parts. It penetrates through dirt and corrosion and flushes them away, eliminating the need to disassemble. It leaves no residue, dries fast and is non-corrosive to metals.

### PRODUCT BENEFITS

Developed for brake professionals and mechanics.  
Aggressively penetrates and cleans  
Dries fast with no residue

### TYPICAL APPLICATIONS

All brake systems  
Drums  
Calipers  
Discs  
Shoes  
Pads  
Cylinders

### PHYSICAL AND CHEMICAL PROPERTIES UNCURED

Chemical Type:	Hydrocarbon Solvents
Appearance:	Clear liquid
Odor:	Mild Solvent
Flash Point:	-4°C

Henkel Australia Pty Limited  
ABN 82 001 302 996

P. O. Box 63  
Kilsyth Victoria 3137  
Australia

135-141 Canterbury Road  
Kilsyth Victoria 3137  
Australia

www.loctite.com.au  
Tel: (+61) 1300 885 556  
Fax: (+61) 03 9728 5877



## **APPLICATION INSTRUCTIONS:**

Provide adequate ventilation.  
Protect painted surfaces from over-spray  
Product can be used as a wipe down solvent or from a pressurized pump pack for the cleaning of oily surfaces.  
Teroson T900 bottle may be used as a pump pack bottle

## **PRECAUTIONS**

Refer to the Material Safety Data Sheet (MSDS) before handling the product.

## **STORAGE**

Store product in the unopened container in a dry location. Storage information may be indicated on the product container labeling.

**Optimal Storage: 8°C TO 21°C. Storage below 8°C or greater than 28°C can adversely affect product properties.**

Material removed from containers may be contaminated during use. Do not return product to the original container. If additional information is required, please contact your local Technical Service Center or Customer Service Representative.

## **DISCLAIMER**

Any information given is, to the best of our knowledge, the best currently available, with respect to our products and their use, but it is subject to revision as additional knowledge and experience is gained. Such information is offered as a guideline for experimentation only and is not to be construed as a representation that the material is suitable for any particular purpose or use. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use. This information is not a license to operate under nor is it intended to suggest infringement of any patent. We guarantee a uniform quality standard for this product. The only conditions and warranties accepted by Henkel in relation to this product or process are those implied by either Commonwealth or State statutes.

Henkel Australia Pty Limited  
ABN 82 001 302 996

P. O. Box 63  
Kilsyth Victoria 3137  
Australia

135-141 Canterbury Road  
Kilsyth Victoria 3137  
Australia

www.loctite.com.au  
Tel: (+61) 1300 885 556  
Fax: (+61) 03 9728 5877