

Take Off

General Purpose Cleaning Compound

APPLIED A4480

Description:	<p>Take Off is a heavy duty alkaline detergent that can be used anywhere in the food industry. Superior hard surface cleaner; e.g. plastics, aluminium, stainless steel, etc., cleaning just about anything e.g. oil, grease, dirt, dust, light carbon deposits, exhaust stains and more.</p> <p>Take Off contains surfactants, active solvent ingredients and foaming additives.</p>
Intended Use:	<p>Take Off is hard surface cleaner and also an excellent as a laundry pre wash stain remover for stains and greasy soils. It may be used as a spray or soak.</p>
Product features:	<p>No toxic residue or odour imparted to surfaces cleaned.</p> <p>Non Flammable.</p> <p>Safe on all hard surfaces.</p> <p>Will not harm good paint work.</p> <p>Spray and wipe - one action cleaning.</p> <p>Economical - Can be diluted to 1:40 with water.</p> <p>Excellent on animal fats.</p>
Typical Physical Properties:	<p><i>Technical data should be considered representative or typical only and should not be used for specification purposes.</i></p> <p>Appearance: Clear, blue liquid.</p>
Directions for Use:	<p><u>General Purpose Cleaning of Food Processing Areas</u></p> <p>Take Off can be used in either hot or cold water, however hot water will speed up the cleaning process.</p> <ul style="list-style-type: none"> • A concentration of 1:4 with water is most suitable for cleaning reactive metal surfaces, aluminium, zinc, cadmium, magnesium etc. • Apply by brush, swab or spray, leave for a short time, then rinse off or wipe off with a clean damp cloth. • For heavier soils, use a stronger solution and leave to work for several minutes before rinsing or wiping off. • For use as a foaming CIP cleaner, use at between 1:20 and 1:10. Foam on. Allow a 10 - 20 minute contact time and rinse off completely. Do not allow foam to dry on the surface. <p><u>Laundry Use</u></p> <p>Take Off is excellent as a de-greaser for heavily soiled articles or as a stain remover.</p> <ul style="list-style-type: none"> • Pre-spotting: spray directly onto stain. Allow contact time of between 2 and 15 minutes. Do not rinse. Wash as normal. • Pre-soak: prepare a 10% solution of Take Off in hot water. Immerse article and allow to soak between 10 minutes and 1 hour depending on level of soiling. Do not rinse. Wash as normal.
Storage:	<p>Store away from direct sunlight as the food grade dye may fade or turn pink. Product is still safe for use. Store at 1°C - 59°C.</p>
Compliances:	<p>AQIS - General Cleaner Type A: General cleaning compound for use in all areas, rinse product contacting surfaces with potable water after use. If used in accordance with label directions, the compound does not deleteriously affect food or food products.</p>
Precautions:	<p>Please refer to appropriate safety data sheet (SDS) prior to using this product.</p>



Technical Data Sheet

**For technical assistance, please call 1800-063-511
FOR INDUSTRIAL USE ONLY**

Warranty:	Applied will replace any material found to be defective. Because the storage, handling and application of this material is beyond our control, we can accept no liability for the results obtained.								
Disclaimer:	All information on this data sheet is based on laboratory testing and is not intended for design purposes. ITW Polymers & Fluids and Applied makes no representations or warranties of any kind concerning this data.								
Order Information:	<table><tr><td>A4480-15</td><td>Applied Take Off 15 L</td></tr><tr><td>A4480-25</td><td>Applied Take Off 25 L</td></tr><tr><td>A4480-200</td><td>Applied Take Off 200 L</td></tr><tr><td>A4480-1000</td><td>Applied Take Off 1000 L (IBC)</td></tr></table>	A4480-15	Applied Take Off 15 L	A4480-25	Applied Take Off 25 L	A4480-200	Applied Take Off 200 L	A4480-1000	Applied Take Off 1000 L (IBC)
A4480-15	Applied Take Off 15 L								
A4480-25	Applied Take Off 25 L								
A4480-200	Applied Take Off 200 L								
A4480-1000	Applied Take Off 1000 L (IBC)								

AUSTRALIA
ITW Polymers & Fluids
100 Hassall Street, Wetherill Park, NSW 2164
Phone: 1800 063 511
www.itwpf.com.au

NEW ZEALAND
ITW Polymers & Fluids
Unit 2 / 38 Trugood Drive, East Tamaki 2013, Auckland
Phone: 0800 476 265
www.itwpf.co.nz