**Technical Data** 

Performance you can trust

# **ROCOL Nickel Anti-Seize Compound**

#### Anti-seize compound for stainless steel

### Description

Rocol Nickel Anti-Seize Compound is formulated to prevent seizure of threaded components which are subjected to extremely high temperatures or adverse environmental conditions for long periods of time. Nickel Anti-Seize Compound contains lubricating solids to prevent galling and seizure during assembly or dismantling under heavy loads. Nickel Anti-Seize Compound has application on most surfaces subject to long term fretting and corrosion.

### Areas of application

- Stainless steel fasteners
- Industrial fasteners

### Features

- Excellent anti-seize properties due to high solids content (>35%)
- Excellent adhesion properties
- Protects against wet conditions and chemical attack
- Provides anti-seize properties up to 1400°C

ROCOL

- Does not contain sulphur or copper
- Aids assembly and dismantling under heavy loads
- NZ MAF Approved C14 (fish, game, meat)

## **Directions for use**

Apply with the brush supplied a thin film to the surface. For best results all surfaces should be clean and dry.

## **Technical data**

Appearance	Smooth brushable silver/grey paste
Carrier	.Bentonite thickened mineral oil
Temperature Range	Up to 1400°C
Anti-Seize Solids	Nickel and mica
Solids content	> 35%
Consistency	NLGI 0-1

## Health & safety information

The product is hazardous. A Material Safety Datasheet is available from the Rocol Customer Services Department upon request.

The information enclosed in this Technical Bulletin is as up to date and correct as possible as at the time of issue. The data provided in this Technical Bulletin should be used as a guide only, as the performance of the product will vary depending on differing operating conditions and application methods.

The sale of any product described in this Technical Bulletin will be in accordance with ITW Polymers & Fluids Pty Ltd Conditions of Sale, a copy of which is available on request. To the extent permitted by law, ITW Polymers & Fluids Pty Ltd excludes all other warranties in relation to this product.