

ROCOL Dry Film Teflon® Spray

Teflon® dry film spray



Description

Rocol Dry Film Teflon® Spray deposits a dry film of teflon to metallic and non-metallic surfaces.

The white non-toxic odourless film provides a lubricating medium with very low frictional properties and is unaffected by water, steam and most chemicals.

Rocol Dry Film Teflon® Spray can be used as a dry film lubricant on a wide variety of applications in food environments or clean industries where contamination must be avoided or dark coloured lubricants are undesirable.

Rocol Dry Film Teflon® Spray is suitable for use as a mold release for DEVCON® epoxy and polyurethane products.

Areas of application

- Food processing machinery
- Packaging machinery
- Freezers
- Paper machinery
- Bakeries
- Bottling plants
- Sealing jaws on packaging equipment

Features

- Non-toxic and non-staining
- Resistant to water, steam, oil and most chemicals
- Excellent anti-static properties
- Unaffected by extreme cold temperatures
- Suitable for temperatures up to 250°C
- Contains no oil or silicone
- Increases component life
- NZFSA Approved C11 (All animal product except dairy)
- AsureQuality NZ approved for Dairy Industry, Food Areas (incidental contact)
- HACCP Australia Pty Ltd endorsed as a food grade lubricant suitable for use in facilities that operate a HACCP based food safety program (PE-626-ITW-1F2-01)
- NOT suitable for direct food contact surfaces.

AUSTRALIA

ITW Polymers & Fluids
100 Hassall Street
Wetherill Park NSW 2164
Phone (02) 9757 8800 Fax (02) 9757 3855

NEW ZEALAND

ITW Polymers & Fluids
Unit 2 / 38 Trugood Drive
East Tamaki 2013, Auckland
Phone (09) 272 1945 Fax (09) 273 6489

Technical data

Appearance (concentrate) Transparent / milky white film

Temperature Range:

Operating-200°C to 250°C

Storage-10°C to 50°C

PropellantHydrocarbon

Directions for use

- Shake well before use and hold can upright when spraying.
- Wash hands before smoking or handling tobacco products.
- After use, clear spray head by inverting can and depressing button for 2 to 3 seconds until jet is cleared.
- Test compatibility with painted and coated surfaces, plastics and rubbers, prior to application.
- Use only as directed.
- Use minimum quantity necessary to achieve desired technical effect.
- NOT suitable for direct food contact surfaces

Health & safety information

The product contains flammable gas. Keep away from sources of ignition. Do not breathe in spray. Use only in well ventilated areas. A Material Safety Datasheet is available from the Rocol Customer Services Department upon request. KEEP OUT OF REACH OF CHILDREN. This product is non-hazardous.

Disclaimer

The information enclosed in this Technical Bulletin is as up to date and correct as possible as at the time of issue. The data provided in this Technical Bulletin should be used as a guide only, as the performance of the product will vary depending on differing operating conditions and application methods.

The sale of any product described in this Technical Bulletin will be in accordance with ITW Polymers & Fluids Pty Ltd Conditions of Sale, a copy of which is available on request. To the extent permitted by law, ITW Polymers & Fluids Pty Ltd excludes all other warranties in relation to this product.

AUSTRALIA

ITW Polymers & Fluids
100 Hassall Street
Wetherill Park NSW 2164
Phone (02) 9757 8800 Fax (02) 9757 3855

NEW ZEALAND

ITW Polymers & Fluids
Unit 2 / 38 Trugood Drive
East Tamaki 2013, Auckland
Phone (09) 272 1945 Fax (09) 273 6489