

ROCOL Open Gear Spray

Open gear lubricant spray

Description

Rocol Open Gear Spray is designed for the lubrication and corrosion protection of all types of open gears. The flexible film contains molybdenum disulphide and provides exceptional load carrying and wear resistance by minimising the retention of dirt or abrasive particles.

Areas of application

- Worm gears
- Open gears
- Crown wheels
- Rack and pinions
- Lead screws

Features

- Outstanding anti-wear properties
- Thin tenacious film does not drip or throw off
- Can be applied while machine is running
- Reduces noise and chatter
- Easily applied through guards and inspection holes
- Water resistant
- NZ MAF Approved C12 (fish, game, meat)

Directions for use

Shake well before use. Hold can upright and spray from a distance of 15 to 30 cm. Use only as directed.

Technical data

Appearance	Black Grease
Lubricating Solids	Molybdenum Disulphide
Operating Temperature Range	-10°C to +150°C
Storage Temperature.....	-10°C to 50°C
Propellant.....	Dimethyl Ether (DME)

Health & safety information

The product contains flammable gas. Keep away from sources of ignition. Do not breathe in spray. Use only in well ventilated areas. A Material Safety Datasheet is available from the Rocol Customer Services Department upon request. KEEP OUT OF REACH OF CHILDREN. This product is non-hazardous.

The information enclosed in this Technical Bulletin is as up to date and correct as possible as at the time of issue. The data provided in this Technical Bulletin should be used as a guide only, as the performance of the product will vary depending on differing operating conditions and application methods.

The sale of any product described in this Technical Bulletin will be in accordance with ITW Polymers & Fluids Pty Ltd Conditions of Sale, a copy of which is available on request. To the extent permitted by law, ITW Polymers & Fluids Pty Ltd excludes all other warranties in relation to this product.