

TECHNICAL DATA

PUMPABLE GUIDE ROPE GREASE

Ropeguard 65/65WM

Description

Pumpable Guide Rope Grease is a tacky heat and water resistant lithium based grease containing lubricating solids including graphite. Based on an oil of high viscosity and formulated to NGLI No.1 consistency, **Pumpable Guide Rope Grease** provides a durable grease film which effectively seals the rope from water and contaminants.

Areas of application

- Guide ropes in mine winder shafts

Features

- Durable, tough and adhesive grease film
- Excellent corrosion resistance
- High load carrying capabilities
- Suitable for automatic greasing systems

Technical Data

	Test Method
Appearance.....	Greyish black grease
Lubricating Solids.....	Graphite
Thickener.....	Lithium
NLGI Classification.....	0 - 1
Worked Penetration (mm X 10 ⁻¹)	340 – 380
Base Fluid Type	Mineral Oil
Base Oil Viscosity at 40°C (cst)	2000
Drop Point (°C).....	150
Temperature Range (Continuous)	-10°C to 150° C
	ASTM D217 (IP50)
	ASTM D445
	ASTM D-566 (IP132)

The information contained in this Technical Bulletin is as up to date and correct as possible as at the time of issue. The data provided should be used as a guide only as the performance of the product will vary depending on differing operating conditions and application methods.

The sale of any product described in this Technical Bulletin will be in accordance with ITW Polymers & Fluids Conditions Of Sale, a copy of which is available on request. To the extent permitted by law, ITW Polymers & Fluids excludes all other warranties in relation to this product.

Directions for use

The product is formulated to enable easy application by automatic lubricator. It can also be applied by brush or paddle. It can be applied over coatings of conventional greases without the need for cleaning.

Storage and Shelf Life

Store in dry conditions between 0°C and 50°C, away from sources of heat and naked flames. When stored in original sealed containers, the minimum shelf life is four (4) years.

Packaging

Pumpable Guide Rope Grease is available in 20 kg drums.

Ordering Information:

20 kg Drum

#RF204287

Health & Safety Information

The product is non-hazardous. A Material Safety Data Sheet is available from the ITW Polymers & Fluids Technical Department upon request or available on our website www.molybond.com.au.

AUSTRALIA

ITW Polymers & Fluids
100 Hassall Street
Wetherill Park NSW 2164
Phone (02) 9757 8800 Fax (02) 9757 3855

NEW ZEALAND

ITW Polymers & Fluids
18-26 Amelia Earhart Avenue
Airport Oaks, Mangere, Auckland
Phone (09) 256 2122 Fax (09) 256 2124