Technical Data



Performance you can trust

ROCOL Moistureguard Spray

Indoor corrosion preventative

Description

Rocol Moistureguard Spray displaces moisture and provides an ultra thin film which remains soft and gives complete corrosion protection in conditions of high humidity. Moistureguard Spray does not interfere with the assembly of precision or interference fit parts, or with gauging and measurement during inspection, so that removal is not normally necessary. The thin semi-dry film contains a blue dye for easy identification and can be removed by normal petroleum solvents such as white spirit, mineral turps or normal degreasing solvents.

Areas of application

- Steel stock
- Machined components
- Moulding dies

- Press tools
- Hand tools
- Machine tools

Features

- Provides corrosion protection indoor for up to 6 months
- Excellent penetration and dewatering properties
- Thin film does not interfere with precision assemblies
- NZFSA Approved C22 (All animal product except dairy)

Directions for use

Apply by brushing, dipping or spraying component so that upon evaporation of the solvent carrier a thin film remains.

Technical data

Appearance	Green waxy coating
Solvent	White Spirit
Drying Time	4 hours
Solvent (for removal / clean up)	White Spirits or Mineral turps
Propellant	Hydrocarbon

Health & safety information

The product contains flammable gas. Keep away from sources of ignition. Do not breathe in spray. Use only in well ventilated areas. A Material Safety Datasheet is available from the Rocol Customer Services Department upon request. KEEP OUT OF REACH OF CHILDREN. This product is hazardous.

The information enclosed in this Technical Bulletin is as up to date and correct as possible as at the time of issue. The data provided in this Technical Bulletin should be used as a guide only, as the performance of the product will vary depending on differing operating conditions and application methods.

The sale of any product described in this Technical Bulletin will be in accordance with ITW Polymers & Fluids Pty Ltd Conditions of Sale, a copy of which is available on request. To the extent permitted by law, ITW Polymers & Fluids Pty Ltd excludes all other warranties in relation to this product.

Date last modified October 2012 T0140