



## ROCOL Rustshield Spray

### Outdoor corrosion preventative spray

#### Description

Rocol Rustshield Spray displaces water and provides a touch-dry durable film which protects against the most severe corrosive conditions. It is effective in conditions of high humidity, salt, chemical or other corrosive atmospheres. The thin film will not affect assembly on most engineering operations but can be removed if required by using common degreasing solvents.

#### Areas of application

- Steel stock
- Machined components
- Moulding dies
- Press tools
- Hand tools
- Machine tools

#### Features

- Corrosion protection - up to 6 months outdoors
- Good dewatering properties
- Provides distinctive coloured film
- Reduces maintenance costs
- Film can be easily removed with common solvents

#### Directions for use

Shake the can. Hold upright when spraying. Apply from 25 to 30 cm distance. Allow 25 minutes drying before handling. After use invert can and spray to clear nozzle. Test compatibility with painted or coated surfaces, plastics and rubbers, prior to application.

#### Technical data

Appearance ..... Brown film  
Temperature Range  
    Operating ..... -10°C to 120°C  
    Storage ..... -10°C to 50°C  
Propellant..... Carbon Dioxide (CO<sub>2</sub>)

#### Health & safety information

The product contains flammable gas. Keep away from sources of ignition. Do not breathe in spray. Use only in well ventilated areas. A Material Safety Datasheet is available from the Rocol Customer Services Department upon request. KEEP OUT OF REACH OF CHILDREN. This product is non-hazardous.

The information enclosed in this Technical Bulletin is as up to date and correct as possible as at the time of issue. The data provided in this Technical Bulletin should be used as a guide only, as the performance of the product will vary depending on differing operating conditions and application methods.

The sale of any product described in this Technical Bulletin will be in accordance with ITW Polymers & Fluids Pty Ltd Conditions of Sale, a copy of which is available on request. To the extent permitted by law, ITW Polymers & Fluids Pty Ltd excludes all other warranties in relation to this product.

