Technical Data



Performance you can trust

Rocol Easyline Ultimate Paint

Permanent linemarking system - General Marking

Description

Rocol Easyline Paint is formulated with a high concentration of pigment and resins to provide a high opacity, durable, semi-gloss finish. Rocol Easyline Aerosol Paint is used in conjunction with a 4 wheel applicator for linemaking in both interior and exterior applications

Areas of application

- Carparks
- Playgrounds

- Factories
- Warehouses

Features

- Durable traffic grade paint
- Touch dry in 10 minutes
- High opacity linemarking paint

- Reusable applicator system for 50 and 75mm lines
- Available in White, Yellow, Red, Green, Blue, Orange, Black & Grey

Directions for use

Surfaces should be clean, dry, dust and grease free.

- 1. Shake can vigorously. When agitator balls rattle shake for a further minute.
- 2. Hold can upright, away from face and fit actuator.
- 3. Invert can and fit into Rocol Easyline Applicator.
- 4. Pull lever to activate aerosol.

Technical data

Appearance	.White, Yellow, Red, Green, Blue, Orange, Black, Grey
Coverage	.Approximately 75 - 110 m of 50 mm wide line
Drying Time	.Touch dry in 10 minutes, light traffic in 40 minutes
Storage	. Always store on its side in a cool place.

Health & safety information

The product contains flammable gas. Keep away from sources of ignition. Do not breathe in spray. Use only in well ventilated areas. A Material Safety Datasheet is available from the Rocol Customer Services Department upon request. KEEP OUT OF REACH OF CHILDREN. This product is non-hazardous.

The information enclosed in this Technical Bulletin is as up to date and correct as possible as at the time of issue. The data provided in this Technical Bulletin should be used as a guide only, as the performance of the product will vary depending on differing operating conditions and application methods.

The sale of any product described in this Technical Bulletin will be in accordance with ITW Polymers & Fluids Pty Ltd Conditions of Sale, a copy of which is available on request. To the extent permitted by law, ITW Polymers & Fluids Pty Ltd excludes all other warranties in relation to this product.

Date last modified January 2011 T0301