

## **240V Mini Diesel Bowsers**



The Macnaught range of 240V Diesel Mini Bowsers offer the operator new options when looking for robust construction that deliver consistently higher flow rates. these compact units come as complete packages that allow delivery rates up to 100 L/min. Equipped with easy to use, accurate mechanical register that can be calibrated on-site, these units also offer smart on/off switches integrated into the nozzle holder. Extremely versatile, the bowsers can be installed directly to the wall or any suitable structure.

Resettable fill totaliser 4-digit resettable

Non-resettable accumulative totaliser

8-digit accumulative total

Hose hanger

Allows for neat hose storage



## Why choose this product?

Complete diesel dispensing unit, ideal for high use applications. The built in meter provides accurate recording of fuel usage, with the use of a micro switch the pump will switch off when nozzle is replaced into holder.



Automatic nozzle with delivery hose

**Built-in on/off switch** Pump protection from overheating

Long fuel hose Long hose provides access to hard to reach fuel fill points

## Service Parts for AMB100L

- AHFP100LPM-1K: Wet Seal Kit
- AHFP100LPM-2K: Poppet Valve Kit
- AHF100LPM-CAP: Capacitor
- AHF-SWITCH: On/Off Switch

## Service Parts for AMB60L

- AHFP70LPM-1K: Wet Seal Kit
- AHFP70LPM-2K: Poppet Valve Kit
- AHF70LPM-CAP: Capacitor
- AHF-SWITCH: On/Off Switch

| Part Number           | AMB100L                        | AMB100L-6M                             | AMB60L                        |
|-----------------------|--------------------------------|--|-------------------------------|
| Description           | 240V Diesel Mini Bowser - 100L | 240V Diesel Mini Bowser - 100L 6m hose | 240V Diesel Mini Bowser - 60L |
| Flow range            | 100L/min (26gal/min)           | 100LPM (26gal/min)                     | 60L/min (16gal/min)           |
| Volt                  | 240V                           | 240V                                   | 240V                          |
| Inlet/ Outlet         | 1" BSP (F)                     | 1" BSP (F)                             | 1" BSP (F)                    |
| Nozzle                | Automatic                      | Automatic                              | Automatic                     |
| Hose length           | 4 metres                       | 6 metres                               | 4 metres                      |
| Duty Cycle            | 30 Min                         | 30 Min                                 | 30 Min                        |
| Suction hose          | 25mm (1") x 2m (6.5ft)         | 25mm (1") x 2m (6.5ft)                 | 25mm (1") x 2m (6.5ft)        |
| Delivery hose         | 25mm (1") x 4m (13ft)          | 25mm (1") x 6m (19.6ft)                | 25mm (1") x 4m (13ft)         |
| Suitable fluids       | *Suitable for diesel use only  | *Suitable for diesel use only          | *Suitable for diesel use only |
| Warranty <sup>1</sup> | 5 Years                        | 5 Years                                | 5 Years                       |

Note<sup>1</sup>: Subject to Macnaught warranty terms and conditions, see www.macnaught.com.au/warranty.



Macnaught Pty Ltd 41-49 Henderson St, Turella NSW 2205 Australia

Ph: +61 2 9567 0401 Fax: +61 2 9597 7773 Email: info@macnaught.com Website: macanught.com

\*For Macnaught warranty, terms and conditions see macnaught.com/warranty ©Macnaught Pty Ltd, 2017.

