

# CHAIN LUBE



**MOREY'S CHAIN LUBE** is formulated to give maximum protection. Micro penetration, high water resistance, and excellent adhesion ensure constant lubrication on high speed operations. Excellent anti-wear and cleaning properties. Reduces friction – will not fling – compatible with all O-rings. Ideal for chains and bar lubricant. Designed for bicycle chains, chainsaw bar and chains, industrial chains, motorcycle chains, wire rope, boat chains and winch ropes.

## Typical Uses:

- Used as a non-drip chain and sprocket lubricant.
- Used as an inexpensive bar lubricant for chain saws.

## Features:

- Economical once-through lubrication.
- Tackiness agent reduces oil consumption and “fling-off”.
- Protects sliding surfaces and chains against wear.

## Typical Properties

Gravity, @°API	24.6
Flash Point, °C	221
Fire Point, °C	243
Pour Point, °C	-23
Viscosity:	
SUS @ 100°F	238
SUS @ 210°F	47.7
cSt @ 40°C	46
cSt @ 100°C	6.4

Values shown here are typical and may vary.

MOREY OIL SOUTH PACIFIC LTD  
ISO 9001-14001 CERTIFIED SUPPLIER  
[www.moreyoil.co.nz](http://www.moreyoil.co.nz)

01/08/2010