

## **LUBEMATE EK-SERIES ENCLOSED HOSE REELS**



The Lubemate EK-Series Enclosed Hose Reels represent a clean, aesthetically neat full size hose containment solution for even the largest workshop applications. The reels are constructed of sturdy powder coated steel with stamped form for strength and fully enclosed spring and swivels for protection. Longevity is assured by equally robust multiple placement mounting brackets. The narrow form of the EK-Series Enclosed Hose Reels from Lubemate offers a reliable & cost-effective solution for your service bay fluid handling.

High capacity enclosure Long hose lengths


**Powder-coated steel construction**For longevity and corrosion protection



**High quality hose and fittings** Exceeds required standards

**Long lasting spring** Fully enclosed and lubricated

## **APPLICATIONS**



Part Number	L-EKAW1015	L-EKAW1215	L-EK01215	L-EKG0615	L-EKG1015
Description	Air/Water Hose Reel 3/8" x 15m	Air/Water Hose Reel 1/2" x 15m	Oil Hose Reel 1/2" x 15m	Grease Hose Reel 1/4" x 15m	Grease Hose Reel 3/8" x 15m
Application	Air/Water	Air/Water	Oil	Grease	Grease
Hose Size (ID)	3/8"	1/2"	1/2"	1/4"	3/8"
Hose Length	15m	15m	15m	15m	15m
Hose Material	NBR Rubber	NBR Rubber	S.A.E 100R1 Wire Braid	S.A.E 100R2 Wire Braid	S.A.E 100R2 Wire Braid
Working Pressure	300 psi	300 psi	2320 psi	5800 psi	4785 psi
Max Temperature	80° C	80° C	100° C	100° C	100° C
Reel Inlet	3/8" BSP	1/2" BSP	1/2" BSP	1/4" BSP	3/8" BSP
Hose Inlet	3/8" BSP	1/2" BSP	1/2" BSP	1/4" BSP	3/8" BSP



Lubemate® is a practical, cost-effective range of equipment brought to you by the trusted team at Macnaught®. All Lubemate products are specially selected by our experienced technical team at Macnaught, ensuring they meet our strict quality standards. Macnaught Pty Ltd 41-49 Henderson St, Turrella NSW 2205. Australia Ph: 1800 185 102 Fax: +61 2 9597 7773 Email: info@macnaught.com.au Website: macnaught.com