

12V & 24V ELECTRIC DIESEL PUMP (40LPM)



The 12V & 24V premium quality diesel transfer pump have been designed and tested for optimum performance and reliability in the harsh Australian environment. They are a perfect economical alternative to using manual pumps. The pumps have a flowrate of 40 l/min (free flow) with a 30-minute duty cycle. The Macnaught range of electric diesel pumps are ideal for quick reliable transfer of Diesel and Kerosene from bulk fuel tanks, service trucks, utes, 205ltr drums and IBC (intermediate bulk containers).

Portable 40L/min Diesel

Pump -Available in 12V or 24V model

Trouble free operation

Self-Priming vane pump fitted with a built-in bypass valve.

AFP12-40LP



3/4"BSP Inlet/Outlet ports

Portable design

Provides versatility for easy change-over of various type fuel containers.



PART NUMBER	AFP12-40LP	AFP24-40LP
Description	12V ELECTRIC DIESEL PUMP 40LPM	24V ELECTRIC DIESEL PUMP 40LPM
Flow range	40L/min (11 gal/min)	40L/min (11 gal/min)
Volt	12V	24V
Inlet/Outlet	3/4" BSP (F)	3/4" BSP (F)
Duty Cycle	30min	30min
Power Cable	4m power cable & alligator clips	
Wetted Materials	Cast Iron, Sintered Steel, Acetal, NBR rubber	
Suitable fluids	Suitable for Diesel	



Macnaught Pty Ltd 41-49 Henderson St, Turrella NSW 2205. Australia Ph: +61 2 9567 0401 Fax: +61 2 9597 7773 Email: info@macna

Email: info@macnaught.com Website: macnaught.com

*For Macnaught warranty, terms and conditions see macnaught.com/warranty @Macnaught Pty Ltd, 2021