

SY Chain No.	Lacing	Dimensions - mm						Average	Maximum	Average
		Pitch Pin		7.7			Hole	Ultimate	Allowable	Weight
		P	Dia.	Length L	Height H	Thickness T	Dia S	Strength kN	Load kN	kg/m
BL422	2×2	12.70	5.08	10.5	11.7	2.0	5.15	27.5	4.51	0.6
BL423	2×3	12.70	5.00	12.5	1117	2.0	3.13	27.5	4.51	0.7
BL434	3×4	271		16.8			71	40.7	5.30	1.0
BL444	4×4			19.0				54.4	5.98	1.2
BL446	4×6			23.0				54.4	5.98	1.5
BL466	6×6			27.5				82.5	9.81	1.8
BL522	2×2	15.875	5.95	12.4	14.6	2.4	6.04	42.7	6.86	1.0
BL523	2×3	15.073	3.22	15.0	1.4.0	2.4	0.04	42.7	6.86	1.1
BL534	3×4			20.0			(4 T H	64.0	8.33	1.6
BL544	4×4			22.2				85.3	9.41	1.8
BL546	4×6			27.6				85.3	9.41	2.2
BL566	6×6			32.4			221	127	15.7	2.6
BL622	2×2	19.05	7.93	16.6	17.5	3.2	8.00	70.6	9.81	1.5
BL623	2×3	19.05	7.93	19.5	17.5	3.2	8.00	70.6	9.81	1.8
BL634	3×4			26.2				106	12.3	2.6
BL644	4×4			29.2				141	13.7	3.0
BL646	4×6			36.5			10 11	141	13.7	4.1
BL666	6×6			43.0			100	212	24.5	4.5
BL822	2×2	25.40	9.53	19.6	24.1	4.0	9.59	114	17.0	2.5
BL823	2×3	23.10	2,53	23.8	. 2.1.1	3.0	3,32	114	17.0	3.1
BL834	3×4			32.5				172	20.6	4.3
BL844	4×4			36.2				228	23.5	4.9
BL846	4×6			45.0				228	23.5	6.2
BL866	6×6			53.5				342	40.2	7.4
BL1022	2×2	31.75	11.10	24.0	29.3	4.8	11.20	157	26.0	3.7
BL1023	2×3	313	200.00	28.6	142.0	3,0	13,22	157	26.0	4.6
BL1034	3×4			38.7			11	245	31.4	6.5
BL1044	4×4			43.7				314	36.3	7.4
BL1046	4×6			53.4				314	36.3	9.2
BL1066	6×6			63.4				471	58.8	11.0
BL1222	2×2	38.10	12.70	27.8	35.1	5.6	12.82	207	36.8	4.7
BL1223	2×3		260.0	34.2	22.1	3.7	19.00	207	36.8	6.4
BL1234	3×4			45.5				332	44.1	9.0
BL1244	4×4			51.2				414	50.5	10.2
BL1246	4×6			62.6				414	50.5	11.8
BL1266	6×6			73.6		-		621	73.1	14.4
BL1422	2×2	44.45	14.28	31.8	40.9	6.4	14.39	270	49.0	7.8
BL1423	2×3	33.05	3.000	38.8	42776	1.00	13/05	270	49.0	8.9
BL1434	3×4			51.7			411	405	58.8	11.6
BL1444	4×4			58.4				539	67.7	12.8
BL1446	4×6			71.2				539	67.7	17.8
BL1466	6×6			84.8				810	95.1	22.3
BL1622	2×2	50.80	17.45	35.8	46.7	7.2	17.62	392	58.8	9.7
BL1623	2×3		344-3	43.7		1.0		392	58.8	12.0
BL1634	3×4			58.9				618	70.6	16.8
BL1644	4×4			65.9			, 7 1 III	785	80.4	18.8
BL1646	4×6			80.2			[785	80.4	23.9
BL1666	6×6			96.2				1176	137.3	28.5