



MSA Pro-Lift 3000 Lifting Magnet

P/N: PL3000




SPECIFICATIONS

Max Break away	9000 kg
Safe Working Load	3000 kg
Full Saturation Thickness	80 mm
Max Safe Shear	NA
Minimum Thickness for De-Stack	80 mm
Net Weight	160 kg
Height - Less Shackle	215 mm
Magnet Footprint (L x B)	232 mm x 442 mm
Handle Length - R	450 mm



MSA Pro-Lift 3000kg Safe Working Load



Fitted Safety Latch Included.

Complies with Lifting Devices
 Standard AS 4991-2004. Section 6.2.1
 Load Control.

Material Thickness	SWL at 3:1 IN KG
80 mm	3000 kg
70 mm	2400 kg
60 mm	1800 kg
50 mm	1350 kg
40 mm	1050 kg
30 mm	750 kg

It is incumbent upon your company to:

- Undertake a risk assessment to identify the hazards prevalent at your workplace which could impact upon the safe operation of the equipment and take action to control those hazards.
- Review the Safety Operating Procedure (SOP) to ensure it captures all the steps involved in your specific use(s) of the equipment and modify accordingly.
- Ensure that staff operating the equipment have been adequately trained in its safe use, provided with the appropriate Personal Protective Equipment (PPE) identified in the SOP and provided with a copy of the Safety Operating Procedure.

Your company also agrees to undertake a risk assessment, review the SOP in light of that risk assessment, make any modifications to reflect how the equipment is to be used at their workplace and then adequately train those people who are going to use the equipment.