

FLAT WEB SLING

SPECIFICATION FOR 2 TONNE - GREEN

**AS
1353.1**



Flat Web Sling - Polyester

Every Austlift flat webbing sling is fabricated using 100% high tenacity polyester yarn. Durable and specially woven, 100% polyester with standard folded eyes that incorporates eye wear padding to provide maximum protection around the eyes.

Each sling is proof tested, individually serial numbered, tagged and complete with test certificates.

Manufactured to the specifications of Austlift and according to Australian Standard AS1353.1.

WLL 2000KG

Note: Other variations available upon request.

GREEN		WIDTH: 60mm
CODE	LENGTH (M)	Wt. (kg)
910205	0.5	0.3
910210	1.0	0.62
910215	1.5	0.84
910220	2.0	1.06
910225	2.5	1.25
910230	3.0	1.4
910235	3.5	1.62
910240	4.0	1.86
910245	4.5	2.3
910250	5.0	2.16
910255	5.5	2.38
910260	6.0	2.6
910270	7.0	3.05
910280	8.0	3
910290	9.0	3.8
910291	10.0	4.2

Application

- Building construction sites
- Ship building yards
- Factory production workshops
- Mine production sites
- Engineering workshops

Features

- Each sling is proof tested 2 x WLL.
- Individually serial numbered.
- Supplied with individual test certificate.
- Break Load Limit is 8 x the load indicated
- 2 Ply webbing



WORKING LOAD LIMITS CHART (KG) - (WLLs)								
FLAT WEBBING SLING								
	VERTICAL	CHOKE	BASKET	60°	90°	120°	60°	60° CHOKE
GREEN	2000	1600	4000	3400	2800	2000	3400	2800

NSW Head Office

43 Frank Street
 Wetherill Park, NSW 2164
 02 9757 2277

WA Office

42 Mulgool Road
 Malaga, WA 6090
 08 9248 6674

QLD Office

7 Durbell Street
 Acacia Ridge, QLD 4110
 07 3272 0777

VIC Office

47 Technology Drive
 Sunshine West, VIC 3020
 03 9314 5525