

FLAT WEB SLING

SPECIFICATION FOR 4 TONNE - GREY

**AS
1353.1**



Flat Web Sling - Polyester

Every Austlift flat webbing sling is fabricated using 100% high tenacity polyester yarn. Durable and specially woven, 100% polyester with standard folded eyes that incorporates eye wear padding to provide maximum protection around the eyes.

Each sling is proof tested, individually serial numbered, tagged and complete with test certificates.

Manufactured to the specifications of Austlift and according to Australian Standard AS1353.1.

Note: Other variations available upon request.

Application

- Building construction sites
- Ship building yards
- Factory production workshops
- Mine production sites
- Engineering workshops

Features

- Each sling is proof tested 2 x WLL.
- Individually serial numbered.
- Supplied with individual test certificate.
- Break Load Limit is 8 x the load indicated
- 2 Ply webbing



WLL 4000KG

GREY WIDTH: 120mm		
CODE	LENGTH (M)	Wt. (kg)
910410	1.0	1.35
910415	1.5	2.02
910420	2.0	2.7
910425	2.5	3.37
910430	3.0	3.49
910435	3.5	3.6
910440	4.0	3.58
910450	5.0	4.58
910460	6.0	5.5
910470	7.0	6.41
910480	8.0	6.1
910491	10.0	9.1

WORKING LOAD LIMITS CHART (KG) - (WLLs)

FLAT WEBBING SLING								
	VERTICAL	CHOKE	BASKET	60°	90°	120°	60°	60° CHOKE
GREY	4000	3200	8000	6800	5600	4000	6800	5600

NSW Head Office

🏠 43 Frank Street
 Wetherill Park, NSW 2164
 ☎ 02 9757 2277

WA Office

🏠 42 Mulgool Road
 Malaga, WA 6090
 ☎ 08 9248 6674

QLD Office

🏠 7 Durbell Street
 Acacia Ridge, QLD 4110
 ☎ 07 3272 0777

VIC Office

🏠 47 Technology Drive
 Sunshine West, VIC 3020
 ☎ 03 9314 5525