

# FLAT WEB SLING

## SPECIFICATION FOR 5 TONNE - RED

**AS  
1353.1**



### Flat Web Sling - Polyester

Every Austlift flat webbing sling is fabricated using 100% high tenacity polyester yarn. Durable and specially woven, 100% polyester with standard folded eyes that incorporates eye wear padding to provide maximum protection around the eyes.

Each sling is proof tested, individually serial numbered, tagged and complete with test certificates.

Manufactured to the specifications of Austlift and according to Australian Standard AS1353.1.

Note: Other variations available upon request.

### Application

- Building construction sites
- Ship building yards
- Factory production workshops
- Mine production sites
- Engineering workshops

### Features

- Each sling is proof tested 2 x WLL.
- Individually serial numbered.
- Supplied with individual test certificate.
- Break Load Limit is 8 x the load indicated
- 2 Ply webbing

**WLL 5000KG**

RED WIDTH: 150mm		
CODE	LENGTH (M)	Wt. (kg)
910515	1.5	1.74
910520	2.0	2.3
910530	3.0	3.5
910540	4.0	4.5
910550	5.0	6
910560	6.0	19
910570	7.0	22.1
910580	8.0	25.3
910590	9.0	28.49
910591	10.0	31.6



WORKING LOAD LIMITS CHART (KG) - (WLLs)								
FLAT WEBBING SLING								
	VERTICAL	CHOKE	BASKET	60°	90°	120°	60°	60° CHOKE
RED	5000	4000	10000	8500	7000	5000	8500	7000

**NSW Head Office**

43 Frank Street  
 Wetherill Park, NSW 2164  
 02 9757 2277

**WA Office**

42 Mulgool Road  
 Malaga, WA 6090  
 08 9248 6674

**QLD Office**

7 Durbell Street  
 Acacia Ridge, QLD 4110  
 07 3272 0777

**VIC Office**

47 Technology Drive  
 Sunshine West, VIC 3020  
 03 9314 5525