# **DID YOU KNOW?**

about our...



# NEW PRODUCT


# Lifting Eye Bolt DIN 580

## LIFTING EYE BOLT 316 STAINLESS / DIN 580 / GRADE A4

Part	QFind	Size	Length	Height	Inside Eye	Working Load	Pack Qty
			L (mm)	H (mm)	ID (mm)	WLL (kg)	
ULEB16PD5M06	EB16M6	M6	13.0	36	20	75	50
ULEB16PD5M08	EB16M8	M8	13.0	36	20	140	50
ULEB16PD5M10	EB16M10	M10	17.0	45	25	230	25
ULEB16PD5M12	EB16M12	M12	20.5	53	30	340	10
ULEB16PD5M16	EB16M16	M16	27.0	62	35	700	10
ULEB16PD5M20	EB16M20	M20	30.0	71	40	1200	5
ULEB16PD5M24	EB16M24	M24	36.0	90	50	1800	2
ULEB16PD5M30	EB16M30	M30	45.0	109	60	3200	2

#### **FEATURES**

- Eye bolt approved and certified for lifting.
- Can be used in axial or angular loading.



## **APPLICATIONS**

- · Connection point for anchoring, rigging, pulling, lifting or hoisting.
- Can be used with ropes, cables, shackles and hooks.
- Threaded into steel equipment, machine and structures.
- Bolt through steel or timber profiles.



## **MARKINGS:**





Disclaimer: While every reasonable effort has been made to ensure that this document is correct at the time of printing, Hobson Engineering®, its agencies and employees, disclaim any and all liability to any person in respect of anything or the consequences of anything done or omitted to be done in reliance upon the whole or any part of this document.

