

FROGLINK

Surface Mounted Anchor



SafetyLink's patented surface mounted FrogLink has set a new benchmark in the field of height safety. This revolutionary all in one unit has been designed to attach to all metal roof profiles with a single row of attachment holes.

- Fast simple unit for installation, fall protection whilst working at heights.
- Low profile reflective design is a plus for any commercial or residential enterprise wanting to maintain an aesthetically pleasing façade.
- Can be fixed to corrugated sheet metal, trimdek, kliplok and a multitude of other metal roof sheeting materials, can be used for domestic or commercial use.
- Dynamic design reduces the load back onto the structure and person attached to the anchor.
- Designed to suit all roof profiles with a single row of attachment holes.
- Install using 7 x 8mm Tri-fold Rivets (Drill Size 7.8-8.2mm, 27.7mm length, 1.0-9.5mm grip range, Aluminium).

WHAT AM I USED FOR?

A surface mounted height safety anchor point for use on metal roof profiles where access to timber is difficult, will arrest from any direction.

STANDARDS

Complies with AS/NZS 1891.4, AS/NZS 5532-2013, EN 795:2012, OSHA 1926.502 and (Plywood – ANSI Z359_18:2017).



Product Code	Description	Weight (kg)	Rated	Material
915160	Surface Mounted Anchor	0.291	15kN	316 Stainless Steel

All products must be installed in accordance with SafetyLink's installation handbook, using only products supplied by SafetyLink Pty Ltd.



© 2018, SafetyLink Pty Ltd, Australia.

Patents: SafetyLink Pty Ltd has a multitude of patents, patents pending, design applications, trademarks and copyrighted documents both lodged and issued. Should you wish to know the progress of our intellectual property on a specific product please email us on ip@safetylink.com and quote the product code.

Doc ID: MKT-64 Version: 18.0

DATA SHEET



FS 707792