



PRODUCT INFORMATION

NOVEMBER 2018



RF40

Spring Operated Single Point Grease Lubricator

The Alemlube RF40 Spring Operated Single Point Grease Lubricator is a refillable lubricator with 220cc capacity that accurately facilitates continuous greasing in a simple and economical fashion.

The RF40 has been designed to provide constant on demand lubrication to bearings, bushings, joints, articulated joints, electric motors, compressors, pumps, valves, reduction units, cranes, mills, ovens, conveyor belts, rolling presses, Archimedean screws, vibrating screens, lifts, elevators, presses, rolling mills, fans and turbines or wherever constant greasing is required to keep your plant and equipment in full working order.

An incremental setting dial allows the user to set the dispensing rate at either 1, 3, 6 or 12 months to suit specific machinery or equipment requirements.

Compatible with NLGI 0, 1, 2 or 3 greases, the Alemlube RF40 spring operated single point grease lubricator is manufactured with UV stable, impact resistant Lexan® and can be mounted in any orientation.

Installation is possible indoors, outdoors, remotely, inversely, under water and in either dangerous or difficult to reach points.

Keeping lubrication constant the RF40 prevents solid matter accumulation, helps to avert production stops, expensive repairs and being environment friendly, the ability to be refilled multiple times avoids constant disposal expenses.



PRODUCT SPECIFICATIONS, FEATURES AND BENEFITS

- 220cc capacity
- On demand grease supply
- Easy & fast to refill multiple times
- Compatible with greases NLGI 0-1-2-3
- Lubricates bearings at preset intervals of 1, 3, 6 and 12 months
- No battery or gas required for operation
- High mechanical, chemical and thermal resistance
- Medium spring supplied as standard
- Optional light and strong springs to suit viscosity and temperature
- Can be mounted in any orientation
- M10 outlet thread
- Sturdy with an operating temperature range of -30°C to +132°C
- UV stable, impact resistant transparent bowl
- Overall dimensions of 185mm (H) x 77mm (W) (including nipple)

ORDERING INFORMATION

RF40 Spring Operated Single Point Grease Lubricator

