NSW (02) 9939 0711

QLD (07) 3204 9166

VIC/TAS (03) 8787 8288

WA (08) 9209 3066

SA/NT (08) 8241 7111

NZ (09) 447 1007



February 2015

AA40CF2P

Alemlube Automotive 2 Post Clear Floor 4t Hoist

The new AA40CF2P clear-floor 2 post 4t hoist allows for quick and easy under vehicle service operations. With fast lifting and lowering times this popular 2 post clear floor hoist design is ideal for both large or small automotive workshops. Large diameter lifting pads comfortably accommodate both large and small vehicles together with a maximum lifting height of 1,900mm and minimum lowered height of 100mm.

The AA40CF2P clear-floor 2 post 4t hoist uses standard economical 415 volt (3 phase) power with an optional 240 volt (single phase) power pack available. An optional 1 metre height extension kit is also available. Electric safety locks ensure operator protection and an aluminium motor provides improved cooling capacity during high work demands and low voltage controls provide additional operator safety. Quality components throughout, compliant with Australian standards and manufactured to European CE Standards.

PRODUCT SPECIFICATIONS, FEATURES AND BENEFITS

Standard height clearance of 3,900mm High lifting capacity of 4t Fast lifting time of 60 seconds Fast lowering time between 18 to 40 seconds Asymmetric lift arm design incorporating 2 and 3 stage arms with toe protection and automatic engaging safety arm locks Large diameter lifting pads comfortably accommodate large & small vehicles Maximum lifting height of 1,900mm Minimum lowered height of 100mm Electric safety lock operation Distance between columns: 2760mm Drive through width: 2640mm Standard economical 3 phase power with optional 240 volt power pack Aluminium motor for improved cooling capacity during high work demands Low voltage controls offer greater operator safety Quality components throughout
Fast lifting time of 60 seconds Fast lowering time between 18 to 40 seconds Asymmetric lift arm design incorporating 2 and 3 stage arms with toe protection and automatic engaging safety arm locks Large diameter lifting pads comfortably accommodate large & small vehicles Maximum lifting height of 1,900mm Minimum lowered height of 100mm Electric safety lock operation Distance between columns: 2760mm Drive through width: 2640mm Standard economical 3 phase power with optional 240 volt power pack Aluminium motor for improved cooling capacity during high work demands Low voltage controls offer greater operator safety
Fast lowering time between 18 to 40 seconds Asymmetric lift arm design incorporating 2 and 3 stage arms with toe protection and automatic engaging safety arm locks Large diameter lifting pads comfortably accommodate large & small vehicles Maximum lifting height of 1,900mm Minimum lowered height of 100mm Electric safety lock operation Distance between columns: 2760mm Drive through width: 2640mm Standard economical 3 phase power with optional 240 volt power pack Aluminium motor for improved cooling capacity during high work demands Low voltage controls offer greater operator safety
Asymmetric lift arm design incorporating 2 and 3 stage arms with toe protection and automatic engaging safety arm locks Large diameter lifting pads comfortably accommodate large & small vehicles Maximum lifting height of 1,900mm Minimum lowered height of 100mm Electric safety lock operation Distance between columns: 2760mm Drive through width: 2640mm Standard economical 3 phase power with optional 240 volt power pack Aluminium motor for improved cooling capacity during high work demands Low voltage controls offer greater operator safety
with toe protection and automatic engaging safety arm locks Large diameter lifting pads comfortably accommodate large & small vehicles Maximum lifting height of 1,900mm Minimum lowered height of 100mm Electric safety lock operation Distance between columns: 2760mm Drive through width: 2640mm Standard economical 3 phase power with optional 240 volt power pack Aluminium motor for improved cooling capacity during high work demands Low voltage controls offer greater operator safety
Maximum lifting height of 1,900mm Minimum lowered height of 100mm Electric safety lock operation Distance between columns: 2760mm Drive through width: 2640mm Standard economical 3 phase power with optional 240 volt power pack Aluminium motor for improved cooling capacity during high work demands Low voltage controls offer greater operator safety
Minimum lowered height of 100mm Electric safety lock operation Distance between columns: 2760mm Drive through width: 2640mm Standard economical 3 phase power with optional 240 volt power pack Aluminium motor for improved cooling capacity during high work demands Low voltage controls offer greater operator safety
Electric safety lock operation Distance between columns: 2760mm Drive through width: 2640mm Standard economical 3 phase power with optional 240 volt power pack Aluminium motor for improved cooling capacity during high work demands Low voltage controls offer greater operator safety
Distance between columns: 2760mm Drive through width: 2640mm Standard economical 3 phase power with optional 240 volt power pack Aluminium motor for improved cooling capacity during high work demands Low voltage controls offer greater operator safety
Drive through width: 2640mm Standard economical 3 phase power with optional 240 volt power pack Aluminium motor for improved cooling capacity during high work demands Low voltage controls offer greater operator safety
Standard economical 3 phase power with optional 240 volt power pack Aluminium motor for improved cooling capacity during high work demands Low voltage controls offer greater operator safety
Aluminium motor for improved cooling capacity during high work demands Low voltage controls offer greater operator safety
Low voltage controls offer greater operator safety
Quality components throughout
Australian WORKSAFE compliance: Design Registration Number: WAH 2095
Manufactured to stringent European CE Standards
Also Available AA40CF2P-240V Also Available AA40CF2PEH - with 1 metre height extension kit

ORDERING INFORMATION



AA40CF2P 2 Post Clear Floor 4t Hoist

